



ARTHROSCOPY AND SPORTS MEDICINE

6th EDITION 1/2017

Chapter			Pages
1	BASIC SETS	SET-ART	1-26
2	HOPKINS® TELESCOPES AND SHEATHS	ART-TEL, ART-S	27-42
3	HOSPITAL INSTRUMENTS	ART-INST	43-52
4	PUNCHES, FORCEPS AND SCISSORS	ART-ST	53-72
5	JOINT AND BONE RECONSTRUCTION	ART-CL	73-80
6	INSTRUMENTS FOR THE KNEE	ART-K	81-126
7	INSTRUMENTS FOR THE SHOULDER	ART-S	127-152
8	INSTRUMENTS FOR THE HIP	ART-H	153-162
9	INSTRUMENTS FOR SMALL AND MEDIUM JOINTS	ART-KG	163-180
10	INSTRUMENTS FOR RHEUMATOLOGY	ART-SM	181-186
11	SPINE SURGERY	see NEUROSURGERY catalog	
12	VISUALIZATION SYSTEMS FOR OPEN SURGERY AND MICROSURGERY	ART-VITOM	187-208
13	FULL HD IMAGING FOR OPERATING MICROSCOPES	ART-MICRO	209-216
14	HOLDING SYSTEMS FOR ARTHROSCOPY	ART-HS	217-220
15	TRAINING MODELS FOR ARTHROSCOPY	ART-TM	221-234
16	EXTRACORPOREAL SHOCK WAVE THERAPY (ESWT) IN ORTHOPEDICS	ART-ESWT	235-240
17	UNITS AND ACCESSORIES	ART-UNITS-INTRO, ART-UNITS	U 1-36
18	COMPONENTS, SPARE PARTS	ART-SP	SP 1-36
19	KARL STORZ OR1 NEO®, TELEPRESENCE HYGIENE, ENDOPROTECT1		

STORZ



THE WORLD OF ENDOSCOPY



Information on events is available on the KARL STORZ website
www.karlstorz.com

ARTHROSCOPY AND SPORTS MEDICINE

6th EDITION 1/2017

Important Notes:

It is recommended to check the suitability of the product for the intended procedure prior to use.

Endoscopes and accessories contained in this catalog have been designed in part with the cooperation of physicians and are manufactured by the KARL STORZ group. If subcontractors are hired to manufacture individual components, these are made according to proprietary KARL STORZ plans or drawings. Furthermore, these products are subject to strict quality and control guidelines of the KARL STORZ group. Both contractual and general legal provisions prohibit subcontractors from supplying components manufactured by order of KARL STORZ to competitors.

Any assumptions that competitors' endoscopes and accessories are acquired from the same suppliers as the KARL STORZ products are not correct. Moreover, endoscopes and instruments provided by competitors are not manufactured according to the design specifications of KARL STORZ. This means it cannot be assumed that these endoscopes and accessories – even if they look identical on the outside – are constructed in the same manner and have been tested according to the same criteria.

Standardized Design and Labeling

KARL STORZ participates both in national and international bodies involved in the development of standards for endoscopes and endoscopic accessories. Standardized design and development therefore have long been implemented consistently by KARL STORZ. The user can rest assured that all products by the KARL STORZ group have been designed and constructed not only in compliance with strict internal quality guidelines, but also with international standards. All data relevant for safe use, such as viewing direction, sizes and diameters, or notes regarding sterilization of telescopes, are applied to the instruments, have been formulated according to international standards, and therefore provide reliable information.

As we constantly seek to improve and modify our products, we reserve the right to make changes in design that vary from catalog descriptions.

Original or Counterfeit

KARL STORZ products are name brand articles renowned around the world and represent the state of the art in important areas of healthcare. A large number of “copy cat” products are currently being offered in many markets. These products are designed intentionally to resemble KARL STORZ products and use marketing strategies that at least point out their compatibility with KARL STORZ products. These products are by no means genuine products, since genuine KARL STORZ products are sold worldwide exclusively under the name of KARL STORZ, which appears on the packaging and the product. In the absence of such labeling, the product is not from KARL STORZ.

KARL STORZ, therefore, is unable to ensure that such products are actually compatible with genuine KARL STORZ products or can be used with them without injury to the patient.



BASIC SETS

UNITS2-6

KNEE JOINT7-16

SHOULDER JOINT17-20

HIP JOINT21-22

SMALL AND MEDIUM JOINTS23-26



Monitor:
9826 NB **26" FULL HD Monitor**

Camera System:
TC 200EN* **IMAGE1 S CONNECT™**, basic module
TC 300 **IMAGE1 S™ H3-LINK**, module for rigid endoscopy
TH 100 **IMAGE1 S™ H3-Z Three-Chip FULL HD Camera Head**

Alternative:
TC 301 **IMAGE1 S™ X-LINK**, module for flexible endoscopy
TH 110 **IMAGE1 S™ HX One-Chip FULL HD Camera Head**

Light Source:
20 1614 01-1 **Cold Light Fountain Power LED 175 SCB**
495 NAC **Fiber Optic Light Cable**

Documentation:
WD 250-EN* **AIDA™ with SMARTSCREEN®**
TC 009 **USB Adaptor**, for ACC 1 and ACC 2

Motor System:
28 7230 01-1 **UNIDRIVE® S III ARTHRO SCB**

HF Unit:
UH 400 **AUTOCON® III 400 High-End**
27805 **Neutral Electrode**
27806 UR **Neutral Electrode Connecting Cable**
UF 902 **Two-Pedal Footswitch**

Pump System:
28 3407 01-1 **ARTHROPUMP® Power**
Alternative:
UP 210 **ENDOMAT® SELECT**, roller pump
UP 605 **Arthroscopy Software**, license

Equipment Cart:
UG 220 **Equipment Cart, wide**
UG 500 **Monitor Holder**
29005 DFH **Footswitch Holder**, for two- and three-pedal footswitches
UG 310 **Isolation Transformer**
UG 410 **Earth Leakage Monitor**
UG 626 **IV Pole**, height-adjustable
Optional:
UG 606 **Keyboard Tray**, wide

* Available in the following languages: DE, ES, FR, IT, PT, RU, SE
Units see chapter 17, UNITS AND ACCESSORIES
FULL HD Camera Platform see TELEPRESENCE catalog
Basic Set for Units for Arthroscopy continued on next page

Units

Basic Sets

Imaging

9826 NB **26" FULL HD Monitor**, color systems PAL/NTSC, max. screen resolution 1920 x 1080, image format 16:9, video inputs: DVI, 3G-SDI, VGA, S-Video, Composite, video outputs: DVI, 3G-SDI, Composite, power supply 100 – 240 VAC, 50/60 Hz, 5 V output (1 A), wall mount with VESA 100 adaptor

20 1614 01-1 **Cold Light Fountain Power LED 175 SCB**, with integrated KARL STORZ-SCB, high-performance LED and one KARL STORZ light outlet, power supply 110 – 240 VAC, 50/60 Hz

optional

495 NAC **Fiber Optic Light Cable**, with straight connector, extremely heat-resistant, with safety lock, enhanced light transmission, can be used for ICG applications, diameter 3.5 mm, length 230 cm

TC 200EN **IMAGE1 S CONNECT™**, connect module, for use with up to 3 link modules, resolution 1920 x 1080 pixels, with integrated KARL STORZ-SCB and digital Image Processing Module, power supply 100 – 120 VAC/200 – 240 VAC, 50/60 Hz

TC 300 **IMAGE1 S™ H3-LINK**, link module, for use with IMAGE1 FULL HD three-chip camera heads, power supply 100 – 120 VAC/200 – 240 VAC, 50/60 Hz, for use with IMAGE1 S CONNECT™ TC 200EN

TH 100 **IMAGE1 S™ H3-Z Three-Chip FULL HD Camera Head**, S-Technologies available, progressive scan, soakable, gas- and plasma-sterilizable, with integrated Parfocal Zoom Lens, focal length f = 15 – 31 mm (2x), 2 freely programmable camera head buttons, for use with IMAGE1 S and IMAGE 1 HUB™ HD/IMAGE1 HD

Documentation

WD 250-EN **AIDA™**, documentation system for recording still images and videos, dual channel up to FULL HD, 2D/3D, including SMARTSCREEN® (touch screen), power supply 100 – 240 VAC, 50/60 Hz

TC 009 **USB Adaptor**, for ACC 1 and ACC 2, for use in conjunction with IMAGE1 S CONNECT™ and AIDA™ HD

optional

TC 301 **IMAGE1 S™ X-LINK**, link module, for use with flexible video endoscopes and one-chip camera heads (up to FULL HD), power supply 100 – 120 VAC/200 – 240 VAC, 50/60 Hz, for use with IMAGE1 S CONNECT™ TC 200EN

UNIDRIVE® S III ARTHRO SCB Motor System

28 7230 01-1 **UNIDRIVE® S III ARTHRO SCB**, with color display, touch screen operation, two motor outputs, with integrated SCB module, power supply 100 – 120/230 – 240 VAC, 50/60 Hz including:

SCB Connecting Cable, length 100 cm

Mains Cord

20 0168 31 **Two-Pedal Footswitch**, for use with UNIDRIVE® S III ARTHRO SCB

optional

20 0128 32 **Three-Pedal Footswitch**, for use with UNIDRIVE® S III ARTHRO SCB

Recommended Handpieces and Accessories for UNIDRIVE® S III ARTHRO

28200 DX **DRILLCUT-X® ARTHRO Shaver Handpiece**, up to 8000 rpm, for use with UNIDRIVE® S III ARTHRO SCB, as of software status 1.10.

28 7210 36 **Multifunction Handpiece**, for use with UNIDRIVE® S III ARTHRO SCB

28 7210 37 **Jacobs Chuck**, up to diameter 6.5 mm

28 7210 39 **Sagittal Saw Attachment**, keyless, with tilt lever, for use with Multifunction Handpiece 28 7210 36 and Saw Blades 28207 SLA – SLH

28 7210 33 **Pin Driver**, for drilling wires diameter 1.5 – 3 mm

28 7210 34 **Pin Driver**, for Synthes attachments

Recommended Shaver Blades, sterile, for single use, package of 6, for use with UNIDRIVE® S III ARTHRO SCB in combination with the DRILLCUT® X ARTHRO handpiece

Working length 180 mm

- 28208 BKS **Aggressive Cutter**, diameter 4.5 mm, color code: green
- 28208 EHS **Curved Aggressive Full Radius Resector**, diameter 4.5 mm, color code: light green
- 28208 IDS **Semi Hooded Barrel Burr**, diameter 5.5 mm, color code: pink

Working length 120 mm

- 28205 DKS **Aggressive Full Radius Resector**, diameter 4.5 mm, color code: blue
- 28205 FDS **Round Burr**, diameter 5.5 mm, color code: orange
- 28205 GES **Finish Barrel Burr**, diameter 5.5 mm, color code: purple
- 28205 HDS **Aggressive Barrel Burr**, diameter 5.5 mm, color code: pink
- 28205 MKS **Pro Line Shaver Blade**, diameter 4.5 mm, color code: pink
- 28205 NKS **Aggressive Pro Line Shaver Blade**, diameter 4.5 mm, color code: light blue

Working length 70 mm

- 28206 CAS **Full Radius Resector**, diameter 2.5 mm, color code: yellow
- 28206 FAS **Small Joint Burr**, diameter 2.5 mm, color code: orange

optional

- 5x 28205 SAA **Irrigation Adaptor**, for validated cleaning of outer blades
- 5x 28205 SAI **Irrigation Adaptor**, for validated cleaning of outer blades

ARTHROPUMP® Power Suction and Irrigation System

- 283407 01-1 **ARTHROPUMP® Power**, power supply 100 – 240 VAC, 50/60 Hz including:
 - Connecting Cable**, to UNIDRIVE® S III ARTHRO SCB
 - SCB Connecting Cable**, length 100 cm
 - Four-Pedal Footswitch**
 - Tubing Set Irrigation**, sterile, for single use, package of 3
 - Tubing Set Suction**, sterile, for single use, package of 3

optional

- UP 210 **ENDOMAT® SELECT**

Equipment Carts and Accessories

- UG 220 **Equipment Cart**, wide, tall, rides on 4 antistatic dual wheels equipped with locking brakes, mains switch on cover, energy beam with integrated electrical subdistributors with 12 sockets, grounding plugs, Dimensions: Equipment cart: 830 x 1474 x 730 mm (w x h x d), Shelf: 630 x 25 x 510 mm (w x h x d), Caster diameter: 150 mm
- UG 310 **Isolation Transformer**, 200 – 240 V, 2000 VA, with 3 special mains sockets, automatic cutout, 3 grounding plugs, dimensions in mm: 330 x 90 x 495 (w x h x d), for use with Equipment Cart UG 220
- UG 410 **Earth Leakage Monitor**, 200 – 240 V, for mounting to equipment carts, control panel dimensions: 44 x 80 x 29 mm (w x h x d), for use with Isolation Transformer UG 310
- UG 500 **Monitor Holder**, height adjustable, swiveling and tilting, central mount, swivel range approx. 360°, loading capacity max. 18 kg, with monitor mount VESA 75/100, for use with Equipment Cart UG 220
- UG 626 **IV Pole**, height adjustable, with 2 bottle hooks à 5 kg, length 118 – 203 cm, for use with Equipment Cart UG 220 including:
 - Multifunctional Holder**

optional

- UG 606 **Keyboard Tray**, wide, for mounting under wide Shelf UG 604, load capacity max. 10 kg, dimensions: 630 x 480 mm (w x d), for use with Equipment Cart UG 220

Basic Set for Units for Arthroscopy continued on next page

Units

Basic Sets

HF Units

UH 400	AUTOCON® III 400 High-End , with KARL STORZ SCB control NEO, power supply 220 – 240 VAC, 50/60 Hz
27805	Neutral Electrode , of conductive silicone with 2 rubber ties for fastening, contact surface A = 500 cm ² , for use with Connecting Cable 27806
27806	Neutral Electrode Connecting Cable , for Neutral Electrodes 27805 and 860021 E, length 400 cm
UF 902	Two-Pedal Footswitch , with button for switchover function, for use with HF generators
UF 901	One-Pedal Footswitch , with button for switchover function, for use with HF generators

Recommended Accessories

26 5200 45	High Frequency Cable , for Electrode Handle 26 5200 43, length 400 cm
26 5200 43	Electrode Handle , with 2 buttons for activating the unipolar generator, yellow button: unipolar cutting, blue button: unipolar coagulation, High Frequency Cord 26 5200 45 required
28801 EF	Arthroscopy HF Hook Electrode , diameter 2.6 mm, electrode length 2.8 mm, working length 6 cm, sterile, for single use, package of 5
28801 EG	Arthroscopy HF Hook Electrode , diameter 2.6 mm, electrode length 2.8 mm, working length 11 cm, sterile, for single use, package of 5
28801 EH	Arthroscopy HF Hook Electrode , diameter 2.6 mm, electrode length 4 mm, working length 11 cm, sterile, for single use, package of 5
28801 EA	Arthroscopy HF Ball Electrode , diameter 2.6 mm, ball diameter 2.5 mm, working length 6 cm, sterile, for single use, package of 5
28801 EB	Arthroscopy HF Ball Electrode , diameter 2.6 mm, ball diameter 2.5 mm, working length 11 cm, sterile, for single use, package of 5
28801 EC	Arthroscopy HF Ball Electrode , diameter 2.6 mm, ball diameter 3.5 mm, working length 6 cm, sterile, for single use, package of 5
28801 ED	Arthroscopy HF Ball Electrode , diameter 2.6 mm, ball diameter 3.5 mm, working length 11 cm, sterile, for single use, package of 5

VITOM® 2D – 2D Visualization System for Open Surgery with Minimal Access

209160 25 AA	VITOM® Telescope 0° with Integrated Illuminator , VITOM® HOPKINS® straight forward telescope 0°, working distance 25 – 75 cm, length 11 cm, autoclavable , with fiber optic light transmission incorporated and condensor lenses, color code: green
optional 209160 25 DA	VITOM® Telescope 90° with Integrated Illuminator , VITOM® HOPKINS® telescope 90°, working distance 25 – 75 cm, length 11 cm, autoclavable , with fiber optic light transmission incorporated and condensor lenses, color code: blue
TL 300 TH 100	Cold Light Fountain Power LED 300 , with KARL STORZ-SCB and high-performance LED IMAGE1 S™ H3-Z Three-Chip FULL HD Camera Head , S-Technologies available, progressive scan, soakable, gas- and plasma-sterilizable, with integrated Parfocal Zoom Lens, focal length f = 15 – 31 mm (2x), 2 freely programmable camera head buttons, for use with IMAGE1 S™ and IMAGE 1 HUB™ HD
TC 200EN	IMAGE1 S CONNECT™ , connect module, for use with up to 3 link modules, resolution 1920 x 1080 pixels, with integrated KARL STORZ-SCB and digital Image Processing Module, power supply 100 – 120 VAC/200 – 240 VAC, 50/60 Hz
TC 300	IMAGE1 S™ H3-LINK , link module, for use with IMAGE1 FULL HD three-chip camera heads, power supply 100 – 120 VAC/200 – 240 VAC, 50/60 Hz, for use with IMAGE1 S CONNECT™ TC 200EN
9826 NB	26" FULL HD Monitor , color systems PAL/NTSC, max. screen resolution 1920 x 1080, image format 16:9, video inputs: DVI, 3G-SDI, VGA, S-Video, Composite, video outputs: DVI, 3G-SDI, Composite, power supply 100 – 240 VAC, 50/60 Hz, 5 V output (1 A), wall mount with VESA 100 adaptor
495 TIP	Fiber Optic Light Cable , with straight connector, extremely heat-resistant, enhanced light transmission, diameter 4.8 mm, length 300 cm
39501 A2	Wire Tray for Cleaning, Sterilization and Storage of two rigid endoscopes and one light cable, including holder for light post adaptors, silicone telescope holders and lid, external dimensions (w x d x h): 352 x 125 x 54 mm, for rigid endoscopes up to diameter 10 mm and working length 20 cm
28272 HC	Articulated Stand , L-shaped, long, reinforced version, especially large swivel range, with one mechanical central clamp for all five joint functions, height 48 cm, swivel range 66 cm, with quick release coupling KSLOCK (female)
28172 HR	Rotation Socket , to clamp to the operating table, with one mounted Butterfly Nut 28172 HRS, for European and US standard rails, with lateral clamp for height and angle adjustment of the articulated stand
28272 UGK	Clamping Jaw , with ball joint, large, clamping range 16.5 to 23 mm, with quick release coupling KSLOCK (male), for use with all square-headed KARL STORZ HOPKINS® telescopes
28172 HM	Extension Rod , 50 cm, with lateral clamp for height adjustment of the articulated stand, for use with Articulated Stands 28272 HA/HB/HC and Sockets 28172 HK/HR
28272 CN	Clamping Cylinder , folding, for flexible mounting of 10 mm telescopes to telescope sheath, autoclavable . The clamping cylinder allows vertical movement and rotation of the telescope.

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Knee Joint

Basic Sets

28731 BWA	HOPKINS® Wide Angle Forward-Oblique Telescope 30° , enlarged view, diameter 4 mm, length 18 cm, autoclavable , fiber optic light transmission incorporated, color code: red
28136 CR	High-Flow Arthroscope Sheath , with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, two stopcocks, rotatable, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, color code: red
28126 BT	Obturator , semisharp, for use with Arthroscope Sheaths 28229 DR, 28129 CR, 28126 CR/R/B, 28136 CR, 28135 CR and 28136 EC, color code: green-red-yellow
28145 LH	Probe , graduated, blunt, length of hook 5.5 mm, diameter 1.5 mm, working length 13 cm
28571 BB	SILCUT® PRO Punch , through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm
28571 AG	SILGRASP® PRO Alligator Grasping Forceps , straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm
28571 BBL	SILCUT® PRO Upbiter , through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, curved 15° to left and 10° curved upwards, handle with cleaning connector, working length 12 cm
28571 BBR	SILCUT® PRO Upbiter , through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, curved 15° to right and 10° curved upwards, handle with cleaning connector, working length 12 cm

Optional for 28731 BWA and 28136 CR

28731 AE	ENDOCAMELEON® ARTHRO HOPKINS® Telescope , diameter 4 mm, length 18 cm, autoclavable , variable direction of view from 15° – 90°, adjustment knob for selecting the desired direction of view, fiber optic light transmission incorporated, color code: gold
28136 EC	Arthroscope Sheath ENDOCAMELEON® , with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, distal tapered, with irrigation holes, two stopcocks, rotatable, for use with ENDOCAMELEON® ARTHRO HOPKINS® Telescope 28731 AE and Obturator 28134 O with cannulated handle or Obturators 28126 BC/BT

Pediatric Interventions

28719 BA	HOPKINS® Forward-Oblique Telescope 30° , diameter 2.7 mm, length 18 cm, autoclavable , fiber optic light transmission incorporated, color code: red
28132 CR	Arthroscope Sheath , with standard coupling mechanism, diameter 4 mm, working length 12.5 cm, two stopcocks, rotatable, for use with HOPKINS® telescope 30° and Obturator 28132 BC, color code: red-yellow
28132 BC	Obturator , blunt, for use with Arthroscope Sheath 28132 CR

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog
Basic Set for Arthroscopy of the Knee Joint continued on next page

Ligament Reconstruction

28729 SB	Tendon Board , including FLIPPTACK Retainer 28729 SC
28729 FK	Thread Clip
28729 P	Tissue Forceps , 1 x 2 teeth, medium, distal curved to left, length 14.5 cm
2x 28729 D-6	Drilling Wire , spiral shape, with eyelet, diameter 2.4 mm, length 38 cm, unsterile, for single use, package of 6, for use with Undercut Drills 28729 BA – BH, Collar Burrs 28729 BLC – BLF and Drills 28729 GA – GE
28729 E	Larding Wire , pyramidal tip, diameter 2.4 mm, length 32 cm, unsterile, for single use, package of 10, for use with Undercut Drills 28729 BA – BH, Collar Burrs BLC – BLF and Drills 28729 GA – GE
28729 BA	Undercut Drill , cannulated, diameter 4.5 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
28729 BB	Same , diameter 5 mm
28729 BI	Same , diameter 5.5 mm
28729 BC	Same , diameter 6 mm
28729 BK	Same , diameter 6.5 mm
28729 BD	Same , diameter 7 mm
28729 BL	Same , diameter 7.5 mm
28729 BE	Same , diameter 8 mm
28729 BM	Same , diameter 8.5 mm
28729 BF	Same , diameter 9 mm
28729 BN	Same , diameter 9.5 mm
28729 BG	Same , diameter 10 mm
28729 BO	Same , diameter 10.5 mm
28729 BH	Same , diameter 11 mm
28729 L	Length Gauge , for cruciate ligament reconstruction, graduated, working length 23 cm or
28729 TL	Depth Gauge , for cruciate ligament reconstruction, working length 22.5 cm, for use with Larding Wire 28729 E
28729 NO	Notch Chisel , curved, 15° downwards, working length 13 cm

Meniscus Suture

28179 HG	Handle , for use with monofilament threads size USP 2-0 to 2, for use with Suture Attachments 28179 PA – PH, 28728 NA – NG, Wheel Attachment 28179 HR and Wheel 28179 R
28179 HR	Wheel Attachment , for use with monofilament threads size USP 2-0 to 2, for use with Handle 28179 HG and Wheel 28179 R
28179 R	Wheel , for use with monofilament threads size USP 2-0 to 2, for use with Wheel Attachment 28179 HR
28728 NA	Suture Attachment , straight, working length 13 cm, for use with Handle 28179 HG
28728 NB	Suture Attachment , distal angled 180° to the right, straight, working length 13 cm, for use with Handle 28179 HG
28728 NC	Suture Attachment , distal angled 180° to the left, straight, working length 13 cm, for use with Handle 28179 HG
28728 ND	Suture Attachment , distal angled 360° to the right, straight, working length 13 cm, for use with Handle 28179 HG
28728 NE	Suture Attachment , distal angled 360° to the left, straight, working length 13 cm, for use with Handle 28179 HG
28728 NF	Suture Attachment , distal angled 20° upwards, straight, working length 13 cm, for use with Handle 28179 HG
28728 NG	Suture Attachment , distal angled 20° upwards, straight, working length 14 cm, for use with Handle 28179 HG
28728 NJ	Suture Grasper , dismantling, jaw length 5.5 mm, straight jaws, straight sheath, working length 8 cm

Meniscus Root Refixation

28729 ZRF	Target Guide Root Refixation , for refixation of the meniscus
28728 MH	HALF PIPE® , without handle, small, working length 95 mm
28572 NJ	SILGRASP® PRO Suture Grasper , straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Container for the Sterilization and Storage of Instruments see HYGIENE catalog

MPFL Reconstruction

MPFL Reconstruction with the Gracilis Tendon and BIOPLUG Suture Anchor

- 28729 A **Tendon Stripper**, graduated, diameter 5.5 mm, length 30 cm
- 28179 KB **Drill**, for preparation of the tunnel for BIOPLUG 2870411 BP, with laser marking for the depth of the drill hole, length 7 cm
- 28179 KI **Insertor**, with lateral thread guide and thread clip at the handle, working length 9 cm, for use with BIOPLUG 2870411 BP
- 2x 2870411 BP **BIOPLUG, bioresorbable suture anchor**, diameter 4.2 mm, length 11 mm, sterile, for single use, for use with Insertor 28179 TI or 28179 KI
- 28729 P **Tissue Forceps**, 1 x 2 teeth, medium, distal curved to left, length 14.5 cm
- 200400 **BEYER Rongeur**, slender, curved, length 17 cm
- 28729 D-6 **Drilling Wire**, spiral shape, with eyelet, diameter 2.4 mm, length 38 cm, unsterile, for single use, package of 6, for use with Undercut Drills 28729 BA – BH, Collar Burrs 28729 BLC – BLF and Drills 28729 GA – GE
- 28729 BE **Undercut Drill**, cannulated, diameter 8 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
- 28789 GW-6 **Nitinol Guide Wire**, diameter 1.1 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Screwdrivers 28789 SK, 28770 SK and 28760 SK
- 28770 SK **CROSSDRIVE® Screwdriver**, cannulated, size 7, for use with bioresorbable MEGA FIX® screws diameter 7 mm and Nitinol Guide Wires 28789 GW/KW
- 2870723 B **MEGA FIX® B**, bioresorbable interference screw, diameter 7 mm, length 23 mm, sterile, for single use
- 2x 801810 **LANGENBECK Retractor**, size 43 x 13 mm, length 21 cm
- 2x 786003 **Retractor**, sharp, 3 prongs, length 17 cm
- 2x 498400 **COTTLE Retractor**, narrow (standard model), length 14 cm

MPFL Reconstruction with the Gracilis Tendon and the Patellar Tunnel

- 28729 A **Tendon Stripper**, graduated, diameter 5.5 mm, length 30 cm
- 2x 28728 BLB **Drill**, for preparation of the tunnel for MPFL reconstruction, with penetration stop, diameter 4.5 mm, for use with Gauge 28728 BL
- 2870723 B **MEGA FIX® B**, bioresorbable interference screw, diameter 7 mm, length 23 mm, sterile, for single use
- 28728 BL **Gauge**, for MPFL reconstruction, for use with Drill 28728 BLB
- 28729 BLK **Collar Burr**, tibial, diameter 6.5 mm, cannulated, collar diameter 8 mm at 43 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
- 28729 D-6 **Drilling Wire**, spiral shape, with eyelet, diameter 2.4 mm, length 38 cm, unsterile, for single use, package of 6, for use with Undercut Drills 28729 BA – BH, Collar Burrs 28729 BLC – BLF and Drills 28729 GA – GE
- 28729 BE **Undercut Drill**, cannulated, diameter 8 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
- 28789 GW-6 **Nitinol Guide Wire**, diameter 1.1 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Screwdrivers 28789 SK, 28770 SK and 28760 SK
- 28770 SK **CROSSDRIVE® Screwdriver**, cannulated, size 7, for use with bioresorbable MEGA FIX® screws diameter 7 mm and Nitinol Guide Wires 28789 GW/KW

MPFL Reconstruction with the Quadriceps Tendon

- 28185 QS **Quadriceps Tendon Cutter**, for subcutaneous terminal cutting of the quadriceps tendon, working length 15 cm
- 2x 28185 MH **Handle**, working length 10 cm, for use with Quadriceps Tendon Knives 28185 FA – FF and Quadriceps Tendon Separators 28185 EA – EC
- 3x 28185 FA **Tendon Knife**, for removal of quadriceps tendon for MPFL reconstruction, vertical parallel cutting, width 10 mm, height 4 mm, sterile, for single use, for use with Handle 28185 MH
- 3x 28185 FB **Same**, width 12 mm
- 3x 28185 EA **Tendon Separator**, for removal of the quadriceps tendon for MPFL reconstruction, horizontal parallel cutting, height 2 mm, sterile, for single use, for use with Handle 28185 MH
- 3x 28185 EB **Same**, height 3 mm
- 28729 D-6 **Drilling Wire**, spiral shape, with eyelet, diameter 2.4 mm, length 38 cm, unsterile, for single use, package of 6, for use with Undercut Drills 28729 BA – BH, Collar Burrs 28729 BLC – BLF and Drills 28729 GA – GE
- 28729 BE **Undercut Drill**, cannulated, diameter 8 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
- 28789 GW-6 **Nitinol Guide Wire**, diameter 1.1 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Screwdrivers 28789 SK, 28770 SK and 28760 SK
- 28770 SK **CROSSDRIVE® Screwdriver**, cannulated, size 7, for use with bioresorbable MEGA FIX® screws diameter 7 mm and Nitinol Guide Wires 28789 GW/KW
- 2870723 B **MEGA FIX® B**, bioresorbable interference screw, diameter 7 mm, length 23 mm, sterile, for single use

Cruciate Ligament Reconstruction

Basic Instruments for Anterior Cruciate Ligament Reconstruction

28729 WZ	Femoral Target Guide Attachment , for ACL reconstruction via a medial port, with 7 mm offset, for use with Handle 28729 ZG
28729 VX	Same , with 8 mm offset
28729 VY	Same , with 9 mm offset
28729 VZ	Same , with 10 mm offset
28729 ZG	Handle , with ratchet, for use with Inserts 28729 VX – VZ, WA – WD, WU – WZ, ZM – ZQ

Additional Instruments for Anterior Cruciate Ligament Reconstruction with Hamstrings, single bundle technique

28729 AC	Open Tendon Stripper , graduated, diameter 7.5 mm, length 30 cm or
28729 AB	Tendon Stripper , graduated, diameter 7 mm, length 30 cm
28729 SH	Tendon Hook
213008	PLESTER Raspatory , width 8 mm, length 18 cm
28729 ZA	Tibial Target Guide , for ACL reconstruction
28729 SE	Tendon Thickness Tester , for determination of tendon thickness size 7 – 12 mm at intervals of 0.5 mm

Additional Instruments for Anterior Cruciate Ligament Reconstruction with Hamstrings, double bundle technique

28729 AC	Open Tendon Stripper , graduated, diameter 7.5 mm, length 30 cm or
28729 AB	Tendon Stripper , graduated, diameter 7 mm, length 30 cm
28729 SH	Tendon Hook
213008	PLESTER Raspatory , width 8 mm, length 18 cm
28729 WU	Femoral Target Guide Attachment , for the ACL double bundle technique, with 8 mm offset, for use with Handle 28729 ZG
28729 WV	Same , with 9 mm offset
28729 WW	Same , with 10 mm offset
28729 WT	Tibial Target Guide , for the ACL double bundle technique, exit point from the tibial plateau adjustable between 8 – 10 mm
28729 SBD	Tendon Board Add-on , for the double bundle retainer technique, including FLIPPTACK Retainer 28729 SC
28729 SD	Tendon Thickness Tester , for determination of tendon thickness size 4 – 7 mm at intervals of 0.5 mm

Additional Instruments for Anterior Cruciate Ligament Reconstruction with the Quadriceps Tendon

28185 QS	Quadriceps Tendon Cutter , for subcutaneous terminal cutting of the quadriceps tendon, working length 15 cm
2x 28185 MH	Handle , working length 10 cm, for use with Quadriceps Tendon Knives 28185 FA – FF and Quadriceps Tendon Separators 28185 EA – EC
3x 28185 FC	Tendon Knife , for removal of the quadriceps tendon for cruciate ligament reconstruction, vertical parallel cutting, width 8 mm, height 6 mm, sterile, for single use, for use with Handle 28185 MH
3x 28185 FD	Same , width 9 mm
3x 28185 FE	Same , width 10 mm
5x 28185 EC	Tendon Separator , for removal of the quadriceps tendon for cruciate ligament reconstruction, horizontal parallel cutting, height 5 mm, sterile, for single use, for use with Handle 28185 MH
28729 CF	Tibial Target Guide , for the placement of a maximum of 3 parallel drilling wires
28185 GA	Rasp , femoral, cannulated, straight, coarse, one side smooth, width 8 mm, height 5 mm, working length 15 cm
28185 GB	Same , width 10 mm
28185 HA	Dilator , rectangular, femoral, cannulated, width 8 mm, height 5 mm, working length 15 cm
28185 HB	Same , width 9 mm
28185 HC	Same , width 10 mm
28185 HD	Same , width 12 mm
28185 IA	Dilator , rectangular, tibial, cannulated, width 8.5 mm, height 5.5 mm, working length 15 cm
28185 IB	Same , width 9.5 mm
28185 IC	Same , width 10.5 mm
28185 ID	Same , width 12.5 mm
28185 MB	Tendon Thickness Tester , for determining the thickness of the quadriceps tendon
174800	Metal Mallet , with plastic replacement head, length 22.5 cm

Additional Instruments for Anterior Cruciate Ligament Reconstruction with the Patellar Tunnel

28729 PC	Patellar Saw Template , for harvesting a bone block with tendon (BTB), width 7 mm
28729 PD	Same , width 8 mm
28729 PE	Same , width 9 mm
28729 PF	Same , width 10 mm
28729 PG	Same , width 11 mm
28729 PL	Coring Reamer , for harvesting a bone block with tendon (BTB), with coil, diameter 7 mm, for use with Handle 28729 PQ
28729 PM	Same , diameter 8 mm
28729 PN	Same , diameter 9 mm
28729 PO	Same , diameter 10 mm
28729 PP	Same , diameter 11 mm
28729 PQ	Handle , T-shaped, for use with Fluted Coring Reamers 28729 PL – PP and Revision Blades 28728 TA – TI
2x 28729 PJ	Bone Block Holder , for use with Tendon Board 28729 SB
28729 PH	Measuring Block , to determine the size of a bone block
28729 PK	Bone Forceps , for use with Measuring Block 28729 PH
28729 PA	Chisel , width 8 mm
28729 PB	Tendon Knife , blunt

Instruments for Posterior Cruciate Ligament Reconstruction

28729 AH	Awl , for PCL reconstruction, working length 20 cm
28729 R	Raspatory , for PCL reconstruction, working length 13 cm
28729 ZG	Handle , with ratchet, for use with Inserts 28729 VX – VZ, WA – WD, WU – WZ, ZM – ZQ
28729 WA	Femoral Target Guide Attachment , for PCL reconstruction, for use through the anterolateral port, for precise anatomic placement of the femoral tunnel, 4 locking positions, for drill diameter 7 mm, for use with Handle 28729 ZG
28729 WB	Same , for drill diameter 8 mm
28729 WC	Same , for drill diameter 9 mm
28729 WD	Same , for drill diameter 10 mm
28729 EH	Elevator , for PCL reconstruction, working length 15.5 cm
28729 ZB	Tibial Target Guide , for PCL reconstruction
28729 ZL	Same , curved to left
28729 ZR	Same , curved to right
28171 KBN	SILGRASP® Grasping Forceps , spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm
28124 BX	Changing Rod , length 23 cm, for use with arthroscopy sheaths with inner diameter 4 mm

optional

Cannulated Drills and Drill Sleeves

28729 GA	Drill , cannulated, diameter 6 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
28729 GB	Same , diameter 7 mm
28729 GC	Same , diameter 8 mm
28729 GD	Same , diameter 9 mm
28729 GE	Same , diameter 10 mm
28729 HA	Cannulated Drill Sleeve , for use with Drill 28729 GA
28729 HB	Cannulated Drill Sleeve , for use with Drill 28729 GB
28729 HC	Cannulated Drill Sleeve , for use with Drill 28729 GC
28729 HD	Cannulated Drill Sleeve , for use with Drill 28729 GD
28729 HE	Cannulated Drill Sleeve , for use with Drill 28729 GE

Cruciate Ligament Revision

Revision Screwdriver Set for Removing Titanium Interference Screws

28728 T **Revision Set**

Instruments for Bone Block Harvesting

28729 HGA	Sleeve , inner diameter 5 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPA, color code: green
28729 HGB	Sleeve , inner diameter 6 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPB, color code: black
28729 HGC	Sleeve , inner diameter 7 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPC, color code: blue
28729 HGD	Sleeve , inner diameter 8 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPD, color code: red
28729 HGE	Sleeve , inner diameter 9 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPE, color code: yellow
28729 HGF	Sleeve , inner diameter 10 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPF, color code: white-yellow
28729 HGG	Sleeve , inner diameter 11 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPG, color code: white-green
28729 HGH	Sleeve , inner diameter 12 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPH, color code: white-blue
28729 HH	Handle , for use with Tap 28729 HP
28729 HP	Tap , for use with Handle 28729 HH
28729 HPA	Tappet , diameter 5 mm, for use with Handle 28729 HH and Sleeve 28729 HGA, color code: green
28729 HPB	Tappet , diameter 6 mm, for use with Handle 28729 HH and Sleeve 28729 HGB, color code: black
28729 HPC	Tappet , diameter 7 mm, for use with Handle 28729 HH and Sleeve 28729 HGC, color code: blue
28729 HPD	Tappet , diameter 8 mm, for use with Handle 28729 HH and Sleeve 28729 HGD, color code: red
28729 HPE	Tappet , diameter 9 mm, for use with Handle 28729 HH and Sleeve 28729 HGE, color code: yellow
28729 HPF	Tappet , diameter 10 mm, for use with Handle 28729 HH and Sleeve 28729 HGF, color code: white-yellow
28729 HPG	Tappet , diameter 11 mm, for use with Handle 28729 HH and Sleeve 28729 HGG, color code: white-green
28729 HPH	Tappet , diameter 12 mm, for use with Handle 28729 HH and Sleeve 28729 HGH, color code: white-blue
174800	Metal Mallet , with plastic replacement head, length 22.5 cm

Cancellous Bone Applicator Set for Filling Bone Defects

28906 CB	Cancellous Bone Applicator Set , diameter 6 mm, color code: red including: Cancellous Bone Applicator Tappet Sealing Cap Plug
28907 CB	Same , diameter 7 mm, color code: yellow
28908 CB	Same , diameter 8 mm, color code: blue
28909 CB	Same , diameter 9 mm, color code: green
28910 CB	Same , diameter 10 mm, color code: white

Fine Tunnel Preparation

28960 B	Blade Dilator , cannulated, diameter 6 mm, working length 14.5 cm, scaled to 70 mm, for compression of the tibial and femoral cancellous bone, for use with Handle 28900 H
28960 BB	Same , diameter 6.5 mm
28960 C	Same , diameter 7 mm
28960 CC	Same , diameter 7.5 mm
28960 D	Same , diameter 8 mm
28960 DD	Same , diameter 8.5 mm
28960 E	Same , diameter 9 mm
28960 EE	Same , diameter 9.5 mm
28960 F	Same , diameter 10 mm
28960 FF	Same , diameter 10.5 mm
28960 G	Same , diameter 11 mm
28900 CP	Center Punch , straight, with pyramidal tip, working length 14.5 cm, for use with Handle 28900 H
28900 H	Handle , T-shaped, with quick coupling system, for use with Blade Dilators 28970 B/BB/C/CC/D/DD/E/EE/F/FF/G and Center Punch 28900 CP
28729 N	Notcher , with fin-like blade to assist screw insertion, working length 15 cm
28729 NM	Chisel , for creating a bone wedge, working length 13 cm
28729 NN	Chisel , for creating a bone wedge, with wide handle, working length 13 cm

optional

Dilators with Fin

28729 DFM	Dilator with Fin , for dilating the femoral drill channel to diameter 4 mm and simultaneous placement of a notch 17 mm in length
28729 DFO	Dilator with Fin , cannulated, for dilating the femoral drill channel to diameter 6 mm and simultaneous placement of a notch 25 mm in length
28729 DFP	Same , for dilating the femoral drill channel to diameter 6.5 mm
28729 DFQ	Same , for dilating the femoral drill channel to diameter 7 mm
28729 DFR	Same , for dilating the femoral drill channel to diameter 7.5 mm
28729 DFS	Same , for dilating the femoral drill channel to diameter 8 mm
28729 DFT	Same , for dilating the femoral drill channel to diameter 8.5 mm
28729 DFU	Same , for dilating the femoral drill channel to diameter 9 mm
28729 DFV	Same , for dilating the femoral drill channel to diameter 9.5 mm

Implants

Extracortical Fixation with Fixation Buttons

Implants for Single Bundle Technique

28729 FT	FLIPPTACK , extracortical fixation button, 4 x 12 mm, sterile, for single use
28729 FC	Catgut Polyester-S white , 3 x 75 cm, USP 7, sterile, for single use, package of 24, for use with FLIPPTACK, extracortical fixation button
28729 TT	ENDOTACK® , tibial fixation button, 10 x 16 mm, sterile, for single use
28729 MS	Button Wrench , for use with ENDOTACK® 28729 TT
28729 ST	Positioning Device , for use with ENDOTACK® 28729 TT
28729 KK	Knot Holder , small, 1 x 1 mm, working length 14.5 cm
28729 TM	Tensiometer , for measuring and controlling the tension of the graft

Implants for Double Bundle Technique

2x 28729 FT	FLIPPTACK , extracortical fixation button, 4 x 12 mm, sterile, for single use
28729 FC	Catgut Polyester-S white , 3 x 75 cm, USP 7, sterile, for single use, package of 24, for use with FLIPPTACK, extracortical fixation button
2x 28729 MT	Mini ENDOTACK® , tibial fixation button, 8 x 12 mm, sterile, for single use
28729 SM	Positioning Device , for use with Mini ENDOTACK® 28729 MT, color code: red
28729 MM	Button Wrench , for use with Mini ENDOTACK® 28729 MT, color code: red
28729 KK	Knot Holder , small, 1 x 1 mm, working length 14.5 cm
28729 TM	Tensiometer , for measuring and controlling the tension of the graft

Interference Screws

Fixation near the Joint with Bioresorbable MEGA FIX® Interference Screws

28789 SK	CROSSDRIVE® Screwdriver , cannulated, size 8 – 11, for use with bioresorbable MEGA FIX® screws diameter 8 – 11 mm
28770 SK	CROSSDRIVE® Screwdriver , cannulated, size 7, for use with bioresorbable MEGA FIX® screws diameter 7 mm
28760 SK	CROSSDRIVE® Screwdriver , cannulated, size 6, for use with bioresorbable MEGA FIX® screws diameter 6 mm
28789 GW-6	Nitinol Guide Wire , diameter 1.1 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® 28789 SK, 28770 SK and 28760 SK

Fixation near the Joint with MEGA FIX® Titanium Interference Screws

28789 CD	CROSSDRIVE® Plus Screwdriver , cannulated, for use with MEGA FIX® titanium interference screws and Nitinol Guide Wire 28789 FW
28789 FW-6	Nitinol Guide Wire , diameter 2 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Plus Screwdriver 28789 CD

Hybrid Fixation

Fixation near the Joint with Bioresorbable MEGASHIM as Hybrid Fixation

28728 DS	Dilator , graduated, diameter 4 mm, working length 15 cm, for use with MEGASHIM 6x20 2870620 MSP and MEGASHIM 7x20 2870720 MSP
28728 DL	Dilator , graduated, diameter 5 mm, working length 15 cm, for use with MEGASHIM 8x20 2870820 MSP and MEGASHIM 9x20 2870920 MSP
28767 E	Applicator , distal marking at 2 mm and 4 mm, with strike plate, working length 15 cm, for use with MEGASHIM 6x20 2870620 MSP and MEGASHIM 7x20 2870720 MSP
28789 EK	Applicator , cannulated, distal marking at 2 and 4 mm, with strike plate, working length 15 cm, for use with MEGASHIM 8x20 2870820 MSP and MEGASHIM 9x20 2870920 MSP
28767 C	Pusher , distal marking at 2 and 4 mm, working length 15 cm, for use with MEGASHIM 6x20 2870620 MSP and MEGASHIM 7x20 2870720 MSP
28789 C	Pusher , distal marking at 2 and 4 mm, working length 15 cm, for use with MEGASHIM 8x20 2870820 MSP and MEGASHIM 9x20 2870920 MSP
28728 SH	HALF PIPE® , without handle, short, working length 85 mm
28789 GW-6	Nitinol Guide Wire , diameter 1.1 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Screwdrivers 28789 SK, 28770 SK and 28760 SK

MEGA FIX® Screws and MEGASHIM see pages 117-125

Shoulder Joint

Basic Sets

- 28731 BWA **HOPKINS® Wide Angle Forward-Oblique Telescope 30°**, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red
- 28130 CR **High-Flow Arthroscope Sheath**, with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, two stopcocks, rotatable, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28130 BC/BT, 28140 O, color code: red
- 28130 BC **Obturator**, blunt
- 28130 BT **Obturator**, semisharp
- 28140 O **Obturator**, cannulated, with handle, diameter 4.8 mm
- 28270 T **Probe**, graduated, length of hook 2 mm, diameter 1.5 mm, working length 18 cm
- 28270 W **Changing Rod**, length 35 cm, for use with arthroscope sheaths with inner diameter 4 mm
- 28171 KPN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 19 cm
- 28171 KGN **SILGRASP® Foreign Body Grasper**, aggressive, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 19 cm
- 28171 SGN **SILGRASP® Suture Grasper**, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 14 cm

Optional for 28171 SGN

- 28171 SGL **SILGRASP® Suture Grasper**, curved jaws, 45° left, sheath diameter 3.5 mm, 5° curved to left, handle with cleaning connector, working length 16 cm
- 28171 SGR **Same**, 45° right, 5° curved to right

Optional for 28731 BWA

- 28731 AE **ENDOCAMELEON® ARTHRO HOPKINS® Telescope**, diameter 4 mm, length 18 cm, **autoclavable**, variable direction of view from 15° – 90°, adjustment knob for selecting the desired direction of view, fiber optic light transmission incorporated, color code: gold
- 28136 EC **Arthroscope Sheath ENDOCAMELEON®**, with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, distal tapered, with irrigation holes, two stopcocks, rotatable, for use with ENDOCAMELEON® ARTHRO HOPKINS® Telescope 28731 AE and Obturator 28134 O with cannulated handle or Obturators 28126 BC/BT
- 28126 BT **Obturator**, semisharp, for use with Arthroscope Sheaths 28229 DR, 28129 CR, 28126 CR/R/B, 28136 CR, 28135 CR and 28136 EC, color code: green-red-yellow

Portal Management System

- 28179 E **Basic Set for SPS – Secure Portal System**
including:
Puncture Needle
Obturator
Guide Wire, package of 6
Dilator
Handle, for Dilator 28179 DL
Valve Housing
- 28179 GS **Seal Set**, sterile, for single use, package of 10, for use with Valve Housing 28179 DG/OG
- 28179 GH **HALF PIPE®**, long, working length 95 mm, for use with Obturator 28179 OB
- 28179 EC **Dilator**, with integrated handle, long, diameter 6 mm, for use with threaded Cannula 28179 SB and Obturator 28179 EP
- 28179 EP **Obturator**, diameter 4 mm, for use with Dilator 28179 EC
- 28179 FC **Dilator**, with integrated handle, long, diameter 8.1 mm, for use with threaded Cannula 28179 SD and Obturator 28179 FP
- 28179 FP **Obturator**, diameter 4 mm, for use with Dilator 28179 FC
- 28179 SD-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6
- 28179 SB-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Reconstruction of the Shoulder Joint

28270 H	Mallet , ergonomic handle, two plane faces, length 17 cm, color code: blue
28179 KS	Bone Punch , for use with Titanium Suture Anchors 2870514 TI, 2870614 TI and 2870309 ST
28179 I	Thread Catcher , working length 15 cm
28179 KP	Knot Pusher , for sutures up to size USP 2, working length 18 cm
	or
2870356 KP	Knot Pusher and Suture Cutter , for cutting sutures up to size USP 2, working length 15 cm
2870356 SC	Suture Cutter , for cutting sutures up to size USP 2, working length 15 cm
28180 CB	Elevator , width 4 mm, curved 15° downwards, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm
28180 CC	Same , curved 30° downwards
28180 CF	Elevator , width 4 mm, curved 15° downwards, blade turned 180°, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm
28180 CJ	Same , curved 30° downwards
28180 CL	Rasp , for use as Glenoid or S.L.A.P. rasps, double-sided, width 4.5 mm, curved 30° downwards, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm
Optional Rasps for 28180 CL	
28180 CE	S.L.A.P. Rasp , width 4.5 mm, curved 30° downwards, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm
28180 DC	Glenoid Rasp , width 4.5 mm, curved 30° upwards, also curved upwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm
28180 GCN	SNAPPER® SHOULDER PRO® Suture Forceps , for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 15 cm, color code: blue
28180 GLN	SNAPPER® SHOULDER PRO® Suture Forceps , for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, curved to left, also curved to left in sheath, handle with cleaning connector, working length 15 cm, color code: red
28180 GRN	SNAPPER® SHOULDER PRO® Suture Forceps , for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, curved to right, also curved to right in sheath, handle with cleaning connector, working length 15 cm, color code: green
Optional SNAPPER® SHOULDER PRO® Suture Forceps	
28180 GAN	SNAPPER® SHOULDER PRO® Suture Forceps , for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, curved upwards, handle with cleaning connector, working length 15 cm, color code: black
28180 GRGN	SNAPPER® SHOULDER PRO® Suture Forceps , for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, retrograde opening, also curved upwards in sheath, handle with cleaning connector, working length 15 cm, color code: white
33136 P	CLICK'line® Handle , with thumb release, with 4 locking positions, for use with Suture Attachments 28180 LA/LC/LL/LR/LRG

Shoulder Joint

Basic Sets

Suture Instruments for the Rotator Cuff: SHOULDER PRO® Suture System

28179 HG	Handle , for use with monofilament threads size USP 2-0 to 2, for use with Suture Attachments 28179 PA – PH, 28728 NA – NG, Wheel Attachment 28179 HR and Wheel 28179 R
28179 HR	Wheel Attachment , for use with monofilament threads size USP 2-0 to 2, for use with Handle 28179 HG and Wheel 28179 R
28179 R	Wheel , for use with monofilament threads size USP 2-0 to 2, for use with Wheel Attachment 28179 HR
28180 BG	Suture Catcher , with inserter, sterile, for single use, package of 10, for use with Suture Attachments 28179 PA – PH and Handle 28179 HG
28179 PC	SHOULDER PRO® Suture Attachment , distal tip curved upwards, straight, 8 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 PG	SHOULDER PRO® Suture Attachment , distal tip angled 30° to right, straight, 8 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 PH	SHOULDER PRO® Suture Attachment , distal tip angled 30° to left, straight, 8 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 R1	Cleaning Adaptor , for use with Suture Attachments 28179 PA – PH and 28728 NA – NG
28179 R2	Cleaning Adaptor , for use with Handle 28179 HG

Optional Suture Attachments

28179 PA	SHOULDER PRO® Suture Attachment , distal tip curved upwards, straight, 5 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 PB	SHOULDER PRO® Suture Attachment , distal tip curved upwards, straight, 7 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 PD	SHOULDER PRO® Suture Attachment , hook-shaped distal tip curved upwards, straight, 8 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 PE	SHOULDER PRO® Suture Attachment , hook-shaped distal tip curved upwards, straight, 8.7 mm in height, working length 15 cm, for use with Handle 28179 HG
28179 PF	SHOULDER PRO® Suture Attachment , hook-shaped distal tip curved upwards, straight, 10 mm in height, working length 15 cm, for use with Handle 28179 HG

Suture Instruments for the Rotator Cuff and Labrum: WONDERHOOK®

28184 WH	WONDERHOOK® Handle, complete , for transporting monofilament threads up to size USP 1 including: Transport Cassette
28184 NG	WONDERHOOK® Suture Attachment , for use with monofilament threads up to size USP 1, straight, length of distal end 3.5 cm, working length 15 cm, for use with Handle 28184 WH, color code: blue
28184 NGL	Same , length of distal end 5 cm, long
28184 NA	WONDERHOOK® Suture Attachment , for use with monofilament threads up to size USP 1, distal tip slightly curved upwards, working length 15 cm, for use with Handle 28184 WH, color code: gold
28184 MR	WONDERHOOK® Suture Attachment , for use with monofilament threads up to size USP 1, distal tip curved 25° right, working length 15 cm, for use with Handle 28184 WH, color code: green
28184 ML	Same , distal tip curved 25° left
28184 NR	WONDERHOOK® Suture Attachment , for use with monofilament threads up to size USP 1, distally strongly curved to right, working length 15 cm, for use with Handle 28184 WH, color code: red
28184 NL	Same , distally strongly curved to right
28184 RA	Cleaning Adaptor , for use with WONDERHOOK® Suture Attachments 28184 ML/MR/NG/NGL/NA/NR/NL

Titanium Suture Anchor, pre-assembled, with MEGAFIBRE® sutures USP 2

- 2870309 ST **Titanium Suture Anchor**, diameter 3 mm, length 9 mm, with two MEGAFIBRE® sutures USP 2, pre-assembled, self-tapping, with inserter, sterile, for single use
- 2870514 TI **Titanium Suture Anchor**, diameter 5 mm, length 12.5 mm, with two MEGAFIBRE® sutures USP 2, pre-assembled, self-tapping, with inserter, sterile, for single use
- 2870614 TI **Titanium Suture Anchor**, diameter 6.5 mm, length 12.5 mm, with two MEGAFIBRE® sutures USP 2, pre-assembled, self-tapping, with inserter, sterile, for single use

Bioresorbable Suture Anchors

- 2870310 BP **BIOPLUG, bioresorbable suture anchor**, diameter 3.5 mm, length 10 mm, with one MEGAFIBRE® USP 2 suture preloaded, sterile, for single use, for use with Inserter 28179 TK
- 2870411 BP **BIOPLUG, bioresorbable suture anchor**, diameter 4.2 mm, length 11 mm, sterile, for single use, for use with Inserter 28179 TI or 28179 KI
- 2870514 BP **BIOPLUG, bioresorbable suture anchor**, diameter 5.2 mm, length 14 mm, sterile, for single use, for use with Inserter 28179 TI
- 28179 TC **Drill**, for preparation of the tunnel for BIOPLUG 2870514 BP, with laser marking for the depth of the drill hole, length 18 cm
- 28179 TB **Drill**, for preparation of the tunnel for BIOPLUG 2870411 BP, with laser marking for the depth of the drill hole, length 15 cm
- 28179 TD **Drill**, for preparation of the tunnel for BIOPLUG 2870310 BP, with laser marking for the depth of the drill hole, length 15 cm
- 28179 TI **Inserter**, with lateral thread guide and thread clip at the handle, working length 18 cm, for use with BIOPLUG 2870411 BP and 2870514 BP
- 28179 TK **Inserter**, with lateral thread guide and thread clip at the handle, working length 18 cm, for use with BIOPLUG 2870310 BP
- 28179 GG **Glenoid Guide**, working length 12.5 cm, for use with BIOPLUG 2870411 BP, 2870310 BP and Drills 28179 TB/TD

Combined Cutting and Grasping Instrument for Biceps Tenotomy or Tenodesis

- 28184 MSL **BITER®**, for the arthroscopic, terminal cutting of the biceps tendon, for the left shoulder, working length 15 cm
- 28184 MSR **Same**, for the right shoulder

Instrument Set for Minimally Invasive AC Joint Reconstruction

- 28379 S **MINAR®**, for minimally invasive AC joint repair including:
Target Guide
Bullet
FLIPPTACK Inserter
FLIPPTACK Inserter Rod
Suture Awl
Repositioner
- 28729 FC **Catgut Polyester-S white**, 3 x 75 cm, USP 7, sterile, for single use, package of 24, for use with FLIPPTACK, extracortical fixation button
- 2x 28729 FT **FLIPPTACK**, extracortical fixation button, 4 x 12 mm, sterile, for single use
- 28729 E **Larding Wire**, pyramidal tip, diameter 2.4 mm, length 32 cm, unsterile, for single use, package of 10, for use with Undercut Drills 28729 BA – BH, Collar Burrs BLC – BLF and Drills 28729 GA – GE
- 28729 BA **Undercut Drill**, cannulated, diameter 4.5 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E

Hip Joint

Basic Sets

28731 BWA	HOPKINS® Wide Angle Forward-Oblique Telescope 30° , enlarged view, diameter 4 mm, length 18 cm, autoclavable , fiber optic light transmission incorporated, color code: red
28731 CWA	HOPKINS® Wide Angle Lateral Telescope 70° , enlarged view, diameter 4 mm, length 18 cm, autoclavable , fiber optic light transmission incorporated, color code: yellow
28131 CR	High-Flow Arthroscope Sheath , with snap-in coupling mechanism, diameter 5.5 mm, working length 13.5 cm, two stopcocks, rotatable, for use HOPKINS® telescopes 0°, 30°, 70° and Obturators 28130 BC/BT, 28140 O, color code: blue
2x 28130 BC	Obturator , blunt, for use with Arthroscope Sheaths 28131 CR/R, 28130 CR/R, color code: green-red-yellow
28130 CR	High-Flow Arthroscope Sheath , with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, two stopcocks, rotatable, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28130 BC/BT, 28140 O, color code: red
28130 R	Same , one stopcock
2x 28140 D	Gasket Attachment , with cone, including Gasket 28140 GU, for use with all Arthroscope Sheaths
2x 28140 DB	Puncture Needle , outer diameter 2.1 mm, inner diameter 1.6 mm, working length 21.3 cm, for use with Guide Wire 28140 GW and Obturator 28140 DO
2x 28140 DO	Obturator , for use with Puncture Needle 28140 DB
28140 GU	Gasket , unsterile, for single use, package of 10, single-packaged, for use with Gasket Attachment 28140 D
28140 O	Obturator , cannulated, with handle, diameter 4.8 mm
28140 S	Evacuation Cannula , with LUER-Lock and one stopcock, working length 18 cm, for use with Arthroscope Sheaths 28130 CR/R and 28131 CR/R
28140 ZAA	Aimer , for use with Guide Sleeves 28140 ZBA/ZCA
28140 ZBA	Guide Sleeve , short, working length 10.5 cm, for use with Aimer 28140 ZAA
28140 ZCA	Guide Sleeve , long, working length 14.5 cm, for use with Aimer 28140 ZAA
28140 WK	Changing Rod , cannulated, diameter 4.8 mm, working length 31 cm, for use with Arthroscope Sheaths 28130 CR/R and 28131 CR/R as well as Nitinol Guide Wire 28140 GW
28140 GW-6	Nitinol Guide Wire , diameter 1.5 mm, length 40 cm, unsterile, for single use, package of 6
28140 HD	HALF PIPE® , for use in hip arthroscopy, handle rotated 90°, handle axis 120°, working length 95 mm
28140 HC	HALF PIPE® , for use in hip arthroscopy, handle rotated 90°, handle axis 120°, distal end flat, atraumatic tip, working length 120 mm
28140 CD	Microfracture Chisel , curved 30°, working length 18 cm
28140 CE	Microfracture Chisel , curved 70°, working length 18 cm
28140 CF	Microfracture Chisel , curved 90°, working length 16 cm
28140 LM	Knife , round, straight, working length 11.5 cm
28140 BM	Knife , round, angled 20°, working length 11.5 cm
28140 MG	Knife , pointed, curved, double-edged, working length 18 cm
28140 T	Probe , graduated, length of hook 3 mm, diameter 1.5 mm, working length 18 cm
28140 TB	Probe , graduated, length of hook 3 mm, angled downwards 20°, diameter 1.5 mm, working length 20 cm
28140 KE	Curette , oval, small, both sides cutting, curved, 20° upwards, working length 18 cm

Optional for 28731 CWA, 28131 CR and 28130 BC

28731 AE	ENDOCAMELEON® ARTHRO HOPKINS® Telescope , diameter 4 mm, length 18 cm, autoclavable , variable direction of view from 15° – 90°, adjustment knob for selecting the desired direction of view, fiber optic light transmission incorporated, color code: gold
28136 EC	Arthroscope Sheath ENDOCAMELEON® , with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, distal tapered, with irrigation holes, two stopcocks, rotatable, for use with ENDOCAMELEON® ARTHRO HOPKINS® Telescope 28731 AE and Obturator 28134 O with cannulated handle or Obturators 28126 BC/BT
28126 BT	Obturator , semisharp, for use with Arthroscope Sheaths 28229 DR, 28129 CR, 28126 CR/R/B, 28136 CR, 28135 CR and 28136 EC, color code: green-red-yellow
28140 EWK	Changing Rod ENDOCAMELEON® , cannulated, diameter 3.8 mm, working length 31 cm, for use with Arthroscope Sheath ENDOCAMELEON® 28136 EC and Nitinol Guide Wire 28140 GW

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Portal Management System

28140 EB	Dilator , with integrated handle, short, diameter 6 mm, for use with Threaded Cannula 28140 SA and Obturator 28140 EO
28140 EO	Obturator , cannulated, inner diameter 1.6 mm, for use with Guide Wire 28140 GW
28140 FC	Dilator , with integrated handle, long, diameter 8.1 mm, for use with Threaded Cannula 28140 SD and Obturator 28140 FP
28140 FP	Obturator , cannulated, inner diameter 1.6 mm, for use with Guide Wire 28140 GW
3x 28179 DG	Valve Housing , with LUER-Lock, for use with Cannulas and Set of Gaskets 28179 GS
28140 SA-6	Cannula , with thread, transparent, unsterile, for single use, package of 6
28140 SD-6	Cannula , with thread, transparent, unsterile, for single use, package of 6

Recommended Shaver Blades, Hip Arthroscopy

28208 BKS	Aggressive Cutter , sterile, for single use, diameter 4.5 mm, working length 180 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: green
28208 EHS	Curved Aggressive Full Radius Resector , sterile, for single use, diameter 4.5 mm, working length 180 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: light green
28208 IDS	Semi Hooded Barrel Burr , sterile, for single use, diameter 5.5 mm, working length 180 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: pink

Wrist Arthroscopy

28320

Wrist Arthroscopy Set

including:

HOPKINS® Wide Angle Forward-Oblique Telescope 30°, diameter 2.4 mm, length 10 cm, autoclavable, fiber optic light transmission incorporated,

color code: red

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 3.5 mm, working length 6.5 cm, two stopcocks, rotatable, for use with HOPKINS® Telescope 30° 28300 BA and Obturators 28302 BU/BV

Obturator, blunt, for use with Arthroscope Sheaths 28303 DS/BS

HOPKINS® Forward-Oblique Telescope 30°, diameter 1.9 mm, length 6.5 cm, autoclavable, fiber optic light transmission incorporated,

color code: red

High-Flow Arthroscope Sheath, with standard coupling mechanism, diameter 2.5 mm, working length 4 cm, one stopcock, fixed, for use with HOPKINS® Telescope 30° 28305 BA and Obturators 28306 BS/BT,

color code: red

Obturator, blunt, for use with Arthroscope Sheath 28306 BN

Probe, graduated, length of hook 2 mm, diameter 1 mm, working length 4 cm

Probe, graduated, length of hook 1 mm, diameter 1 mm, working length 7.5 cm

SILGRASP® PRO Suture Grasper, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm

SILCUT® PRO Oval Biter, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2 mm, jaws curved to left 45°, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm

Same, jaws curved to right 45°

HARTMANN Forceps, extra delicate, serrated, 1 x 4.5 mm, working length 12.5 cm

MASING Needle Holder, smooth jaws, working length 8 cm

Retractor, 2 x 3 prongs, blunt, length 10 cm

Recommended Grasping Forceps for Small Joints

28572 CGU

SILGRASP® PRO Cartilage Grasping Forceps, spoon-shaped jaws, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

28572 GU

SILGRASP® PRO Grasping Forceps, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Recommended Shaver Blades for Small Joints, Arthroscopy

28206 FAS

Small Joint Burr, sterile, for single use, diameter 2.5 mm, working length 70 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: orange

28206 FBS

Small Joint Burr, sterile, for single use, diameter 3.5 mm, working length 70 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: orange

28206 DAS

Aggressive Full Radius Resector, sterile, for single use, diameter 2.5 mm, working length 70 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: blue

28206 DBS

Aggressive Full Radius Resector, sterile, for single use, diameter 3.5 mm, working length 70 mm, package of 6, for use with UNIDRIVE® S III ARTHRO SCB, color code: blue

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

28330

Accessory Set Hand Arthroscopy, complete,

including:

Ligature Scissors, with tungsten carbide blades, curved, lower blade serrated, length 18 cm, color code: one black handle ring, one gold-plated handle ring

MAYO Scissors, curved, length 17 cm

JAMESON Scissors, curved, pointed, delicate tips, length 15.5 cm

BEYER Rongeur, slender, curved, length 17 cm

Needle Holder, tungsten carbide inserts, length 15 cm

2x **Hook**, one prong, large curve, length 18 cm

2x **JOSEPH Double Hook**, sharp, width 7 mm, length 15 cm

2x **HALSTEAD "Mosquito" Artery Forceps**, micro-model, curved, length 12.5 cm

HALSTEAD "Mosquito" Artery Forceps, micro-model, straight, length 12.5 cm

Double Elevator, size 18 cm

Retractor, double-ended, size 6 x 20 mm and 5 x 10 mm, length 14.5 cm

ADSON Tissue Forceps, 1 x 2 teeth, length 15 cm

ADSON Dressing Forceps, serrated, tungsten carbide inserts, length 12 cm

2x **Surgical Handle**, Fig. 3, length 12.5 cm, for Blades 208010 – 15, 208210 – 15

2x **Towel Forceps**, with serrated inserts, length 13 cm, for paper cover sheets

Medicine Cup, 100 cm³, diameter 80 mm, height 30 mm

Carpal Tunnel Syndrome

- 28731 BVA **HOPKINS® Wide Angle Forward-Oblique Telescope 30°**, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light connector in line of sight, fiber optic light transmission incorporated, color code: red
- 28147 C **GILBERT Operating Sheath**, continuously slotted, diameter 5.5 mm, working length 9 cm, for use with Obturator 28147 CO and HOPKINS® Telescope 28731 BVA
- 28147 CO **Obturator**, blunt, with attached segment, for use with Operating Sheath 28147 C
- 28147 E **GILBERT Rasp**, for preparation of the carpal ligament
- 28147 S **Dilator Set**
including:
Dilator, diameter 4 mm
Dilator, diameter 5 mm
Dilator, diameter 6 mm
Dilator, diameter 7 mm
- 28147 R **Knife**, retractable, backward cutting, with exchangeable Knife Attachment 28147 RM, diameter 3.5 mm, working length 9 cm
- 28147 RM **Knife Attachment**, backward cutting, for use with Knife 28147 R

Cubital Tunnel Syndrome

- 50600 **HOFFMANN Cubital Tunnel Set**
including:
HOPKINS® Wide Angle Forward-Oblique Telescope 30°, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**
Optical Dissector, with distal spatula, fenestrated, sharp
Speculum, with fiber optic light carrier, with set screw, blade length 90 mm, length 13.5 cm
COTTLE Speculum, with fiber optic light carrier, without set screw, special matt finish, blade length 55 mm, length 13 cm
Speculum, with fiber optic light carrier, with set screw, blade length 110 mm, length 13.5 cm
DUPLAY Dressing and Sponge Holding Forceps, curved, with ratchet, length 21 cm
DUPLAY Dressing and Sponge Holding Forceps, straight, with ratchet, length 21 cm
METZENBAUM Scissors, curved, length 18 cm
METZENBAUM Scissors, curved, length 23 cm
METZENBAUM Scissors, curved, length 28 cm
ROBI® KELLY Grasping Forceps, CLERMONT-FERRAND model, with connector pin for bipolar coagulation, especially suitable for dissection, double action jaws, size 3.5 mm, length 20 cm, color code: light blue
- optional**
50300 ES **Optical Dissector**, with distal spatula, working length 14.5 cm, for use with HOPKINS® telescopes 30°

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Elbow Arthroscopy

- 28208 BA **HOPKINS® Forward-Oblique Telescope 30°**, diameter 2.7 mm, length 11 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red
- 28133 DS **Arthroscope Sheath**, with snap-in coupling mechanism, diameter 4 mm, working length 7.5 cm, two stopcocks, rotatable, for use with HOPKINS® telescope 30° and Obturator 28133 BC
- 28133 BC **Obturator**, blunt, for use with Arthroscope Sheath 28133 DS
- 28124 BZ **Changing Rod**, diameter 2.7, length 23 cm, for use with Arthroscope Sheath 28132 CR
- 28145 S **Probe**, graduated, length of hook 2 mm, diameter 1.5 mm, working length 8.5 cm
- 28728 CG **Microfracture Chisel**, angled 30°, working length 9 cm
- 28728 CH **Microfracture Chisel**, angled 70°, working length 9 cm
- 28572 AD **SILCUT® PRO Punch**, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 AE **SILCUT® PRO Punch**, through-cutting, cross-toothed, cutting width 1 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 O **SILCUT® PRO Oval Biter**, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 G **SILGRASP® PRO Grasping Forceps**, spoon-shaped jaws, serrated, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 CGU **SILGRASP® PRO Cartilage Grasping Forceps**, spoon-shaped jaws, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 GU **SILGRASP® PRO Grasping Forceps**, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Ankle Arthroscopy

- 28208 BA **HOPKINS® Forward-Oblique Telescope 30°**, diameter 2.7 mm, length 11 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red
- 28133 DS **Arthroscope Sheath**, with snap-in coupling mechanism, diameter 4 mm, working length 7.5 cm, two stopcocks, rotatable, for use with HOPKINS® telescope 30° and Obturator 28133 BC
- 28133 BC **Obturator**, blunt, for use with Arthroscope Sheath 28133 DS
- 28124 BZ **Changing Rod**, diameter 2.7, length 23 cm, for use with Arthroscope Sheath 28132 CR
- 28145 S **Probe**, graduated, length of hook 2 mm, diameter 1.5 mm, working length 8.5 cm
- 28728 CG **Microfracture Chisel**, angled 30°, working length 9 cm
- 28728 CH **Microfracture Chisel**, angled 70°, working length 9 cm
- 28572 AD **SILCUT® PRO Punch**, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 AE **SILCUT® PRO Punch**, through-cutting, cross-toothed, cutting width 1 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 O **SILCUT® PRO Oval Biter**, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 G **SILGRASP® PRO Grasping Forceps**, spoon-shaped jaws, serrated, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 CGU **SILGRASP® PRO Cartilage Grasping Forceps**, spoon-shaped jaws, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm
- 28572 GU **SILGRASP® PRO Grasping Forceps**, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog



HOPKINS® TELESCOPES AND SHEATHS

ENDOCAMELEON® ARTHRO28-29

HOPKINS® TELESCOPES, Diameter 4 mm,
ARTHROSCOPE SHEATHS
Diameter 5.5 - 6.5 mm30-36

OBTURATORS AND
CHANGING RODS37

HOPKINS® TELESCOPES,
Diameter 1.9 - 2.7 mm,
ARTHROSCOPE SHEATHS
Diameter 2.5 - 4 mm38-41



 **EndoCAMEleon**® ARTHRO

ENDOCAMELEON® ARTHRO




Diameter 4 mm, length 18 cm

Recommended in combination with IMAGE1 S™ (CLARA and CHROMA modes)

ENDOCAMELEON® ARTHRO is the newest member of the HOPKINS® family of rod-lens telescopes – and the most versatile. A simple turn of the adjusting knob enables the user to select the direction of view between 15° and 90°. This enables the surgeon to quickly and easily select the desired direction of view for optimal orientation and control. Consequently,

ENDOCAMELEON® ARTHRO is an excellent tool for diagnostic examinations. This can also eliminate the time-consuming switching between telescopes. ENDOCAMELEON® ARTHRO combines the user comfort of HOPKINS® telescopes with unprecedented versatility – in proven, high quality KARL STORZ style.



28731 AE



ENDOCAMELEON® telescope with variable direction of view – isometric view

28731 AE

ENDOCAMELEON® ARTHRO HOPKINS® Telescope, diameter 4 mm, length 18 cm, **autoclavable**, variable direction of view from 15° – 90°, adjustment knob for selecting the desired direction of view, fiber optic light transmission incorporated, color code: gold



28136 EC



28136 EC

Arthroscope Sheath ENDOCAMELEON®, with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, distal end tapered, with irrigation holes, two stopcocks, **rotatable**, for use with ENDOCAMELEON® ARTHRO HOPKINS® Telescope 28731 AE and Obturator 28134 O with cannulated handle or Obturators 28126 BC/BT



The familiar ergonomics and handling of conventional telescopes is enhanced with the additional convenience of a variable direction of view.



The direction of view is adjusted by a mere turn of the adjusting knob at the proximal end of the ENDOCAMELEON® ARTHRO.

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog
Components/Spare Parts see chapter 18

Special Features:

- Unique rod lens system
- First-class image quality with optimal brightness and contrast
- High detail resolution
- Autoclavable

The product range includes all standard directions of view required for arthroscopy: **0°, 30° and 70°**.
The arthroscopy portfolio includes diameter sizes ranging from **1 to 4 mm**.



The color code of the HOPKINS® telescopes denotes the direction of view.

Color Code	Direction of View
Green	0°
Red	30°
Yellow	70°



Container for the Sterilization and Storage of Telescopes see HYGIENE catalog


Diameter 4 mm, length 18 cm



28731 AWA **HOPKINS® Wide Angle Straight Forward Telescope 0°**, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light transmission incorporated, color code: green



28731 BWA **HOPKINS® Wide Angle Forward-Oblique Telescope 30°**, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red



28731 CWA **HOPKINS® Wide Angle Lateral Telescope 70°**, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light transmission incorporated, color code: yellow


Arthroscope Sheaths

with Standard Coupling Mechanism


Diameter 6.5 and 5.5 mm, working length 12 cm,
for use with HOPKINS® telescopes, diameter 4 mm, length 18 cm

Special Features:

- High mechanical stability
- Stable and reliable telescope-sheath lock
- Sheath tip is tapered towards the distal end to hold the telescope securely in place.
- Telescopes and sheaths are color-coded to ensure compatibility and to prevent wrong combinations.
- The high-flow system provides improved in- and outflow.
- Sheaths can be fully dismantled to allow proper cleaning and processing.



Increased inflow and outflow rate
without disturbing turbulence




28229 DR



28229 DR

High-Flow Arthroscope Sheath, with standard coupling mechanism, diameter 6.5 mm, working length 12 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, *color code: green-red-yellow



28126 B



28126 B

Arthroscope Sheath, with standard coupling mechanism, diameter 5.5 mm, working length 12 cm, two stopcocks, **fixed**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, *color code: green-red-yellow

***Note:** For an overview of color codes for HOPKINS® Telescopes see page 30


Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Components/Spare Parts see chapter 18

Arthroscope Sheaths

with Standard Coupling Mechanism

Diameter 5.5 mm, working length 12 cm,
for use with HOPKINS® telescopes, diameter 4 mm, length 18 cm



28126 CR



28126 CR

Arthroscope Sheath, with standard coupling mechanism, diameter 5.5 mm, working length 12 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, color code: green-red-yellow

28126 R

Same, one stopcock

***Note:** For an overview of color codes for HOPKINS® Telescopes see page 30


Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Components/Spare Parts see chapter 18

Arthroscope Sheaths

with Snap-in Coupling Mechanism

Diameter 6 mm, color code red, working length 13.5 cm,
for use with HOPKINS® telescopes, diameter 4 mm, length 18 cm



28136 DS




28136 DS

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, distal tapered, with irrigation holes, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 30°, 70° and Obturators 28136 BC/BT, color code: red

28136 S

Same, one stopcock



28130 CR



28130 CR

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28130 BC/BT, 28140 O, color code: red

28130 R

Same, one stopcock



28136 CR



28136 CR

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 6 mm, working length 13.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, color code: red


Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Components/Spare Parts see chapter 18

Arthroscope Sheaths

with Snap-in Coupling Mechanism

Diameter 5.5 mm, color code blue, working length 13.5 cm,
for use with HOPKINS® telescopes, diameter 4 mm, length 18 cm



28131 CR




28131 CR

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 5.5 mm, working length 13.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28130 BC/BT, 28140 O, color code: blue

28131 R

Same, one stopcock



28135 CR



28135 CR

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 5.5 mm, working length 13.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, color code: blue

5-08z

Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Components/Spare Parts see chapter 18


Arthroscope Sheath

with Lock-in Coupling Mechanism


Diameter 6 mm, working length 12 cm,
for use with HOPKINS® telescopes, diameter 4 mm, length 18 cm

Special Features:

- Click mechanism for adaption between telescope and sheath



*Increased inflow and outflow rate
without disturbing turbulence*



28129 CR



28129 CR

STROBEL Arthroscope Sheath, with automatic lock-in coupling mechanism, diameter 6 mm, working length 12 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescopes 0°, 30°, 70° and Obturators 28126 BC/BT/BS, 28134 O, *color code: green-red-yellow


***Note:** For an overview of color codes for HOPKINS® Telescopes see page 30

Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Components/Spare Parts see chapter 18

Obturator and Changing Rods


For use with Arthroscope Sheaths 28136 DS/S



28136 BT


- 28136 BT **Obturator**, semisharp
- 28136 BC **Same**, blunt

For use with Arthroscope Sheaths 28229 DR, 28129 CR, 28126 CR/R/B, 28136 CR, 28135 CR and 28136 EC



28126 BT


- 28126 BT **Obturator**, semisharp
- 28126 BS **Same**, sharp
- 28126 BC **Same**, blunt



28134 O


- 28134 O **Obturator**, cannulated, with handle, diameter 4.1 mm

For use with Arthroscope Sheaths 28131 CR/R, 28130 CR/R



28130 BT

- 28130 BT **Obturator**, semisharp
- 28130 BC **Same**, blunt



28140 O

- 28140 O **Obturator**, cannulated, with handle, diameter 4.8 mm

For use with arthroscope sheaths that can be used with telescopes with diameter 4 mm



28124 BX


- 28124 BX **Changing Rod**, length 23 cm, for use with arthroscope sheaths with inner diameter 4 mm
- 28270 W **Same**, length 35 cm

Components/Spare Parts see chapter 18

HOPKINS® Telescope and Arthroscope Sheath

with Standard Coupling Mechanism

Diameter 2.7 mm, length 18 cm




28719 BA



28719 BA

HOPKINS® Forward-Oblique Telescope 30°, diameter 2.7 mm, length 18 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameter 4 mm, working length 12.5 cm




28132 CR



28132 CR

Arthroscope Sheath, with standard coupling mechanism, diameter 4 mm, working length 12.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® telescope 30° and Obturator 28132 BC, *color code: red-yellow



28132 BC

28132 BC

Obturator, blunt, for use with Arthroscope Sheath 28132 CR

***Note: For an overview of color codes for HOPKINS® Telescopes** see page 30

Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.


Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Components/Spare Parts see chapter 18


HOPKINS® Telescope and Arthroscope Sheath

with Snap-in Coupling Mechanism

Diameter 2.7 mm, length 11 cm




28208 BA



28208 BA

HOPKINS® Forward-Oblique Telescope 30°, diameter 2.7 mm, length 11 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameter 4 mm, working length 7.5 cm




28133 DS



28133 DS

Arthroscope Sheath, with snap-in coupling mechanism, diameter 4 mm, working length 7.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® Telescope 30° and Obturator 28133 BC



28133 BC

28133 BC

Obturator, blunt, for use with Arthroscope Sheath 28133 DS

***Note:** For an overview of color codes for HOPKINS® Telescopes see page 30

Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.


Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Components/Spare Parts see chapter 18


HOPKINS® Telescope and Arthroscope Sheaths

with Snap-in Coupling Mechanism

Diameter 2.4 mm, length 10 cm




28300 BA



28300 BA

HOPKINS® Wide Angle Forward-Oblique Telescope 30°, diameter 2.4 mm, length 10 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameter 3.5 and 3.2 mm, working length 6.5 and 8.5 cm




28303 DS



28303 DS

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 3.5 mm, working length 6.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® Telescope 30° 28300 BA and Obturators 28302 BU/BV




28303 BS



28303 BS

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 3.2 mm, working length 8.5 cm, one stopcock, **fixed**, for use with HOPKINS® Telescope 30° 28300 BA and Obturators 28302 BU/BV



28302 BU



28302 BU

Obturator, sharp, for use with Arthroscope Sheaths 28303 DS/BS



28302 BV

Same, blunt


***Note: For an overview of color codes for HOPKINS® Telescopes** see page 30

Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Components/Spare Parts see chapter 18

Diameter 1.9 mm, length 6.5 cm




28305 BA



28305 BA

HOPKINS® Forward-Oblique Telescope 30°, diameter 1.9 mm, length 6.5 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameter 2.5 mm, working length 4 cm




28306 BN



28306 BN

High-Flow Arthroscope Sheath, with standard coupling mechanism, diameter 2.5 mm, working length 4 cm, one stopcock, **fixed**, for use with HOPKINS® Telescope 30° 28305 BA and Obturators 28306 BS/BT, *color code: red



28306 BS



28306 BS

Obturator, sharp, for use with Arthroscope Sheath 28306 BN



28306 BT


Same, blunt

***Note: For an overview of color codes for HOPKINS® Telescopes** see page 30

Please note: Up to now arthroscope sheaths and trocars included two obturators. Due to customer demand, we will deliver the sheaths and trocars without obturators in future. We ask you to specify the required obturator in your order.

Container for the Sterilization and Storage of Telescopes see HYGIENE catalog

Components/Spare Parts see chapter 18





HOSPITAL INSTRUMENTS

RETRACTORS, PROBES, PALPATION HOOKS,
KNIVES, CURETTES, MIRRORS,
CHISELS, RASPS, CANNULAS 44-52



801810

801810 LANGENBECK **Retractor**, size 43 x 13 mm,
length 21 cm




786003

786003 **Retractor**, sharp, 3 prongs,
length 17 cm




498400

498400 **COTTLE Retractor**, narrow (standard model),
length 14 cm



28140 T



28140 T

Probe, graduated, length of hook 3 mm, diameter 1.5 mm, working length 18 cm



28140 TL

Same, working length 21.5 cm



28140 TA

Probe, graduated, length of hook 3 mm, angled downwards 10°, diameter 1.5 mm, working length 20 cm



28140 TB

Probe, graduated, length of hook 3 mm, angled downwards 20°, diameter 1.5 mm, working length 20 cm



28145 LH

28145 LH

Probe, graduated, blunt, length of hook 5.5 mm, diameter 1.5 mm, working length 13 cm



28145 S

28145 S

Probe, graduated, length of hook 2 mm, diameter 1.5 mm, working length 8.5 cm

28145 V

Same, length of hook 4 mm

28145 W

Probe, graduated, length of hook 4 mm, diameter 1.5 mm, working length 12 cm

28270 T

Probe, graduated, length of hook 2 mm, diameter 1.5 mm, working length 18 cm

28170 S

Probe, working length 14 cm




28302 S

28302 S

Probe, graduated, length of hook 1 mm, diameter 1 mm, working length 7.5 cm

Working length 11.5 cm



28146 D

Probe, straight,
working length 11.5 cm



28146 E

Pointed Knife, straight,
working length 11.5 cm



28146 K

SMILLIE Knife, straight,
working length 11.5 cm



28146 L

Hook Knife, straight,
working length 11.5 cm



28146 N

Sickle Knife, straight,
working length 11.5 cm



28146 H

Rosette Knife, straight,
working length 11.5 cm



NEW 28140 LM


Knife, round, straight,
working length 11.5 cm



NEW 28140 BM

Knife, round, angled 20°,
working length 11.5 cm

Working length 18 cm



28140 MG



28140 MG

Knife, pointed, curved, double-edged,
working length 18 cm




Curettes

Special Features:

- Smoothing of tunnels possible
- Easy insertion through the instrument port
- Precise treatment of cartilage lesions, without injuring adjacent intact cartilage areas



28728 KA - KF



Single cutting edge



28728 KA

Curette, oval, large, curved, 10° upwards, working length 13 cm



28728 KB

Curette, oval, large, curved, 30° upwards, working length 13 cm



28728 KC

Curette, oval, medium, curved, 10° upwards, working length 13 cm



28728 KD

Curette, oval, medium, curved, 30° upwards, working length 13 cm



28728 KE

Curette, oval, small, curved, 10° upwards, working length 13 cm



28728 KF

Curette, oval, small, curved, 30° upwards, working length 13 cm

Double cutting edge



28195 KC

Curette, oval, large, both sides cutting, curved, 20° upwards, working length 13 cm



28140 KE

Curette, oval, small, both sides cutting, curved, 20° upwards, working length 18 cm

Special Features:


- Easy-to-use system for enhanced arthroscopic view
- Better visualization of anatomic structures



28728 G **Handle**, for use with Mirror Attachments 28728 MA/MC and Suture Curette 28728 K



28728 MA **Mirror Attachment**, straight, diameter 6.2 mm, working length 11 cm, for use with Handle 28728 G




28728 MC **Mirror Attachment**, curved, 40° upwards, diameter 6.2 mm, working length 11 cm, for use with Handle 28728 G

Chisel

Notch chisels for notchplasty can also be used after transplantation.

Benefits:

- **Rounded chisel tip facilitates insertion into the joint**
- **Extra wide chisel tip enables fast and efficient work**
- **Curved chisel tip, optimized resection**
- **Depth markings enables controlled removal of bone at the notch**



28729 NO



28729 NO

Notch Chisel, curved, 15° downwards, working length 13 cm



These instruments were primarily developed for the smoothing of bone surfaces after removing portions of bone in the knee joint (notchplasty, osteophytes), in the ankle joint, in the elbow joint and the wrist.

Special Features:

- **Rounded tip which allows easier introduction of rasp into the intraarticular joint cavity through the instrument approach.**
- **The lateral rasp surfaces are slightly polished to allow improved introduction through the instrument approach.**
- **Due to the rounded edges, the rasp may be pushed over the cartilage to a certain extent without injuring it.**
- **Various diameters and angulations allow bone surfaces to be worked in different joint sites.**



28728 RF



28728 RF

Rasp, narrow, straight, fine, working length 13 cm



28728 RFG

Rasp, narrow, curved, fine, working length 13 cm



28728 RGG

Rasp, narrow, curved, coarse, working length 13 cm



28728 BFG

Rasp, wide, curved, fine, working length 13 cm

Please note: Provided that an initial order is placed, it is recommended to buy a complete set of instruments.

Special Features:

- Lateral outflow of the irrigation liquid
- Safe instrument for removal of small arthroliths and meniscus fragments still remaining in the joint. In contrast to removal with a motor system, the risk of injuring intact synovial or cartilage areas is considerably reduced
- Easy to use




28728 DB

28728 DB **Irrigation Cannula**, diameter 5 mm,
length 14.5 cm




28728 DC

28728 DC **Irrigation Cannula**, diameter 6 mm,
length 14.5 cm




28146 T

28146 T **Irrigation Cannula**, with LUER-Lock and stopcock, diameter 3.2 mm, working length 7 cm, for use with Obturator 28146 QO




28146 QO

28146 QO **Obturator**, sharp, for use with Cannula 28146 T



28146 TT

28146 TT **Irrigation Cannula**, with LUER-Lock and stopcock, diameter 4.5 mm, working length 7 cm, for use with Obturators 28146 TO/TS



28146 TO

28146 TO **Obturator**, sharp, for use with Cannula 28146 TT

28146 TS **Same**, blunt

Please note: Up to now arthroscope sheaths and trocars included 2 obturators. Due to customer demand, we no longer include obturators with sheath and trocar deliveries. Please don't forget to specify the desired obturator in your order.

Components/Spare Parts see chapter 18



PUNCHES, FORCEPS AND SCISSORS

SILCUT® PRO AND
SILCUT® PUNCHES AND SCISSORS54-61

SILGRASP® PRO AND
SILGRASP® GRASPING FORCEPS62-67

SPECIAL PUNCHES, FORCEPS68-69

RETROFORCE® BIOPSY PUNCH70-71

The new hand instruments in the SILCUT® PRO and SILCUT® product lines set standards in arthroscopic resection. The combination of utmost precision, state-of-the-art design and an optimal cleaning concept make these instruments unique.

Unique benefits of the SILCUT® PRO and SILCUT® instruments:



Unique hygiene concept for efficient instrument cleaning (KARL STORZ CLEANFIT®)



Ergonomic handle for fatigue-free work while the large aperture angle of the instrument jaws allows efficient resection


The SILCUT® PRO premium line offers further decisive advantages for your applications:



Extremely flat jaw (1.5 – 1.9 mm) for improved anatomical adaptation



Special jaw shapes for gentle access in challenging indications



Optimized mechanics for better cutting force and cutting sensation

The new hand instruments in the SILCUT® PRO and SILCUT® product lines set standards in arthroscopic resection. The combination of utmost precision, state-of-the-art design and an optimal cleaning concept make these instruments unique.


Unique benefits of the SILCUT® PRO and SILCUT® instruments:



Unique hygiene concept for efficient instrument cleaning (KARL STORZ CLEANFIT®)



Ergonomic handle for fatigue-free work while the large aperture angle of the instrument jaws allows efficient resection



28571 AB

Square jaws

Cross-toothed, cutting width 3.4 mm, sheath diameter 3.5 mm, working length 12 cm
(recommended for the knee and shoulder)



28571 AB

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 BB

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 BBL
NEW

SILCUT® PRO Upbiter, through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, curved 15° to left and 10° curved upwards, handle with cleaning connector, working length 12 cm



28571 BBR
NEW Same, 15° to right

Cross-toothed, cutting width 2.7 mm, sheath diameter 3.5 mm, working length 12 cm
(recommended for the knee and shoulder)



28571 AC

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2.7 mm, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 BC

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2.7 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18



Cross-toothed, cutting width 2 mm, sheath diameter 2.5 mm, working length 8.5 cm
(recommended for small joints)



28572 AD

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 ADL
NEW

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2 mm, jaws curved to left 45°, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 ADR
NEW

Same, jaws curved to right 45°

Cross-toothed, cutting width 1 mm, sheath diameter 2.5 mm, working length 8.5 cm
(recommended for small joints)



28572 AE

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 1 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm

Oval jaws

Cross-toothed, cutting width 4.1 mm, sheath diameter 3.5 mm, working length 12 cm
(recommended for the knee and shoulder)



28571 O

SILCUT® PRO Oval Biter, through-cutting, cross-toothed, cutting width 4.1 mm, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 OA

SILCUT® PRO Oval Biter, through-cutting, cross-toothed, cutting width 4.1 mm, jaws curved, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Cross-toothed, cutting width 2 mm, sheath diameter 2.5 mm, working length 8.5 cm
(recommended for small joints)



28572 O

SILCUT® PRO Oval Biter, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm

Circumferential teeth, cutting width 4.1 mm, sheath diameter 3.5 mm, working length 12 cm
(recommended for the knee and shoulder)



28571 OC

SILCUT® PRO Oval Biter, through-cutting, with circumferential teeth, cutting width 4.1 mm, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 OAC

SILCUT® PRO Oval Upbiter, through-cutting, with circumferential teeth, cutting width 4.1 mm, curved jaws, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 ODC
NEW

SILCUT® PRO Oval Downbiter, through-cutting, with circumferential teeth, cutting width 4.1 mm, curved jaws, 15° downwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18



Special jaw design

Circumferential teeth, cutting width 5.8 mm, sheath diameter 3.5 mm, working length 12 cm (recommended for the knee and shoulder)



28571 E

SILCUT® PRO Giga Punch, through-cutting, with circumferential teeth, cutting width 5.8 mm, straight jaws, sheath diameter 3.5 mm, straight, handle with connector for cleaning, working length 12 cm



28571 EU

SILCUT® PRO Giga Punch, through-cutting, with circumferential teeth, cutting width 5.8 mm, curved jaws, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Circumferential teeth, cutting width 5 mm, sheath diameter 3.5 mm, working length 12 cm (recommended for the knee and shoulder)



28571 S

SILCUT® PRO Square Punch, through-cutting, with circumferential teeth, cutting width 5 mm, rhombic jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 SU

SILCUT® PRO Square Punch, through-cutting, with circumferential teeth, cutting width 5 mm, rhombic jaws, 15° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Circumferential teeth, cutting width 4.3 mm, sheath diameter 3.5 mm, working length 12 cm (recommended for the knee and shoulder)



28571 CL

SILCUT® PRO Side Punch, through-cutting, with circumferential teeth, cutting width 4.3 mm, angled jaws, curved to left 45°, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 CLU

SILCUT® PRO Side Punch, through-cutting, with circumferential teeth, cutting width 4.3 mm, angled jaws, 15° upwards, left 45°, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 CR

SILCUT® PRO Side Punch, through-cutting, with circumferential teeth, cutting width 4.3 mm, angled jaws, curved to right 45°, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 CRU

SILCUT® PRO Side Punch, through-cutting, with circumferential teeth, cutting width 4.3 mm, angled jaws, 15° upwards, right 45°, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Scissors




28571 SP

SILCUT® PRO Scissors, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 14 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog

Components/Spare Parts see chapter 18



28171 BBN

Square jaws

Cross-toothed, cutting width 3.4 mm, sheath diameter 3 mm, working length 19 cm (recommended for the shoulder and hip)



28171 KPN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 19 cm



28171 KUN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, 15° curved upwards, handle with cleaning connector, working length 19 cm

Cross-toothed, cutting width 3.4 mm, sheath diameter 3 mm, working length 12 cm (recommended for the knee)



28171 ABN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 BBN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, curved jaws, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm




28171 CBN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, 30° curved to left, handle with cleaning connector, working length 12 cm



28171 DBN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, 30° curved to right, handle with cleaning connector, working length 12 cm



28171 EBN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, curved jaws, 90° left, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 FBN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, curved jaws, 90° right, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 GBN

SILCUT® Punch, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, 15° curved upwards, handle with cleaning connector, working length 12 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog

Components/Spare Parts see chapter 18



Cross-toothed, cutting width 2.7 mm, sheath diameter 3 mm, working length 12 cm (recommended for the knee)



28171 ACN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 BCN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 CCN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, straight jaws, sheath diameter 3 mm, 30° curved to left, handle with cleaning connector, working length 12 cm



28171 DCN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, straight jaws, sheath diameter 3 mm, 30° curved to right, handle with cleaning connector, working length 12 cm



28171 ECN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, curved jaws, 90° left, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 FCN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, curved jaws, 90° right, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 GCN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 2.7 mm, straight jaws, sheath diameter 3 mm, 15° curved upwards, handle with cleaning connector, working length 12 cm

Cross-toothed, cutting width 1.5 mm, sheath diameter 3 mm, working length 12 cm (recommended for the knee)



28171 ADN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 1.5 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 BDN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 1.5 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm

Cutting width 0.5 mm, sheath diameter 3 mm, working length 12 cm (recommended for the knee)



28171 SPN **SILCUT® Punch**, through-cutting, cutting width 0.5 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 SLN **SILCUT® Punch**, through-cutting, cutting width 0.5 mm, straight jaws, sheath diameter 3 mm, 10° curved to left, handle with cleaning connector, working length 12 cm

28171 SRN **SILCUT® Punch**, through-cutting, cutting width 0.5 mm, straight jaws, sheath diameter 3 mm, 10° curved to right, handle with cleaning connector, working length 12 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18



Oval jaws

Cross-toothed, cutting width 4.1 mm, sheath diameter 3 mm, working length 12 cm
(recommended for the knee)



28171 OAN **SILCUT® Oval Upbiter**, through-cutting, cross-toothed, cutting width 4.1 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 OUN **SILCUT® Oval Upbiter**, through-cutting, cross-toothed, cutting width 4.1 mm, jaws curved, 15° upwards, sheath diameter 3 mm, 15° curved upwards, handle with cleaning connector, working length 12 cm

Special jaw design

Cross-toothed, cutting width 3.4 mm, sheath diameter 3 mm, working length 12 cm
(recommended for the knee)



28171 SBN **SILCUT® Backbiter**, backward cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm

SILGRASP® PRO Grasping Forceps

The SILGRASP® PRO and SILGRASP® hand instruments from KARL STORZ include forceps for grasping various tissue structures. The combination of utmost precision, state-of-the-art design and an optimal cleaning concept make these instruments unique.

Unique benefits of the SILGRASP® PRO and SILGRASP® grasping forceps:



Unique hygiene concept for efficient instrument cleaning (KARL STORZ CLEANFIT®)



Ergonomic handle for fatigue-free work while the large aperture angle of the instrument jaws allows efficient grasping


The SILGRASP® PRO premium line offers further decisive advantages for your applications:



Filigree jaws for improved anatomical adaptation



Special jaw shapes for gentle access in challenging indications




Optimized mechanics for enhanced tactile feedback

SILGRASP® Grasping Forceps

The SILGRASP® PRO and SILGRASP® hand instruments from KARL STORZ include forceps for grasping various tissue structures. The combination of utmost precision, state-of-the-art design and an optimal cleaning concept make these instruments unique.

Unique benefits of the SILGRASP® PRO and SILGRASP® grasping forceps:



Unique hygiene concept for efficient instrument cleaning (KARL STORZ CLEANFIT®)



Ergonomic handle for fatigue-free work while the large aperture angle of the instrument jaws allows efficient grasping



Sheath diameter 2.8 mm, working length 8.5 cm (recommended for small joints)



28572 NJ

SILGRASP® PRO Suture Grasper, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 CG

SILGRASP® PRO Cartilage Grasping Forceps, spoon-shaped jaws, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 CGU

SILGRASP® PRO Cartilage Grasping Forceps, spoon-shaped jaws, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 G

SILGRASP® PRO Grasping Forceps, spoon-shaped jaws, serrated, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 GU

SILGRASP® PRO Grasping Forceps, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 AG

SILGRASP® PRO Alligator Grasping Forceps, serrated, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18

SILGRASP® PRO Grasping Forceps ^{NEW}



Sheath diameter 3.5 mm, working length 12 cm (recommended for the knee)



28571 FG **SILGRASP® PRO Foreign Body Grasper**, aggressive, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 CG **SILGRASP® PRO Cartilage Grasping Forceps**, spoon-shaped jaws, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 CGU **SILGRASP® PRO Cartilage Grasping Forceps**, spoon-shaped jaws, jaws curved, 30° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 G **SILGRASP® PRO Grasping Forceps**, spoon-shaped jaws, serrated, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm




28571 GU **SILGRASP® PRO Grasping Forceps**, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm



28571 AG **SILGRASP® PRO Alligator Grasping Forceps**, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18



Sheath diameter 3 mm, working length 12 cm (recommended for the knee)



28171 HAN **SILGRASP® Grasping Forceps**, spoon-shaped jaws, jaw width 4.5 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 HBN **SILGRASP® Grasping Forceps**, spoon-shaped jaws, jaw width 3.4 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 HCN **SILGRASP® Grasping Forceps**, spoon-shaped jaws, jaw width 2.7 mm, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 KBN **SILGRASP® Grasping Forceps**, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm



28171 AGN **SILGRASP® Alligator Grasping Forceps**, straight jaws, serrated, sheath diameter 3 mm, straight, handle with cleaning connector, working length 12 cm

28171 AGSN **Same**, with ratchet

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18

SILGRASP® Grasping Forceps



Sheath diameter 3 mm, working length 14 cm (recommended for the knee and shoulder)



28171 PGN **SILGRASP® Foreign Body Grasper**, aggressive, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 14 cm

28171 PGSN **Same**, with ratchet



28171 SGN **SILGRASP® Suture Grasper**, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 14 cm

Sheath diameter 3.5 mm, working length 16 cm (recommended for the knee and shoulder)



28171 SGL **SILGRASP® Suture Grasper**, curved jaws, 45° left, sheath diameter 3.5 mm, 5° curved to left, handle with cleaning connector, working length 16 cm
NEW

28171 SGR **Same**, 45° right, 5° curved to right
NEW

Sheath diameter 3.5 mm, working length 19 cm (recommended for the shoulder and hip)



28171 KGN **SILGRASP® Foreign Body Grasper**, aggressive, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 19 cm

28171 KGSN **Same**, with ratchet

Sheath diameter 4 mm, working length 22 cm (recommended for the hip)




28573 FD **SILGRASP® Foreign Body Grasper**, aggressive, sheath diameter 4 mm, straight, handle with cleaning connector and ratchet, working length 22 cm
NEW

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18

Special Punches, Forceps

Grasping Forceps

Working length 8 cm (recommended for the knee and small joints)




28728 NJ



28728 NJ

Suture Grasper, dismantling, jaw length 5.5 mm, straight jaws, straight sheath, working length 8 cm

Working length 9.5 cm (recommended for the knee)



28001 A




28001 A

Grasping Forceps, dismantling, jaw length 11 mm, curved jaws, 30° upwards, straight sheath, working length 9.5 cm

Special Punches, Forceps

Meniscus Grasping Forceps, Meniscus Retractor

Working length 13 cm (recommended for the knee)




28146 UH



28146 UH

SCHLESINGER Meniscus Grasping Forceps, dismantling, with teeth and ratchet, straight jaws, straight sheath, working length 13 cm




28146 UD



28146 UD

SCHLESINGER Meniscus Grasping Forceps, dismantling, with ratchet, straight jaws, straight sheath, working length 13 cm



28157 K



28157 K

Meniscus Retractor, with serrated jaws, with teeth and ratchet, straight jaws, straight sheath, working length 13 cm

For native joints

There are a number of indications for synovial biopsy. Joint inflammation of unknown origin (e.g., sarcoidosis), the accumulation of crystals or proteins (amyloidosis) or synovial tumors (e.g. PVNS) cannot be detected in the blood or through radiological assessments. The

RETROFORCE® allows safe and fast synovial biopsies, particularly in large joints such as the shoulder, hip or knee. Thanks to this retrograde technique, biopsies can be performed without simultaneous imaging.




Fig. 1: The open RETROFORCE® biopsy punch after insertion via the suprapatellar recess; the correct position is confirmed by the aspiration of synovial fluid.



Fig 2: The biopsy punch is retracted until contact with the synovial tissue is obtained.



Fig. 3: The punch is closed in a retrograde manner in order to obtain the synovial biopsy.



Scan the DataMatrix code to view a video on the application of the RETROFORCE® biopsy punch.






RETROFORCE® Biopsy Punch ^{NEW}

For the safe diagnosis of implant failures

Painful or loose prosthetic joints may have various causes. Infection associated with the implant, a common cause, must first be ruled out but symptoms may also arise from an allergic reaction to the implant or metal/plastic abrasion. In the case of infection in particular, synovial biopsy is far more effective than arthrocentesis alone according to available data. Furthermore, it can detect an allergic cellular reaction or

abrasion particles in the synovial membrane. RETROFORCE® allows a synovial biopsy to be safely performed under local anesthesia in a matter of minutes, e.g., in the hip, knee or shoulder joint. The robust instrument can easily pass through the tough joint capsule and provide a thorough diagnostic evaluation of possible reasons for implant failure within a short period of time.



28902 RF

28902 RF

RETROFORCE® Biopsy Punch, for biopsy of the joints, backward cutting, pointed, diameter 4 mm, working length 13 cm, with suction channel for the aspiration of synovial fluid, suitable for use under local anesthesia or arthroscopy

including:

Outer Sheath, with LUER-Lock connector

Inner Sheath, with backward cutting punch

Handle, without ratchet

optional:

28902 HGR **Handle**, with ratchet

Components/Spare Parts see chapter 18





JOINT AND BONE RECONSTRUCTION

INSTRUMENTS FOR MICROFRACTURING . . .74


INSTRUMENTS FOR
AUTOLOGOUS CHONDROCYTE
TRANSPLANTATION75

INSTRUMENTS FOR
BONE BLOCK HARVESTING76-77

INSTRUMENTS FOR
CANCELLOUS BONE APPLICATION78-79

Instruments for Microfracturing

Chisels



28140 CE



28140 CE **Microfracture Chisel**, curved 70°, working length 18 cm



28140 CD **Microfracture Chisel**, curved 30°, working length 18 cm



28728 CC **Microfracture Chisel**, straight, working length 12 cm



28728 CD **Microfracture Chisel**, angled 30°, working length 12 cm




28728 CE **Microfracture Chisel**, angled 70°, working length 12 cm



28728 CG **Microfracture Chisel**, angled 30°, working length 9 cm



28728 CH **Microfracture Chisel**, angled 70°, working length 9 cm



28140 CF



28140 CF **NEW** **Microfracture Chisel**, curved 90°, working length 16 cm

Please note: Provided that an initial order is placed, it is recommended to buy a complete set of instruments.

Instruments for Autologous Chondrocyte Transplantation (ACT)

Autologous Chondrocyte Transplantation (ACT) is an established therapy for treating cartilage defects in the knee. A special instrument was designed for a gentle and effective extraction of cartilage cells.

The biopsy set was designed to meet the specific demands of ACT:

- Extraction of a suitable cartilage cylinder
- Atraumatic and safe use
- Easy handling
- Effective extraction of cartilage cells
- Osteochondral cylinder to improve healing of the extraction site



28904 S

28904 S

Biopsy Set

including:

Biopsy Punch, with cutting tooth, to extract cartilage cells for ACT

Obturator, to penetrate connective tissue without extracting tissue and to extrude excised biopsy sample

O-Ring, package of 10

Instruments for Bone Reconstruction


Bone Block Harvesting

Instrumentation for bone block harvesting consists of an instrument set for the safe and easy harvesting of autologous bone or cartilage-bone-blocks for cancellous bone grafting.

The bone-block harvesting system can be used for bridging bone gaps with an opening wedge osteotomy, to treat joint stiffness or for cruciate ligament revision surgery.

Special Features:

- **Wide range of harvesting sizes: 5 – 12 mm**
- **Various sizes are color-coded**
- **Ergonomic handle for optimal force regulation during harvesting**
- **Sharp cutting edge for precise harvesting**



28729 HGA

- 28729 HGA **Sleeve**, inner diameter 5 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPA, color code: green
- 28729 HGB **Sleeve**, inner diameter 6 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPB, color code: black
- 28729 HGC **Sleeve**, inner diameter 7 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPC, color code: blue
- 28729 HGD **Sleeve**, inner diameter 8 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPD, color code: red
- 28729 HGE **Sleeve**, inner diameter 9 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPE, color code: yellow
- 28729 HGF **Sleeve**, inner diameter 10 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPF, color code: white-yellow
- 28729 HGG **Sleeve**, inner diameter 11 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPG, color code: white-green
- 28729 HGH **Sleeve**, inner diameter 12 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPH, color code: white-blue



28729 HH

- 28729 HH **Handle**, for use with Tap 28729 HP




28729 HP

- 28729 HP **Tap**, for use with Handle 28729 HH

Instruments for Bone Reconstruction

Bone Block Harvesting



28729 HPA

- 28729 HPA **Tappet**, diameter 5 mm, for use with Handle 28729 HH and Sleeve 28729 HGA, color code: green
- 28729 HPB **Tappet**, diameter 6 mm, for use with Handle 28729 HH and Sleeve 28729 HGB, color code: black
- 28729 HPC **Tappet**, diameter 7 mm, for use with Handle 28729 HH and Sleeve 28729 HGC, color code: blue
- 28729 HPD **Tappet**, diameter 8 mm, for use with Handle 28729 HH and Sleeve 28729 HGD, color code: red
- 28729 HPE **Tappet**, diameter 9 mm, for use with Handle 28729 HH and Sleeve 28729 HGE, color code: yellow
- 28729 HPF **Tappet**, diameter 10 mm, for use with Handle 28729 HH and Sleeve 28729 HGF, color code: white-yellow
- 28729 HPG **Tappet**, diameter 11 mm, for use with Handle 28729 HH and Sleeve 28729 HGG, color code: white-green
- 28729 HPH **Tappet**, diameter 12 mm, for use with Handle 28729 HH and Sleeve 28729 HGH, color code: white-blue



174800

- 174800 **Metal Mallet**, with plastic replacement head, length 22.5 cm

Instruments for Bone Reconstruction

Cancellous Bone Applicators

Several arthroscopic interventions – mostly revision procedures – require the filling of bone defects.

Such bone-filling procedures may be indicated in the following cases:

1. Enlarged tunnels following ligament reconstruction
2. Subchondral bone cysts
3. Tumors
4. Fractures (e.g. compression fractures of the tibial head)

Up to now, the filling of defect zones with cancellous bone or bone graft materials has not been complex and extremely time-consuming. Arthroscopic treatment of defect zones in the femur in particular was difficult to perform.

As a result, this innovative and straightforward system offers several advantages:

- Easy handling
- Time-saving procedures
- Controllable application depth
- For use with ENDOCAMELEON®




Fig. 1: Several arthroscopic interventions – mostly revision procedures – require the filling of bone defects.




Fig. 2: Insertion and application of the filling material




Fig. 3: View of the femoral tunnel filled with cancellous bone

Instruments for Bone Reconstruction

Cancellous Bone Applicators



28906 CB

28906 CB **Cancellous Bone Applicator Set**, diameter 6 mm,
color code: red
including:
Cancellous Bone Applicator
Tappet
Sealing Cap
Plug



28907 CB

28907 CB **Same**, diameter 7 mm,
color code: yellow



28908 CB

28908 CB **Same**, diameter 8 mm,
color code: blue



28909 CB

28909 CB **Same**, diameter 9 mm,
color code: green



28910 CB

28910 CB **Same**, diameter 10 mm,
color code: white

Components/Spare Parts see chapter 18





INSTRUMENTS FOR THE KNEE

BASIC INSTRUMENTS82-85

MENISCUS AND MPFL
RECONSTRUCTION86-91

CRUCIATE LIGAMENT
RECONSTRUCTION92-113

IMPLANTS114-125


Knee Laxity Tester for Instrumented Stability Testing

Instrumented stability measurement of the cruciate ligaments is a clinical examination that provides exact and reproducible measurements of the movement of the tibia in the case of cruciate ligament instability.

The Knee Laxity Tester (KLT) was developed to allow straightforward, fast and accurate instrumented stability tests in the examination room.

Special Features:

- Practical
- Easy to use
- Reproducible results
- Exact measurements



28729 KLT **Knee Laxity Tester**, for instrumented stability testing




Fig. 1: Using the knee laxity tester when performing a Lachman test

Instruments for Ligament Reconstruction

Special Features:

- Preparation of different transplants (hamstrings, quadriceps tendon and patellar tendon) for various fixation techniques
- Measuring scales for rapid and safe transplant preparation using FLIPPTACK
- User-friendly



28729 SB

28729 SB **Tendon Board**, including
FLIPPTACK Retainer 28729 SC



28729 SC

28729 SC **FLIPPTACK Retainer**



28729 FK


28729 FK **Thread Clip**




28729 P

28729 P **Tissue Forceps**, 1 x 2 teeth, medium,
distal curved to left, length 14.5 cm

Components/Spare Parts see chapter 18



28729 D-6 **Drilling Wire**, spiral shape, with eyelet, diameter 2.4 mm, length 38 cm, unsterile, for single use, package of 6, for use with Undercut Drills 28729 BA – BH, Collar Burrs 28729 BLC – BLF and Drills 28729 GA – GE



28729 E **Larding Wire**, pyramidal tip, diameter 2.4 mm, length 32 cm, unsterile, for single use, package of 10, for use with Undercut Drills 28729 BA – BH, Collar Burrs BLC – BLF and Drills 28729 GA – GE



- 28729 BH **Undercut Drill**, cannulated, diameter 4.5 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
- 28729 BA **Same**, diameter 5 mm
 - 28729 BB **Same**, diameter 5 mm
 - 28729 BI **Same**, diameter 5.5 mm
 - 28729 BC **Same**, diameter 6 mm
 - 28729 BK **Same**, diameter 6.5 mm
 - 28729 BD **Same**, diameter 7 mm
 - 28729 BL **Same**, diameter 7.5 mm
 - 28729 BE **Same**, diameter 8 mm
 - 28729 BM **Same**, diameter 8.5 mm
 - 28729 BF **Same**, diameter 9 mm
 - 28729 BN **Same**, diameter 9.5 mm
 - 28729 BG **Same**, diameter 10 mm
 - 28729 BO **Same**, diameter 10.5 mm
 - 28729 BH **Same**, diameter 11 mm



28729 L **Length Gauge**, for cruciate ligament reconstruction, graduated, working length 23 cm




28729 TL **Depth Gauge**, for cruciate ligament reconstruction, working length 22.5 cm, for use with Larding Wire 28729 E

Knee

Basic Instruments




28729 FF



28729 FF

Thread Catcher, for cruciate ligament reconstruction, working length 23 cm



28171 SGN



28171 SGN

SILGRASP® Suture Grasper, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 14 cm



28729 NO



28729 NO

Notch Chisel, curved, 15° downwards, working length 13 cm

Instruments for the All-Inside Suture

Meniscus Suture for the Posterior Horn area of the Lateral and Medial Meniscus

This meniscus suture set was specially developed for use with all-inside suture on the posterior horn area of the lateral and medial meniscus. A fundamental advantage of this suture set lies in the simple thread

release. After passing through the tip of the suture hooks and advancing the thread, the latter appears inside the joint. The thread may now be easily pulled out of the joint with the grasping forceps.



28179 HG

28179 HG

Handle, for use with monofilament threads size USP 2-0 to 2, for use with Suture Attachments 28179 PA – PH, 28728 NA – NG, Wheel Attachment 28179 HR and Wheel 28179 R



28179 HR/R

28179 HR

Wheel Attachment, for use with monofilament threads size USP 2-0 to 2, for use with Handle 28179 HG and Wheel 28179 R

28179 R

Wheel, for use with monofilament threads size USP 2-0 to 2, for use with Wheel Attachment 28179 HR

Instruments for the All-Inside Suture

Meniscus Suture for the Posterior Horn area of the Lateral and Medial Meniscus


- | | | |
|--|----------|--|
| | 28728 NA | Suture Attachment , straight, working length 13 cm, for use with Handle 28179 HG |
| | 28728 NB | Suture Attachment , distal angled 180° to the right, straight, working length 13 cm, for use with Handle 28179 HG |
| | 28728 NC | Suture Attachment , distal angled 180° to the left, straight, working length 13 cm, for use with Handle 28179 HG |
| | 28728 ND | Suture Attachment , distal angled 360° to the right, straight, working length 13 cm, for use with Handle 28179 HG |
| | 28728 NE | Suture Attachment , distal angled 360° to the left, straight, working length 13 cm, for use with Handle 28179 HG |
| | 28728 NF | Suture Attachment , distal angled 20° upwards, straight, working length 13 cm, for use with Handle 28179 HG |
| | 28728 NG | Suture Attachment , distal angled 20° upwards, straight, working length 14 cm, for use with Handle 28179 HG |



28179 R1 **Cleaning Adaptor**, for use with Suture Attachments 28179 PA – PH and 28728 NA – NG



28179 R2 **Cleaning Adaptor**, for use with Handle 28179 HG



28728 NJ **Suture Grasper, dismantling**, jaw length 5.5 mm, straight jaws, straight sheath, working length 8 cm

Please note: Provided that an initial order is placed, it is recommended to buy a complete set of instruments.

Instruments for Refixation of the Meniscus Root

The target guide was designed for refixation of the posterior meniscal root to the outer meniscus. In the case of a wide intraarticular space, the target guide can also be used for refixation of the posterior root to the inner meniscus.

The target guide enables two larding wires to be pre-drilled until they appear submeniscal under the meniscal horn.

Following adequate positioning, the initial centimeters of the K-wires are overdrilled with a 4.5 mm undercut drill to facilitate the introduction of the prepared cannulas

with suture loops. After the larding wires are withdrawn, cannulas with PDS suture loops are advanced through the channels until they appear in the submeniscal area. After any required repositioning of the meniscus, the detached posterior meniscal horn is pierced with the suture cannula. Once both suture loops emerge in the submeniscal area, the loops are widened and a fixation suture is placed. This is then withdrawn through the cannula together with the PDS suture loop. The resulting U-suture fixates the posterior horn root.



28729 ZRF

28729 ZRF **Target Guide Root Refixation**, for refixation of the meniscus



28728 MH

28728 MH **HALF PIPE®**, without handle, small, working length 95 mm



28572 NJ



28572 NJ **SILGRASP® PRO Suture Grasper**, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18

Knee

MPFL Reconstruction with the Quadriceps Tendon

This system was especially developed for harvesting the quadriceps tendon for MPFL reconstruction.

Special Features:


- Safe subcutaneous tendon harvesting
- Defined harvesting depth
- Attractive cosmetic results



28185 MH

28185 MH **Handle**, working length 10 cm

For use with:




28185 FA

28185 FA **Tendon Knife**, for removal of quadriceps tendon for MPFL reconstruction, vertical parallel cutting, width 10 mm, height 4 mm, sterile, for single use, for use with Handle 28185 MH



28185 FB **Same**, width 12 mm




28185 EA

28185 EA **Tendon Separator**, for removal of the quadriceps tendon for MPFL reconstruction, horizontal parallel cutting, height 2 mm, sterile, for single use, for use with Handle 28185 MH



28185 EB **Same**, height 3 mm



28185 QS

28185 QS **Quadriceps Tendon Cutter**, for subcutaneous terminal cutting of the quadriceps tendon, working length 15 cm

A workable set requires the use of additional implants see pages 114-125

Special Features:

- The implant is made of the bioresorbable material Poly(L-lactide-co-D,L-lactide)
- For Suture Anchors 2870411 BP and 2870514 BP, the use of suture material size USP 2 is recommended
- Very good degradation behavior



2870411 BP **BIOPLUG, bioresorbable suture anchor**, diameter 4.2 mm, length 11 mm, sterile, for single use, for use with Inserter 28179 TI or 28179 KI



28179 KB



28179 KB **Drill**, for preparation of the tunnel for BIOPLUG 2870411 BP, with laser marking for the depth of the drill hole, length 7 cm



28179 KI



28179 KI **Inserter**, with lateral thread guide and thread clip at the handle, working length 9 cm, for use with BIOPLUG 2870411 BP

A workable set requires the use of additional harvesting instrumentation see page 93

A workable set requires the use of additional implants see pages 114-125

Knee

MPFL Reconstruction with the Gracilis Tendon and the Patellar Tunnel

Special Features:

- Impant-free fixation on the patella
- Optimal handling
- Safe drilling in the patella
- Stable bone bridge



28728 BL

28728 BL

Gauge, for MPFL reconstruction,
for use with Drill 28728 BLB



28728 BLB

Drill, for preparation of the tunnel for
MPFL reconstruction, with penetration stop,
diameter 4.5 mm, for use with Gauge 28728 BL

A workable set requires the use of additional harvesting instrumentation see page 93
A workable set requires the use of additional implants see pages 114-125

Knee

Basic Instrumentation for Anterior Cruciate Ligament Reconstruction



28729 ZG

28729 WY

Handle, with ratchet, for use with Inserts 28729 VX – VZ, WA – WD, WU – WZ, ZM – ZQ

28729 ZG

Special Features:

- **Attachments for femoral tunnel placement via a medial port**



28729 WX

Femoral Target Guide Attachment, for ACL reconstruction via a medial port, with 5 mm offset, for use with Handle 28729 ZG

28729 WY

Same, with 6 mm offset

28729 WZ

Same, with 7 mm offset

28729 VX

Same, with 8 mm offset

28729 VY

Same, with 9 mm offset

28729 VZ

Same, with 10 mm offset

Special Features:

- **Attachments for femoral tunnel placement via a medial or transtibial port**



28729 ZM

Femoral Target Guide Attachment, for ACL reconstruction, with 4 mm offset, for use with Handle 28729 ZG

28729 ZN

Same, with 5 mm offset

28729 ZO

Same, with 6 mm offset

28729 ZP

Same, with 7 mm offset

28729 ZQ


Same, with 8 mm offset

Knee

Anterior Cruciate Ligament Reconstruction with Hamstrings

Special Features:

- Length marks on the tendon stripper enables measurement of the tendon during removal
- Smaller tendon stripper for atraumatic removal of the gracilis tendon



28729 A



28729 A

Tendon Stripper, graduated, diameter 5.5 mm, length 30 cm



28729 AB

Tendon Stripper, graduated, diameter 7 mm, length 30 cm



28729 AC

Open Tendon Stripper, graduated, diameter 7.5 mm, length 30 cm



28729 SH

Tendon Hook



28729 A

213008

PLESTER Raspatory, width 8 mm, length 18 cm



28729 SA



28729 SE



28729 SD

28729 SA

Tendon Thickness Tester, for determination of tendon thickness size 6 – 10.5 mm at intervals of 0.5 mm

28729 SE

Same, size 7 – 12 mm at intervals of 0.5 mm

28729 SD

Same, size 4 – 7 mm at intervals of 0.5 mm

Knee

Anterior Cruciate Ligament Reconstruction with Hamstrings Single Bundle Technique

Special Features:

- Secure positioning of the tunnel
- Measurement of the length of the tibial tunnel before placing the tunnel
- Simple and secure fixation of the guide pin
- Stable construction prevents winding and torsion of the target guide



28729 ZA

28729 ZA **Tibial Target Guide**, for ACL reconstruction



28729 DG

28729 DG **Guide Sleeve**, for the correction of the tibial tunnel, with concentric holes for a 2.4 mm guide wire diameter, realignment possible from 3 – 9 mm

A workable set requires the use of additional implants see pages 114-125
Components/Spare Parts see chapter 18

Knee

Anterior Cruciate Ligament Reconstruction with Hamstrings Double Bundle Technique




28729 SBD

28729 SBD **Tendon Board Add-On**, for the double bundle retainer technique, including FLIPPTACK Retainer 28729 SC

Special Features:

- Easy and reproducible application
- Orientation along anatomic landmarks
- Femoral tunnel placement via a medial port
- Variability in spacing of tunnels



28729 WU

28729 WU **Femoral Target Guide Attachment**, for the ACL double bundle technique, with 8 mm offset, for use with Handle 28729 ZG

28729 WV **Same**, with 9 mm offset

28729 WW **Same**, with 10 mm offset

28729 ZG **Handle**, with ratchet, for use with Inserts 28729 VX – VZ, WA – WD, WU – WZ, ZM – ZQ



28729 ZG



28729 WT



28729 WT **Tibial Target Guide**, for the ACL double bundle technique, exit point from the tibial plateau adjustable between 8 – 10 mm

A workable set requires the use of Tendon Board 28729 SB see page 83
A workable set requires the use of additional implants see pages 114-125
Components/Spare Parts see chapter 18

Knee

Anterior Cruciate Ligament Reconstruction with the Quadriceps Tendon



28185 MH

28185 MH **Handle**, working length 10 cm

For use with:



28185 FC

28185 FC **Tendon Knife**, for removal of the quadriceps tendon for cruciate ligament reconstruction, vertical parallel cutting, width 8 mm, height 6 mm, sterile, for single use, for use with Handle 28185 MH



28185 FD **Same**, width 9 mm

28185 FE **Same**, width 10 mm

28185 FF **Same**, width 12 mm




28185 EC

28185 EC **Tendon Separator**, for removal of the quadriceps tendon for cruciate ligament reconstruction, horizontal parallel cutting, height 5 mm, sterile, for single use, for use with Handle 28185 MH



28185 MB

28185 MB **Tendon Thickness Tester**, for determining the thickness of the quadriceps tendon



28185 QS

28185 QS **Quadriceps Tendon Cutter**, for subcutaneous terminal cutting of the quadriceps tendon, working length 15 cm

A workable set requires the use of additional implants see pages 114-125

Knee

Anterior Cruciate Ligament Reconstruction with the Quadriceps Tendon

Anatomical studies have shown that the insertion area of the anterior cruciate ligament is not circular. To adapt to the anatomical conditions in cruciate ligament recon-

struction using transplants with femoral bone blocks, special instruments were developed that enable the creation of rectangular channels.

Special Features:

- Allows use of small bone blocks
- Anatomic channel shape
- Suitable for both femoral and tibial systems
- Easy and safe application
- Suitable for revision surgery



28185 GA

- 28185 GA **Rasp**, femoral, cannulated, straight, coarse, one side smooth, width 8 mm, height 5 mm, working length 15 cm
- 28185 GB **Same**, width 10 mm



28185 HA

- 28185 HA **Dilator**, rectangular, femoral, cannulated, width 8 mm, height 5 mm, working length 15 cm
- 28185 HB **Same**, width 9 mm
- 28185 HC **Same**, width 10 mm
- 28185 HD **Same**, width 12 mm



174800

- 174800 **Metal Mallet**, with plastic replacement head, length 22.5 cm


Components/Spare Parts see chapter 18

Knee

Anterior Cruciate Ligament Reconstruction with the Quadriceps Tendon

Special Features:

- Enables drilling of up to 3 larding wires
- Creation of an oblong tibial canal possible



28729 CF

28729 CF

Tibial Target Guide, for the placement of a maximum of 3 parallel drilling wires



28185 IA

28185 IA

Dilator, rectangular, tibial, cannulated, width 8.5 mm, height 5.5 mm, working length 15 cm

28185 IB

Same, width 9.5 mm

28185 IC

Same, width 10.5 mm

28185 ID

Same, width 12.5 mm

Components/Spare Parts see chapter 18

Knee

Anterior Cruciate Ligament Reconstruction with the Patellar Tendon (Bone-Tendon-Bone)



28729 PD

- 28729 PC **Patellar Saw Template**, for harvesting a bone block with tendon (BTB), width 7 mm
- 28729 PD **Same**, width 8 mm
- 28729 PE **Same**, width 9 mm
- 28729 PF **Same**, width 10 mm
- 28729 PG **Same**, width 11 mm



28729 PA

- 28729 PA **Chisel**, width 8 mm



28729 PB


- 28729 PB **Tendon Knife**, blunt



28729 PH



28729 PJ



28729 PK

- 28729 PH **Measuring Block**, to determine the size of a bone block
- 28729 PJ **Bone Block Holder**, for use with Tendon Board 28729 SB
- 28729 PK **Bone Forceps**, for use with Measuring Block 28729 PH

A workable set requires the use of Tendon Board 28729 SB see page 83
A workable set requires the use of additional implants see pages 114-125
Basic Instruments see page 83

Knee

Anterior Cruciate Ligament Reconstruction with the Patellar Tendon (Bone-Tendon-Bone)



28729 ZF

28729 ZF **CHANNEL-LOCK® Tibial Target Guide**, for ACL reconstruction, tunnel angle between 40° and 55°, adjustable in 5° increments



28729 PL

28729 PL **Coring Reamer**, for harvesting a bone block with tendon (BTB), with coil, diameter 7 mm, for use with Handle 28729 PQ

28729 PM **Same**, diameter 8 mm

28729 PN **Same**, diameter 9 mm

28729 PO **Same**, diameter 10 mm

28729 PP **Same**, diameter 11 mm



28729 PQ

28729 PQ **Handle**, T-shaped, for use with Fluted Coring Reamers 28729 PL – PP and Revision Blades 28728 TA – TI


Components/Spare Parts see chapter 18

Knee

Posterior Cruciate Ligament Reconstruction

Special Features:

- Precise, reproducible tunneling



28729 WA

28729 WA

Femoral Target Guide Attachment, for PCL reconstruction, for use through the anterolateral port, for precise anatomic placement of the femoral tunnel, 4 locking positions, for drill diameter 7 mm, for use with Handle 28729 ZG

28729 WB

Same, for drill diameter 8 mm

28729 WC

Same, for drill diameter 9 mm

28729 WD

Same, for drill diameter 10 mm

28729 ZG

Handle, with ratchet, for use with Inserts 28729 VX – VZ, WA – WD, WU – WZ, ZM – ZQ

28729 ZG



28729 MH



28729 MH

Femoral Target Guide, for PCL reconstruction, graduated, working length 14.5 cm




28729 R

Raspatory, for PCL reconstruction, working length 13 cm

A workable set requires the use of additional implants see pages 114-125

Knee

Posterior Cruciate Ligament Reconstruction




28729 ZB

- 28729 ZB **Tibial Target Guide**, for PCL reconstruction
- 28729 ZL **Same**, curved to left
- 28729 ZR **Same**, curved to right

Special Features:

- Determination of the tunnel length
- Protected target area
- Precise determination of the distance from the tibial plateau surface to the exit of the tibial tunnel on the posterior side of the tibia



28729 ZBB

- 28729 ZBB **Tibial Target Guide**, large, for PCL reconstruction

Components/Spare Parts see chapter 18



28729 GA

28729 GA	Drill , cannulated, diameter 6 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E
28729 GB	Same , diameter 7 mm
28729 GC	Same , diameter 8 mm
28729 GD	Same , diameter 9 mm
28729 GE	Same , diameter 10 mm

Cannulated Drill Sleeves for use with cannulated Drills 28729 GA – GE

Special Features:

- Safe due to self-centering drills
- Easy to use




28729 HA

28729 HA	Cannulated Drill Sleeve , for use with Drill 28729 GA
28729 HB	Cannulated Drill Sleeve , for use with Drill 28729 GB
28729 HC	Cannulated Drill Sleeve , for use with Drill 28729 GC
28729 HD	Cannulated Drill Sleeve , for use with Drill 28729 GD
28729 HE	Cannulated Drill Sleeve , for use with Drill 28729 GE

Knee

Posterior Cruciate Ligament Reconstruction



28729 AH



28729 AH

Awl, for PCL reconstruction,
working length 20 cm



28729 EH



28729 EH

Elevator, for PCL reconstruction,
working length 15.5 cm



28729 WH



28729 WH

Elevator, for PCL reconstruction,
with T-shaped handle



28729 WJ

Thread Catcher, for PCL reconstruction,
with T-shaped handle

In revision surgery, it is often necessary to remove previous implants (titanium interference screws, staples). It is therefore recommended to have special

instrumentation at hand that enables implants to be removed quickly.





To remove titanium interference screws, a revision screwdriver set was developed to accommodate all standard interference screw sizes. In many cases, it is

necessary to remove bone from the screwdriver insertion site. Microfracture chisels have been included in the screwdriver revision set for this purpose.

Special Features:

- **Modular system: Quick coupling via T-Handle**
- **Revision screwdriver attachments available for all standard screw sizes**
- **Self-centering: Enables removal of interference screws even if access is unfavorable**
- **Tapered tip: Enables use even in the case of slightly deformed screw heads**

28728 T



Revision Set

including:

- 28728 TA **Revision Screwdriver Blade**, size 1.9 mm, working length 12.5 cm
- 28728 TB **Revision Screwdriver Blade**, size 2.3 mm, working length 12.5 cm
- 28728 TC **Revision Screwdriver Blade**, size 2.4 mm, working length 12.5 cm
- 28728 TD **Revision Screwdriver Blade**, size 2.7 mm, working length 12.5 cm
- 28728 TE **Revision Screwdriver Blade**, size 3.4 mm, working length 12.5 cm
- 28728 TF **Large Fragment Screwdriver Blade**, size 3.5 mm, working length 12.5 cm
- 28728 TG **Small Fragment Screwdriver Blade**, size 2.5 mm, working length 12.5 cm
- 28728 TH **Microfracture Chisel**, straight, working length 12.5 cm
- 28728 TI **Microfracture Chisel**, curved 30°, working length 12.5 cm
- 28729 PQ **Handle**, T-shaped, for use with 28728 TA – TI




Handle

Instrumentation for bone block harvesting consists of an instrument set for the safe and easy harvesting of autologous bone or cartilage-bone-blocks for cancellous bone grafting.

The bone-block harvesting system can be used for bridging bone gaps with an opening wedge osteotomy, to treat joint stiffness or for cruciate ligament revision surgery.

Special Features:

- **Wide range of harvesting sizes: 5 – 12 mm**
- **Various sizes are color-coded**
- **Ergonomic handle for optimal force regulation during harvesting**
- **Sharp cutting edge for precise harvesting**



28729 HGA

- 28729 HGA **Sleeve**, inner diameter 5 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPA, color code: green
- 28729 HGB **Sleeve**, inner diameter 6 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPB, color code: black
- 28729 HGC **Sleeve**, inner diameter 7 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPC, color code: blue
- 28729 HGD **Sleeve**, inner diameter 8 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPD, color code: red
- 28729 HGE **Sleeve**, inner diameter 9 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPE, color code: yellow
- 28729 HGF **Sleeve**, inner diameter 10 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPF, color code: white-yellow
- 28729 HGG **Sleeve**, inner diameter 11 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPG, color code: white-green
- 28729 HGH **Sleeve**, inner diameter 12 mm, working length 70 mm, for use with Handle 28729 HH, Tap 28729 HP and Tappet 28729 HPH, color code: white-blue




28729 HH

- 28729 HH **Handle**, for use with Tap 28729 HP



28729 HP

- 28729 HP **Tap**, for use with Handle 28729 HH



28729 HPA

- 28729 HPA **Tapet**, diameter 5 mm, for use with Handle 28729 HH and Sleeve 28729 HGA, color code: green
- 28729 HPB **Tapet**, diameter 6 mm, for use with Handle 28729 HH and Sleeve 28729 HGB, color code: black
- 28729 HPC **Tapet**, diameter 7 mm, for use with Handle 28729 HH and Sleeve 28729 HGC, color code: blue
- 28729 HPD **Tapet**, diameter 8 mm, for use with Handle 28729 HH and Sleeve 28729 HGD, color code: red
- 28729 HPE **Tapet**, diameter 9 mm, for use with Handle 28729 HH and Sleeve 28729 HGE, color code: yellow
- 28729 HPF **Tapet**, diameter 10 mm, for use with Handle 28729 HH and Sleeve 28729 HGF, color code: white-yellow
- 28729 HPG **Tapet**, diameter 11 mm, for use with Handle 28729 HH and Sleeve 28729 HGG, color code: white-green
- 28729 HPH **Tapet**, diameter 12 mm, for use with Handle 28729 HH and Sleeve 28729 HGH, color code: white-blue



174800

174800

Metal Mallet, with plastic replacement head, length 22.5 cm

Several arthroscopic interventions – mostly revision procedures – require the filling of bone defects.

Such bone-filling procedures may be indicated in the following cases:

1. Enlarged tunnels following ligament reconstruction
2. Subchondral bone cysts
3. Tumors
4. Fractures (e.g. compression fractures of the tibial head)

Up to now, the filling of defect zones with cancellous

bone or bone graft materials has not been complex and extremely time-consuming. Arthroscopic treatment of defect zones in the femur in particular was difficult to perform.

As a result, this innovative and straightforward system offers several advantages:

- Easy handling
- Time-saving procedures
- Controllable application depth
- For use with ENDOCAMELEON®




Fig. 1: Several arthroscopic interventions – mostly revision procedures – require the filling of bone defects.




Fig. 2: Insertion and application of the filling material



Fig. 3: View of the femoral tunnel filled with cancellous bone

Knee

Cruciate Ligament Revision Surgery



28906 CB

28906 CB **Cancellous Bone Applicator Set**, diameter 6 mm,
color code: red
including:
Cancellous Bone Applicator
Tappet
Sealing Cap
Plug



28907 CB

28907 CB **Same**, diameter 7 mm,
color code: yellow



28908 CB

28908 CB **Same**, diameter 8 mm,
color code: blue



28909 CB

28909 CB **Same**, diameter 9 mm,
color code: green



28910 CB

28910 CB **Same**, diameter 10 mm,
color code: white

Components/Spare Parts see chapter 18

Special Features:

- Dilation of the drill channel and notching in one step
- Cancellous bone compression through tunnel dilation
- The direction of the interference screw is pre-determined → no migration of the screw during insertion



28729 DFO



- | | |
|-----------|---|
| 28729 DFM | Dilator with Fin , for dilating the femoral drill channel to diameter 4 mm and simultaneous placement of a notch 17 mm in length |
| 28729 DFO | Dilator with Fin , cannulated, for dilating the femoral drill channel to diameter 6 mm and simultaneous placement of a notch 25 mm in length |
| 28729 DFP | Same , for dilating the femoral drill channel to diameter 6.5 mm |
| 28729 DFQ | Same , for dilating the femoral drill channel to diameter 7 mm |
| 28729 DFR | Same , for dilating the femoral drill channel to diameter 7.5 mm |
| 28729 DFS | Same , for dilating the femoral drill channel to diameter 8 mm |
| 28729 DFT | Same , for dilating the femoral drill channel to diameter 8.5 mm |
| 28729 DFU | Same , for dilating the femoral drill channel to diameter 9 mm |
| 28729 DFV | Same , for dilating the femoral drill channel to diameter 9.5 mm |



Dilating a PL canal using a dilator with fin

Components/Spare Parts see chapter 18

Knee

Fine Tunnel Preparation



28900 H

28900 H **Handle**, T-shaped, with quick coupling system, for use with Blade Dilators 28960 B/BB/C/CC/D/DD/E/EE/F/FF/G and Center Punch 28900 CP



28900 CP

28900 CP **Center Punch**, straight, with pyramidal tip, working length 14.5 cm, for use with Handle 28900 H



28960 B



28960 F

- 28960 B **Blade Dilator**, cannulated, diameter 6 mm, working length 14.5 cm, scaled to 70 mm, for compression of the tibial and femoral cancellous bone, for use with Handle 28900 H
- 28960 BB **Same**, diameter 6.5 mm
- 28960 C **Same**, diameter 7 mm
- 28960 CC **Same**, diameter 7.5 mm
- 28960 D **Same**, diameter 8 mm
- 28960 DD **Same**, diameter 8.5 mm
- 28960 E **Same**, diameter 9 mm
- 28960 EE **Same**, diameter 9.5 mm
- 28960 F **Same**, diameter 10 mm
- 28960 FF **Same**, diameter 10.5 mm
- 28960 G **Same**, diameter 11 mm

Knee

Fine Tunnel Preparation




28729 N



28729 N

Notcher, with fin-like blade to assist screw insertion, working length 15 cm



28729 NM



28729 NM

Chisel, for creating a bone wedge, working length 13 cm



28729 NN



28729 NN

Chisel, for creating a bone wedge, with wide handle, working length 13 cm

FLIPPTACK and ENDOTACK® – Titanium

FLIPPTACK

- Individual preparation of a defined thread loop
- Implant preparation before operation possible
- Easy to use

ENDOTACK®

- Secure fixation
- No tilting of fixation button
- Transplant tension defined by testing with tensiometer
- Correction of transplant tension by rotating of fixation button with the button key
- Simple and safe handling



FLIPPTACK
from Titanium Ti-6AL-4V ELI



ENDOTACK®
from titanium Ti-6AL-4V ELI

FLIPPTACK and ENDOTACK® – Fixation Buttons



28729 FT

- 28729 FT **FLIPPTACK**, extracortical fixation button, 4 x 12 mm, sterile, for single use
- 28729 FC **Catgut Polyester-S white**, 3 x 75 cm, USP 7, sterile, for single use, package of 24, for use with FLIPPTACK, extracortical fixation button



28729 TT



28729 MT

- 28729 TT **ENDOTACK®**, tibial fixation button, 10 x 16 mm, sterile, for single use
- 28729 MT **Mini ENDOTACK®**, tibial fixation button, 8 x 12 mm, sterile, for single use

Knee

Implants

Fixation Buttons



28729 ST

28729 ST **Positioning Device**, for use with ENDOTACK® 28729 TT


28729 SM **Positioning Device**, for use with Mini ENDOTACK® 28729 MT, color code: red



28729 MS


28729 MS **Button Wrench**, for use with ENDOTACK® 28729 TT

28729 MM **Button Wrench**, for use with Mini ENDOTACK® 28729 MT, color code: red



28729 TM

28729 TM **Tensiometer**, for measuring and controlling the tension of the graft



28729 KK

28729 KK **Knot Holder**, small, 1 x 1 mm, working length 14.5 cm

MEGA FIX® – Bioresorbable

MEGA FIX® B, P, C and CP

- Extreme torsional stability
- Three-dimensional bony ingrowth in perforated MEGA FIX® screws (MEGA FIX® P and CP)
- Optimal connection between the MEGA FIX® screw and screwdriver (CROSSDRIVE®)
- Minimized risk of graft damage thanks to optimal thread design
- High fixation strength
- Wide range of indications
- Complete absorption
- Osseous replacement following absorption



MEGA FIX® B and P

from the bioresorbable material Poly(L-lactide-co-D,L-lactide)



MEGA FIX® C and CP

from an optimal mixing ratio of 80:20 between the bioresorbable material Poly(L-lactide-co-D,L-lactide) and the ceramic material beta-tricalcium phosphate (β -TCP)

MEGA FIX® B



2870823 B

- 2870619 B **MEGA FIX® B**, bioresorbable interference screw, diameter 6 mm, length 19 mm, sterile, for single use
- 2870623 B **Same**, length 23 mm

- 2870719 B **MEGA FIX® B**, bioresorbable interference screw, diameter 7 mm, length 19 mm, sterile, for single use
- 2870723 B **Same**, length 23 mm
- 2870728 B **Same**, length 28 mm

- 2870819 B **MEGA FIX® B**, bioresorbable interference screw, diameter 8 mm, length 19 mm, sterile, for single use
- 2870823 B **Same**, length 23 mm
- 2870828 B **Same**, length 28 mm

- 2870923 B **MEGA FIX® B**, bioresorbable interference screw, diameter 9 mm, length 23 mm, sterile, for single use
- 2870928 B **Same**, length 28 mm

MEGA FIX® P



2870828 P


- 2870823 P **MEGA FIX® P**, bioresorbable interference screw, perforated, diameter 8 mm, length 23 mm, sterile, for single use
- 2870828 P **Same**, length 28 mm

- 2870923 P **MEGA FIX® P**, bioresorbable interference screw, perforated, diameter 9 mm, length 23 mm, sterile, for single use
- 2870928 P **Same**, length 28 mm
- 2870935 P **Same**, length 35 mm

- 2871028 P **MEGA FIX® P**, bioresorbable interference screw, perforated, diameter 10 mm, length 28 mm, sterile, for single use
- 2871035 P **Same**, length 35 mm

- 2871135 P **MEGA FIX® P**, bioresorbable interference screw, perforated, diameter 11 mm, length 35 mm, sterile, for single use

MEGA FIX® C



2870819 C

- 2870619 C **MEGA FIX® C**, bioresorbable composite interference screw, diameter 6 mm, length 19 mm, sterile, for single use
- 2870623 C **Same**, length 23 mm
- 2870719 C **MEGA FIX® C**, bioresorbable composite interference screw, diameter 7 mm, length 19 mm, sterile, for single use
- 2870723 C **Same**, length 23 mm
- 2870728 C **Same**, length 28 mm
- 2870819 C **MEGA FIX® C**, bioresorbable composite interference screw, diameter 8 mm, length 19 mm, sterile, for single use
- 2870823 C **Same**, length 23 mm
- 2870828 C **Same**, length 28 mm
- 2870923 C **MEGA FIX® C**, bioresorbable composite interference screw, diameter 9 mm, length 23 mm, sterile, for single use
- 2870928 C **Same**, length 28 mm

MEGA FIX® CP



2870923 CP

- 2870823 CP **MEGA FIX® CP**, bioresorbable composite interference screw, perforated, diameter 8 mm, length 23 mm, sterile, for single use
- 2870828 CP **Same**, length 28 mm
- 2870923 CP **MEGA FIX® CP**, bioresorbable composite interference screw, perforated, diameter 9 mm, length 23 mm, sterile, for single use
- 2870928 CP **Same**, length 28 mm
- 2870935 CP **Same**, length 35 mm
- 2871028 CP **MEGA FIX® CP**, bioresorbable composite interference screw, perforated, diameter 10 mm, length 28 mm, sterile, for single use
- 2871035 CP **Same**, length 35 mm
- 2871135 CP **MEGA FIX® CP**, bioresorbable composite interference screw, perforated, diameter 11 mm, length 35 mm, sterile, for single use

MEGA FIX® – Titanium

MEGA FIX® T for Bone-Tendon-Bone Technique

- Sharp thread enables easy insertion
- Diameter 7 – 9 mm, lengths 20 and 25 mm

MEGA FIX® T for the Hamstring Technique

- Blunt thread protects the transplant
- Diameter 7 – 10 mm, lengths 23 and 28 mm



MEGA FIX® T
from titanium Ti-6AL-4V ELI

MEGA FIX® T for the Bone-Tendon-Bone Technique



2870720 T

- 2870720 T **MEGA FIX® T**, titanium interference screw, diameter 7 mm, length 20 mm, for Cruciate Ligament Reconstruction with Bone-Tendon-Bone Transplant, sterile, for single use
- 2870725 T **Same**, length 25 mm
- 2870820 T **MEGA FIX® T**, titanium interference screw, diameter 8 mm, length 20 mm, for Cruciate Ligament Reconstruction with Bone-Tendon-Bone Transplant, sterile, for single use
- 2870825 T **Same**, length 25 mm
- 2870920 T **MEGA FIX® T**, titanium interference screw, diameter 9 mm, length 20 mm, for Cruciate Ligament Reconstruction with Bone-Tendon-Bone Transplant, sterile, for single use
- 2870925 T **Same**, length 25 mm

MEGA FIX® T for the Hamstring Technique




2870723 T

- 2870723 T **MEGA FIX® T**, titanium interference screw, diameter 7 mm, length 23 mm, for Cruciate Ligament Reconstruction with Semitendinosus Transplant, sterile, for single use
- 2870728 T **Same**, length 28 mm
- 2870823 T **MEGA FIX® T**, titanium interference screw, diameter 8 mm, length 23 mm, for Cruciate Ligament Reconstruction with Semitendinosus Transplant, sterile, for single use
- 2870828 T **Same**, length 28 mm
- 2870923 T **MEGA FIX® T**, titanium interference screw, diameter 9 mm, length 23 mm, for Cruciate Ligament Reconstruction with Semitendinosus Transplant, sterile, for single use
- 2870928 T **Same**, length 28 mm
- 2871023 T **MEGA FIX® T**, titanium interference screw, diameter 10 mm, length 23 mm, for Cruciate Ligament Reconstruction with Semitendinosus Transplant, sterile, for single use




Screwdriver for Interference Screws

CROSSDRIVE®

- **Special cross drive**
- **Optimum torsion stability due to the fine-tuned regulation of force transmission between the screwdriver and the interference screw**



28789 SK

28789 SK	CROSSDRIVE® Screwdriver , cannulated, size 8 – 11, for use with bioresorbable MEGA FIX® screws diameter 8 – 11 mm and Nitinol Guide Wires 28789 GW/KW	
28770 SK	CROSSDRIVE® Screwdriver , cannulated, size 7, for use with bioresorbable MEGA FIX® screws diameter 7 mm and Nitinol Guide Wires 28789 GW/KW	
28760 SK	CROSSDRIVE® Screwdriver , cannulated, size 6, for use with bioresorbable MEGA FIX® screws diameter 6 mm and Nitinol Guide Wires 28789 GW/KW	
28789 CD	CROSSDRIVE® Plus Screwdriver , cannulated, for use with MEGA FIX® titanium interference screws and Nitinol Guide Wire 28789 FW	
28789 GW-6	Nitinol Guide Wire , diameter 1.1 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Screwdrivers 28789 SK, 28770 SK and 28760 SK	
28789 KW-6	Nitinol Guide Wire , diameter 1.1 mm, length 25.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Screwdrivers 28789 SK, 28770 SK and 28760 SK	
28789 FW-6	Nitinol Guide Wire , diameter 2 mm, length 38.5 cm, unsterile, for single use, package of 6, for use with CROSSDRIVE® Plus Screwdriver 28789 CD	


Components/Spare Parts see chapter 18

MEGASHIM Implants

- For hybrid fixation
- Optimized implant volume
- Prevention of graft lesions
- Anatomical femoral insertion
- Simplified application
- Enhanced implant stability
- Complete degradation
- Osseous replacement



MEGASHIM Implants
from the bioresorbable material Poly(L-lactide-co-D,L-lactide)



STERILE 



2870620 MSP

- 2870620 MSP **MEGASHIM**, bioresorbable oval wedge, perforated, 6x20 mm, sterile, for single use
- 2870720 MSP **MEGASHIM**, bioresorbable oval wedge, perforated, 7x20 mm, sterile, for single use
- 2870820 MSP **MEGASHIM**, bioresorbable oval wedge, perforated, 8x20 mm, sterile, for single use
- 2870920 MSP **MEGASHIM**, bioresorbable oval wedge, perforated, 9x20 mm, sterile, for single use


Order No.	Size (width x length)	Height	Instrumentation
2870620 MSP	6x20 mm	4 mm	Dilator 28728 DS Applicator 28767 E Pusher 28767 C HALF PIPE® 28728 SH
2870720 MSP	7x20 mm	4.5 mm	
2870820 MSP	8x20 mm	5 mm	Dilator 28728 DL Applicator 28789 EK Pusher 28789 C HALF PIPE® 28728 SH
2870920 MSP	9x20 mm	5.5 mm	



28728 DS

28728 DS **Dilator**, graduated, diameter 4 mm, working length 15 cm, for use with MEGASHIM 6x20 2870620 MSP and MEGASHIM 7x20 2870720 MSP

28728 DL **Dilator**, graduated, diameter 5 mm, working length 15 cm, for use with MEGASHIM 8x20 2870820 MSP and MEGASHIM 9x20 2870920 MSP



28767 E

28767 E **Applicator**, distal marking at 2 and 4 mm, with strike plate, working length 15 cm, for use with MEGASHIM 6x20 2870620 MSP and MEGASHIM 7x20 2870720 MSP


28789 EK **Applicator**, cannulated, distal marking at 2 and 4 mm, with strike plate, working length 15 cm, for use with MEGASHIM 8x20 2870820 MSP and MEGASHIM 9x20 2870920 MSP



28728 SH

28728 SH **HALF PIPE**®, without handle, short, working length 85 mm


28728 LH **HALF PIPE**®, without handle, long, working length 95 mm



28767 C

28767 C **Pusher**, distal marking at 2 and 4 mm, working length 15 cm, for use with MEGASHIM 6x20 2870620 MSP and MEGASHIM 7x20 2870720 MSP

28789 C **Pusher**, distal marking at 2 and 4 mm, working length 15 cm, for use with MEGASHIM 8x20 2870820 MSP and MEGASHIM 9x20 2870920 MSP





INSTRUMENTS FOR THE SHOULDER

PORTAL SYSTEMS
SHOULDER ARTHROSCOPY129-135

INSTRUMENTS FOR
SHOULDER ARTHROSCOPY136-145

BICEPS TENDONESIS146-147

AC JOINT RECONSTRUCTION
MINAR®148-149

IMPLANTS150-152

Shoulder

Portal Systems for Shoulder Arthroscopy

Special Features:

- Dilator with handle and thread attachment for optimal rotation
- Cannulated dilator with thread for use via a guide wire
- Various thread depths of the cannulas ensure very good tissue compression
- Good stability due to special thread wings



28180 GO

28180 GO **Dilator, with handle and thread attachment**, cannulated, outer diameter 8 mm, inner diameter 1.6 mm, for use with Cannula 28180 GT and Nitinol Guide Wire 28140 GW



28180 GT-6

28180 GT-6 **Cannula**, with thread, unsterile, for single use, package of 6, for Gasket 28180 GD, inner diameter 8.25 mm, working length 7 cm, for use with Dilator 28180 GO



28180 GDS

28180 GDS **Seal Set**, unsterile, for single use, with sealing cap, package of 5, for use with Cannula 28180 GT



SPS – Secure Portal System

The SPS – Secure Portal System facilitates the positioning of the portals during shoulder arthroscopy and offers better support for the introduced trocar sheaths by protecting the surrounding soft tissue. The atraumatic and targeted insertion of the puncture needle makes it possible to introduce both the subsequent dilation system as well as the trocar sheath system into the shoulder joint without any problems. It is possible to probe the target structures in this joint in

advance with the puncture needle, whereby it is also possible to confirm the correct position of the trocar sheath to be inserted. If the puncture needle is unable to reach the desired areas, it can be easily repositioned without trauma to the soft tissue.

The individual steps during the insertion of the trocar sheath system are arthroscopically controlled, which prevents damage when the joint is entered.

The SPS – Secure Portal System is recommended for shoulder portals.

This system allows for an optimal control of the direction and position of the portals.



Fig. 1




Fig. 2

- The puncture needle with a diameter of 1.4 mm is introduced transcutaneously into the joint. The position must be corrected until the puncture needle penetrates the capsule at the desired point in the correct direction.
- The obturator is removed from the puncture needle.

- A guide wire with a diameter of 0.9 mm is introduced through the puncture needle into the joint.
- The puncture needle is removed from the joint while the guide wire is left in position.
- Skin incision along the guide wire corresponding to cannula size

Shoulder

Portal Systems for Shoulder Arthroscopy




Fig. 3




Fig. 4



Fig. 5

The SPS – Secure Portal System provides a portal to the joint by merely dilating the soft tissue without injuring the soft tissue. Positioning is performed under

- A cannulated dilator is pushed along the guide wire into the joint with the help of a handle.

- The guide wire is removed.

- The trocar sheath that was inserted into the handle for easy handling is advanced along the dilator.


- The soft tissue is hereby dilated until the trocar sheath “snaps” safely in place behind the capsule.

- Then the handle can be pulled off the trocar sheath. The trocar sheath then is ready for use and remains safely in the joint.


arthroscopic vision in order to provide optimal positioning of the lastly inserted cannula.

Shoulder

Portal Systems for Shoulder Arthroscopy



- 28179 DB **Puncture Needle**, outer diameter 1.4 mm, inner diameter 1 mm, working length 12 cm, for single use, for use with Guide Wire 28179 DW and Obturator 28179 DO
- 28179 DO **Obturator**



- 28179 DW **Guide Wire**, diameter 0.9 mm, length 30 cm, for single use, package of 6



- 28179 DL **Dilator**, cannulated, outer diameter 3.8 mm, inner diameter 1.2 mm, length 30 cm



- 28179 DF **Handle**, for use with Dilator 28179 DL


Shoulder

Portal Systems for Shoulder Arthroscopy


A workable instrument set requires the following supplementary sets:




For inner diameter 6.1 mm, working length 7 cm

- 28179 EB **Dilator**, with integrated handle, short, diameter 6 mm, for use with threaded Cannula 28179 SA and Obturator 28179 EO, color code: dark blue
- 28179 EO **Obturator**, diameter 4 mm, color code: dark blue
- 28179 SA-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 


For inner diameter 6.1 mm, working length 8.5 cm

- 28179 EC **Dilator**, with integrated handle, long, diameter 6 mm, for use with threaded Cannula 28179 SB and Obturator 28179 EP, color code: light blue
- 28179 EP **Obturator**, diameter 4 mm, color code: light blue
- 28179 SB-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 


For inner diameter 8.25 mm, working length 7 cm

- 28179 FB **Dilator**, with integrated handle, short, diameter 8.1 mm, for use with threaded Cannula 28179 SC and Obturator 28179 FO, color code: dark red
- 28179 FO **Obturator**, diameter 4 mm, color code: dark red
- 28179 SC-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 


For inner diameter 8.25 mm, working length 8.5 cm

- 28179 FC **Dilator**, with integrated handle, long, diameter 8.1 mm, for use with threaded Cannula 28179 SD and Obturator 28179 FP, color code: light red
- 28179 FP **Obturator**, diameter 4 mm, color code: light red
- 28179 SD-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 

Also required for each combination:



28179 GS

- 28179 GS **Seal Set**, sterile, for single use, package of 10, for use with Valve Housing 28179 DG/OG 



28179 DG 28179 OG

- 28179 DG **Valve Housing**, with LUER-Lock, for use with Cannulas and Set of Gaskets 28179 GS
- or
- 28179 OG **Valve Housing**, without LUER-Lock, for use with Cannulas and Set of Gaskets 28179 GS


Shoulder

Portal Systems for Shoulder Arthroscopy


HALF PIPE®

Benefits:


- Insertion through the soft tissue into the joint is not limited by the diameter of the cannula
- High flexibility of the operating instruments as the HALF PIPE® is removed again after the instrument changeover
- Safe exchange of instruments in joints in which no cannulas can be used (such as elbow, wrist, etc.)




Insertion of the HALF PIPE® along an instrument



Removal of the instrument



Maintenance of the portal




Insertion of a given instrument along the HALF PIPE®

Shoulder

Portal Systems for Shoulder Arthroscopy

HALF PIPE®



28179 OB



28179 GH



28179 GK

28179 GH **HALF PIPE®**, long, working length 95 mm,
for use with Obturator 28179 OB

28179 GK **HALF PIPE®**, short, working length 80 mm,
for use with Obturator 28179 OB

28179 OB **Obturator**, for use with
HALF PIPE® 28179 GH/GK

Shoulder

Instruments for Shoulder Arthroscopy

SHOULDER PRO® Suture System



28179 HG

28179 HG **Handle**, for use with monofilament threads size USP 2-0 to 2, for use with Suture Attachments 28179 PA – PH, 28728 NA – NG, Wheel Attachment 28179 HR and Wheel 28179 R



28179 HR/R

28179 HR **Wheel Attachment**, for use with monofilament threads size USP 2-0 to 2, for use with Handle 28179 HG and Wheel 28179 R

28179 R **Wheel**, for use with monofilament threads size USP 2-0 to 2, for use with Wheel Attachment 28179 HR



28180 BG



28180 BG **Suture Catcher**, with inserter, sterile, for single use, package of 10, for use with Suture Attachments 28179 PA – PH and Handle 28179 HG



Shoulder

Instruments for Shoulder Arthroscopy

SHOULDER PRO® Suture System



28179 PA



28179 PA

SHOULDER PRO® Suture Attachment, distal tip curved upwards, straight, 5 mm in height, working length 15 cm, for use with Handle 28179 HG



28179 PB

Same, 7 mm in height



28179 PC

Same, 8 mm in height



28179 PD

Same, hook-shaped distal tip curved upwards, 8 mm in height



28179 PE



28179 PE

SHOULDER PRO® Suture Attachment, hook-shaped distal tip curved upwards, straight, 8.7 mm in height, working length 15 cm, for use with Handle 28179 HG

28179 PF

Same, 10 mm in height



28179 PG

SHOULDER PRO® Suture Attachment, distal tip angled 30° to right, straight, 8 mm in height, working length 15 cm, for use with Handle 28179 HG



28179 PH

Same, angled 30° to left



28179 R1

Cleaning Adaptor, for use with Suture Attachments 28179 PA – PH and 28728 NA – NG



28179 R2

Cleaning Adaptor, for use with Handle 28179 HG



Shoulder

Instruments for Shoulder Arthroscopy

WONDERHOOK® Suture System



28184 WH **WONDERHOOK® Handle, complete**, for transporting monofilament threads up to size USP 1 including:
Transport Cassette



28184 NG **WONDERHOOK® Suture Attachment**, for use with monofilament threads up to size USP 1, straight, length of distal end 3.5 cm, working length 15 cm, for use with Handle 28184 WH, color code: blue




28184 NGL **Same**, length of distal end 5 cm, long




28184 NA **WONDERHOOK® Suture Attachment**, for use with monofilament threads up to size USP 1, distal tip slightly curved upwards, working length 15 cm, for use with Handle 28184 WH, color code: gold




28184 MR **WONDERHOOK® Suture Attachment**, for use with monofilament threads up to size USP 1, distal tip curved 25° right, working length 15 cm, for use with Handle 28184 WH, color code: green



28184 ML **Same**, distal tip curved 25° left



28184 NR **WONDERHOOK® Suture Attachment**, for use with monofilament threads up to size USP 1, distally strongly curved to right, working length 15 cm, for use with Handle 28184 WH, color code: red



28184 NL **Same**, distally strongly curved to left



28184 RA

28184 RA **Cleaning Adaptor**, for use with WONDERHOOK® Suture Attachments 28184 ML/MR/NG/NGL/NA/NR/NL

Components/Spare Parts see chapter 18

Shoulder


Instruments for Shoulder Arthroscopy




SNAPPER® SHOULDER PRO® Suture Forceps

This forceps was specially designed for suture management in shoulder arthroscopy, in particular for the reconstruction of the rotator cuff. It provides the following features and benefits:

- Very slender jaw design
- Sharp distal tip
- Large eyelet and angle of view
- Additional bending at the distal end of the sheath
- Ergonomic handle design



Rotator cuff suture with SNAPPER® SHOULDER PRO®




Reconstructed rotator cuff

Shoulder

Instruments for Shoulder Arthroscopy



SNAPPER® SHOULDER PRO® Suture Forceps



28180 GCN



28180 GAN **SNAPPER® SHOULDER PRO® Suture Forceps**, for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, curved upwards, handle with cleaning connector, working length 15 cm, color code: black



28180 GCN **Same**, straight, color code: blue



28180 GLN **Same**, curved to left, also curved to left in sheath, color code: red



28180 GRN **Same**, curved to right, also curved to right in sheath, color code: green




28180 GRGN **Same**, retrograde opening, also curved upwards in sheath, color code: white

Container for Sterilization and Storage of Instruments see HYGIENE catalog
Components/Spare Parts see chapter 18

Shoulder


Instruments for Shoulder Arthroscopy

SHOULDER PRO® Suture Forceps Attachments



33136 P

33136 P **CLICKline® Handle**, with thumb release, with 4 locking positions, for use with Suture Forceps Attachments 28180 LA/LC/LL/LR/LRG



28180 LA



28180 LA **SHOULDER PRO® Suture Forceps Attachment**, for punching soft tissue and suture management in shoulder arthroscopy, sheath diameter 3.5 mm, curved upwards, working length 15 cm, for use with Handle 33136 P, color code: black



28180 LC **Same**, straight, color code: blue




28180 LL **Same**, curved to left, also curved to left in sheath, color code: red



28180 LR **Same**, curved to right, also curved to right in sheath, color code: green



28180 LRG **Same**, retrograde opening, also curved upwards in sheath, color code: white



28179 HA

28179 HA **Suture Hook**, with eyelet, curved to left



28179 HB **Suture Hook**, with eyelet, curved to right



28179 HC **Suture Hook**, with eyelet, straight




28179 HD

28179 HD **Threading Device**, for use with Suture Hooks 28179 HA – HC

Components/Spare Parts see chapter 18

Shoulder

Instruments for Shoulder Arthroscopy



2870356 SC




2870356 SC **Suture Cutter**, for cutting sutures up to size USP 2, working length 15 cm



28179 I



28179 I **Thread Catcher**, working length 15 cm



28179 KP



28179 KP **Knot Pusher**, for sutures up to size USP 2, working length 18 cm



2870356 KP




2870356 KP **Knot Pusher and Suture Cutter**, for cutting sutures up to size USP 2, working length 15 cm
including:
Insert and Blade
Handle

Components/Spare Parts see chapter 18

Shoulder

Instruments for Shoulder Arthroscopy



28171 KPN



28171 KPN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 19 cm



28171 KUN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, 15° curved upwards, handle with cleaning connector, working length 19 cm



28171 KGN **SILGRASP® Foreign Body Grasper**, aggressive, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 19 cm

28171 KGSN **Same**, with ratchet



28573 FD **SILGRASP® Foreign Body Grasper**, aggressive, sheath diameter 4 mm, straight, handle with cleaning connector and ratchet, working length 22 cm

NEW



28171 SGN **SILGRASP® Suture Grasper**, straight jaws, sheath diameter 3 mm, straight, handle with cleaning connector, working length 14 cm



28171 SGL **SILGRASP® Suture Grasper**, curved jaws, 45° left, sheath diameter 3.5 mm, 5° curved to left, handle with cleaning connector, working length 16 cm

NEW

28171 SGR **Same**, 45° right, 5° curved to right

NEW



28171 SHN **SILGRASP® Suture Grasper**, straight jaws, sheath diameter 3.5 mm, handle with cleaning connector, working length 14 cm


NEW

7-16

Components/Spare Parts see chapter 18

Shoulder

Instruments for Shoulder Arthroscopy



28180 GFN
NEW

TARPUN SHOULDER PRO® Suture Forceps, for punching soft tissue and suture management in shoulder arthroscopy, curved, 47° upwards, sheath diameter 3.5 mm, handle with cleaning connector, working length 14 cm



28180 HC
NEW

FETCHER SHOULDER PRO® Suture Forceps, for punching soft tissue and suture management in shoulder arthroscopy, straight jaws, sheath diameter 3.5 mm, handle with cleaning connector, working length 14 cm



28180 HL
NEW

FETCHER SHOULDER PRO® Suture Forceps, for punching soft tissue and suture management in shoulder arthroscopy, curved jaws, 43° left, sheath diameter 3.5 mm, handle with cleaning connector, working length 14 cm


28180 HR
NEW

Same, curved jaws, 43° right

Components/Spare Parts see chapter 18

Shoulder

Instruments for Shoulder Arthroscopy



28180 CB



28180 CB **Elevator**, width 4 mm, curved 15° downwards, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm



28180 CC **Same**, curved 30° downwards



28180 CF **Elevator**, width 4 mm, curved 15° downwards, blade turned 180°, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm



28180 CJ **Same**, curved 30° downwards



28180 DC **Glenoid Rasp**, width 4.5 mm, curved 30° upwards, also curved upwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm



28180 CE **S.L.A.P Rasp**, width 4.5 mm, curved 30° downwards, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm



28180 CL **Rasp**, for use as Glenoid or S.L.A.P rasps, **double-sided**, width 4.5 mm, curved 30° downwards, also curved downwards in sheath, working length 15 cm, for use with cannulas inner diameter 8.25 mm



28179 BB



28179 BB **Elevator**, width 4 mm, 15° curved upwards, working length 15 cm



28179 BC **Elevator**, width 4 mm, 30° curved upwards, working length 15 cm



28179 CB **Glenoid Rasp**, width 5.5 mm, 30° curved upwards, working length 15 cm



BITER®

Special Features:

- Unique instrument for simple and precise tenotomy of the biceps tendon and/or biceps tenodesis
- Combined cutting and grasping instrument
- Anatomic design for optimal use



Fig. 1: Exposure of the biceps tendon




Fig. 2: Introducing the BITER® instrument and grasping the biceps tendon



Figs. 3 and 4: Cutting the biceps tendon and subsequent removal with the tendon grasped in the BITER®

BITER®



28184 MSR



28184 MSL **BITER®**, for the arthroscopic, terminal cutting of the biceps tendon, for the left shoulder, working length 15 cm

28184 MSR **Same**, for the right shoulder


Shoulder

AC Joint Reconstruction

MINAR®

Special Features:

- Complete technique using a 3-cm skin incision
- Minimally invasive
- Easy application
- No need to remove implants
- Use of aimer protects neurovascular structures
- Compact instrument set



AC joint reconstruction with MINAR®



28729 FT

28729 FT * **FLIPPTACK**, extracortical fixation button, 4 x 12 mm, sterile, for single use



28729 FC **Catgut Polyester-S white**, 3 x 75 cm, USP 7, sterile, for single use, package of 24, for use with FLIPPTACK, extracortical fixation button




* Each intervention requires two FLIPPTACK fixation buttons.

Shoulder

AC Joint Reconstruction

MINAR®




28379 SA

28379 SA **Target Guide**, for AC joint reconstruction


28379 SB

28379 SB **Bullet**, working length 9.5 cm, for use with Aimer 28379 SA




28379 SC

28379 SC **FLIPTACK Inserter**, working length 19.5 cm




28379 SD

28379 SD **FLIPTACK Inserter Rod**, working length 24.5 cm, for use with FLIPTACK Inserter 28379 SC



28379 SE

28379 SE **Suture Awl**, working length 15 cm



28379 SF

28379 SF **Repositioner**, for AC joint reconstruction, working length 20 cm

A workable instrument set requires the following instruments:



28729 E

28729 E **Larding Wire**, pyramidal tip, diameter 2.4 mm, length 32 cm, unsterile, for single use, package of 10, for use with Undercut Drills 28729 BA – BH, Collar Burs BLC – BLF and Drills 28729 GA – GE



28729 BA

28729 BA **Undercut Drill**, cannulated, diameter 4.5 mm, for use with Drilling Wire 28729 D and Larding Wire 28729 E

7-16


Shoulder

Implants for Shoulder Arthroscopy


Suture Anchors – Titanium

Special Features:

- Implants are made of titanium Ti-6AL-4V
- Anchor is available in three different sizes
- Pre-loaded inserter for single use
- Anchors are pre-assembled with MEGAFIBRE® threads USP 2-0
- Special MEGAFIBRE® threads are made of braided, non-resorbable, ultra-high molecular polyethylene
- Extremely smooth surface and flat design ensures enhanced knot strength and distinguishes MEGAFIBRE® threads from other threads such as polyester and polyblend
- Laser markings at the distal end aid orientation during anchor placement



STERILE 




2870309 ST



2870309 ST

Titanium Suture Anchor, diameter 3 mm, length 9 mm, with two MEGAFIBRE® threads USP 2, pre-assembled, self-tapping, with inserter, sterile, for single use




2870514 TI



2870514 TI

Titanium Suture Anchor, diameter 5 mm, length 12.5 mm, with two MEGAFIBRE® threads USP 2, pre-assembled, self-tapping, with inserter, sterile, for single use



2870614 TI



2870614 TI

Titanium Suture Anchor, diameter 6.5 mm, length 12.5 mm, with two MEGAFIBRE® threads USP 2, pre-assembled, self-tapping, with inserter, sterile, for single use



28179 KS

Bone Punch, for use with Titanium Suture Anchors 2870514 TI, 2870614 TI and 2870309 ST

Shoulder

Implants for Shoulder Arthroscopy

BIOPLUG – Bioresorbable

Special Features:

- The implants consist of a bioresorbable material Poly(L-lactide-co-D,L-lactide)
- Suture Anchor 2870310 BP is pre-loaded with MEGAFIBRE® threads USP 2
- The use of suture material size USP 2 is recommended for Suture Anchors 2870411 BP and 2870514 BP
- Very good degradation behavior



STERILE 

2870310 BP **BIOPLUG, bioresorbable suture anchor**, diameter 3.5 mm, length 10 mm, with one MEGAFIBRE® USP 2 suture preloaded, sterile, for single use, for use with Inserter 28179 TK

2870411 BP **BIOPLUG, bioresorbable suture anchor**, diameter 4.2 mm, length 11 mm, sterile, for single use, for use with Inserter 28179 TI or 28179 KI

2870514 BP **BIOPLUG, bioresorbable suture anchor**, diameter 5.2 mm, length 14 mm, sterile, for single use, for use with Inserter 28179 TI



28179 GG



28179 GG

Glenoid Guide, working length 12.5 cm, for use with BIOPLUG 2870411 BP, 2870310 BP and Drills 28179 TB/TD

Shoulder

Implants for Shoulder Arthroscopy



28179 TB



28179 TD

Drill, for preparation of the tunnel for BIOPLUG 2870310 BP, with laser marking for the depth of the drill hole, length 15 cm




28179 TB

Drill, for preparation of the tunnel for BIOPLUG 2870411 BP, with laser marking for the depth of the drill hole, length 15 cm



28179 TC

Drill, for preparation of the tunnel for BIOPLUG 2870514 BP, with laser marking for the depth of the drill hole, length 18 cm



28179 TI




28179 TK

Inserter, with lateral thread guide and thread clip at the handle, working length 18 cm, for use with BIOPLUG 2870310 BP

28179 TI

Inserter, with lateral thread guide and thread clip at the handle, working length 18 cm, for use with BIOPLUG 2870411 BP and 2870514 BP



28270 H

28270 H

Mallet, ergonomic handle, two plane faces, length 17 cm, color code: blue

Components/Spare Parts see chapter 18



INSTRUMENTS FOR THE HIP

PORTAL SYSTEMS FOR
HIP ARTHROSCOPY154-158

INSTRUMENTS FOR
HIP ARTHROSCOPY159-160

ACCESSORIES FOR
HIP ARTHROSCOPY161

Hip

Portal Systems for Hip Arthroscopy

The HPS – Hip Portal System provides the ideal synthesis between a cannulated access/arthroscopy system and various hip instruments. It offers the


surgeon a complete instrument set for safe portal placement as well as diagnostic and therapeutic hip arthroscopy.


Benefits:

- Precise portal placement with cannulated system and target guide
- Versatile portal management:
 - a. Stable ports and safe fluid management
 - b. HALF PIPE® – enhanced maneuverability and faster changeover of instruments
 - c. Portal-free instrumentation – maximum instrument flexibility
- Arthroscope sheath and instruments with longer working length
- Easier instrument changeover

Special Features:

- High-flow sheaths, specially designed for the hip, with an outer diameter 5.5 or 6 mm and a working length of 13.5 cm
- Fast, stable and reliable telescope and sheath connection
- Fully cannulated construction system
- HALF PIPE®, specially designed for the hip, for fast instrument changeover and greater flexibility of operating instruments





28140 ZBA/
28140 ZCA

28140 ZAA

- 28140 ZAA **Aimer**, for use with Guide Sleeves 28140 ZBA/ZCA
- 28140 ZBA **Guide Sleeve**, short, working length 10.5 cm, for use with Aimer 28140 ZAA
- 28140 ZCA **Guide Sleeve**, long, working length 14.5 cm, for use with Aimer 28140 ZAA

Optional:

Attachment for triangulation




28140 ZDA

- 28140 ZDA **Aimer Attachment**, for use with Aimer 28140 ZAA

Hip

Portal Systems for Hip Arthroscopy




28140 DB **Puncture Needle**, outer diameter 2.1 mm, inner diameter 1.6 mm, working length 21.3 cm, for single use, for use with Nitinol Guide Wire 28140 GW and Obturator 28140 DO



28140 DO **Obturator**



28140 GW-6 **Nitinol Guide Wire**, diameter 1.5 mm, length 40 cm, unsterile, for single use, package of 6



28140 W **Changing Rod**, diameter 4.8 mm, length 31 cm, for use with Arthroscope Sheaths 28130 CR/R and 28131 CR/R




28140 WK **Changing Rod**, cannulated, diameter 4.8 mm, length 31 cm, for use with Arthroscope Sheaths 28130 CR/R and 28131 CR/R as well as Nitinol Guide Wire 28140 GW



28140 EWK **Changing Rod ENDOCAMELEON®**, cannulated, diameter 3.8 mm, length 31 cm, for use with Arthroscope Sheath ENDOCAMELEON® 28136 EC and Nitinol Guide Wire 28140 GW

NEW




28140 S **Evacuation Cannula**, with LUER-Lock and one stopcock, working length 18 cm, for use with Arthroscope Sheaths 28130 CR/R and 28131 CR/R

Components/Spare Parts see chapter 18


A workable instrument set requires the following supplementary sets:




For inner diameter 6.1 mm, working length 9 cm

- 28140 EB **Dilator**, with integrated handle, short, diameter 6 mm, for use with Threaded Cannula 28140 SA and Obturator 28140 EO, color code: dark blue
- 28140 EO **Obturator**, cannulated, inner diameter 1.6 mm, for use with Guide Wire 28140 GW, color code: dark blue
- 28140 SA-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 


For inner diameter 6.1 mm, working length 12 cm

- 28140 EC **Dilator**, with integrated handle, long, diameter 6 mm, for use with Threaded Cannula 28140 SB and Obturator 28140 EP, color code: light blue
- 28140 EP **Obturator**, cannulated, inner diameter 1.6 mm, for use with Guide Wire 28140 GW, color code: light blue
- 28140 SB-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 


For inner diameter 8.25 mm, working length 9 cm

- 28140 FB **Dilator**, with integrated handle, short, diameter 8.1 mm, for use with Threaded Cannula 28140 SC and Obturator 28140 FO, color code: dark red
- 28140 FO **Obturator**, cannulated, inner diameter 1.6 mm, for use with Guide Wire 28140 GW, color code: dark red
- 28140 SC-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 

For inner diameter 8.25 mm, working length 12 cm

- 28140 FC **Dilator**, with integrated handle, long, diameter 8.1 mm, for use with Threaded Cannula 28140 SD and Obturator 28140 FP, color code: light red
- 28140 FP **Obturator**, cannulated, inner diameter 1.6 mm, for use with Guide Wire 28140 GW, color code: light red
- 28140 SD-6 **Cannula**, with thread, transparent, unsterile, for single use, package of 6 

Also required for each combination:



28179 GS



28179 DG 28179 OG

28179 GS **Seal Set**, sterile, for single use, package of 10, for use with Valve Housing 28179 DG/OG



and

28179 DG **Valve Housing**, with LUER-Lock, for use with Cannulas and Set of Gaskets 28179 GS

or

28179 OG **Valve Housing**, without LUER-Lock, for use with Cannulas and Set of Gaskets 28179 GS

Hip

Portal Systems for Hip Arthroscopy

HALF PIPE®



28140 HD

28140 HC


28140 HD **HALF PIPE®**, for use in hip arthroscopy, handle rotated 90°, handle axis 120°, working length 95 mm

28140 HC **HALF PIPE®**, for use in hip arthroscopy, handle rotated 90°, handle axis 120°, distal end flat, atraumatic tip, working length 120 mm

HALF PIPE® for Shoulder Arthroscopy see page 135 and for **Knee Arthroscopy** see pages 88 and 125

Hip

Instruments for Hip Arthroscopy



28140 MG



28140 MG

Knife, pointed, curved, double-edged, working length 18 cm




28140 LM
NEW

Knife, round, straight, working length 11.5 cm



28140 BM
NEW

Knife, round, angled 20°, working length 11.5 cm



28140 T



28140 T

Probe, graduated, length of hook 3 mm, diameter 1.5 mm, working length 18 cm

28140 TL

Same, working length 21.5 cm



28140 TA

Probe, graduated, length of hook 3 mm, angled downwards 10°, diameter 1.5 mm, working length 20 cm



28140 TB

Probe, graduated, length of hook 3 mm, angled downwards 20°, diameter 1.5 mm, working length 20 cm



28140 CD



28140 CD

Microfracture Chisel, curved 30°, working length 18 cm



28140 CE

Microfracture Chisel, curved 70°, working length 18 cm




28140 CF



28140 CF
NEW

Microfracture Chisel, curved 90°, working length 16 cm



28140 KE




28140 KE

Curette, oval, small, both sides cutting, curved, 20° upwards, working length 18 cm

Curettes see page 47

Hip

Instruments for Hip Arthroscopy



28171 KPN



28171 KPN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 3.4 mm, jaws curved, 15° upwards, sheath diameter 3 mm, straight, handle with cleaning connector, working length 19 cm



28171 KUN **SILCUT® Punch**, through-cutting, cross-toothed, cutting width 3.4 mm, straight jaws, sheath diameter 3 mm, 15° curved upwards, handle with cleaning connector, working length 19 cm



28140 GA **Suture Forceps**, for punching soft tissue and suture management in hip arthroscopy, curved upwards, working length 19 cm

NEW



28171 KGN **SILGRASP® Foreign Body Grasper**, aggressive, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 19 cm

28171 KGSN **Same**, with ratchet



28171 SGD **SILGRASP® Suture Grasper**, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 19 cm

NEW



28573 FD **SILGRASP® Foreign Body Grasper**, aggressive, sheath diameter 4 mm, straight, handle with cleaning connector and ratchet, working length 22 cm

NEW

Components/Spare Parts see chapter 18

Hip

Accessories for Hip Arthroscopy



28140 D

28140 D **Gasket Attachment**, with cone, including Gasket 28140 GU, for use with all Arthroscope Sheaths



28140 GU

28140 GU **Gasket**, unsterile, for single use, package of 10, single-packaged, for use with Gasket Attachment 28140 D



533 TVA

533 TVA **Adaptor, autoclavable**, permits telescope changing under sterile conditions





INSTRUMENTS FOR SMALL AND MEDIUM JOINTS

HOPKINS® TELESCOPES
AND SHEATHS165-167

INSTRUMENTS FOR
SMALL AND MEDIUM JOINTS168-173


ENDOSCOPIC TREATMENT OF THE
CARPAL TUNNEL SYNDROME174-175

ENDOSCOPIC TREATMENT OF THE
CUBITAL TUNNEL SYNDROME176-179


Small and Medium Joints

HOPKINS® Telescopes and Sheaths

Diameter 1.9 mm, length 6.5 cm



28305 BA



28305 BA

HOPKINS® Forward-Oblique Telescope 30°, diameter 1.9 mm, length 6.5 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameter 2.5 mm, working length 4 cm



28306 BN



28306 BN

High-Flow Arthroscope Sheath, with standard coupling mechanism, diameter 2.5 mm, working length 4 cm, one stopcock, **fixed**, for use with HOPKINS® Telescope 30° 28305 BA and Obturators 28306 BS/BT, *color code: red



28306 BS



28306 BS

Obturator, sharp, for use with Arthroscope Sheath 28306 BN



28306 BT

Same, blunt


9-131

***Note:** For an overview of color codes for HOPKINS® Telescopes see page 30
Container for Sterilization and Storage of Telescopes see HYGIENE catalog
Components/Spare Parts see chapter 18


Small Joints

HOPKINS® Telescopes and Sheaths

Diameter 2.4 mm, length 10 cm




28300 BA



28300 BA

HOPKINS® Wide Angle Forward-Oblique Telescope 30°, diameter 2.4 mm, length 10 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameters 3.5 and 3.2 mm, working lengths 6.5 and 8.5 cm




28303 DS



28303 DS

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 3.5 mm, working length 6.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® Telescope 30° 28300 BA and Obturators 28302 BU/BV




28303 BS



28303 BS

High-Flow Arthroscope Sheath, with snap-in coupling mechanism, diameter 3.2 mm, working length 8.5 cm, one stopcock, **fixed**, for use with HOPKINS® Telescope 30° 28300 BA and Obturators 28302 BU/BV



28302 BU



28302 BU

Obturator, sharp, for use with Arthroscope Sheaths 28303 DS/BS



28302 BV


Same, blunt

***Note: For an overview of color codes for HOPKINS® Telescopes see page 30**
Container for Sterilization and Storage of Telescopes see catalog HYGIENE
Components/Spare Parts see chapter 18

Small and Medium Joints

HOPKINS® Telescopes and Sheaths


Diameter 2.7 mm, length 11 cm



28208 BA


HOPKINS® Forward-Oblique Telescope 30°, diameter 2.7 mm, length 11 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red

Diameter 4 mm, working length 7.5 cm



28133 DS

Arthroscope Sheath, with snap-in coupling mechanism, diameter 4 mm, working length 7.5 cm, two stopcocks, **rotatable**, for use with HOPKINS® Telescope 30° and Obturator 28133 BC



28133 BC

28133 BC

Obturator, blunt, for use with Arthroscope Sheath 28133 DS

Container for Sterilization and Storage of Telescopes see HYGIENE catalog
Components/Spare Parts see chapter 18

Small and Medium Joints


Instruments



791618




792005




791803



200400



221150



517000



516015



535312



535112

791618 **Ligature Scissors**, with tungsten carbide blades, curved, lower blade serrated, length 18 cm, color code: one black handle ring, one gold-plated handle ring

792005 **MAYO Scissors**, curved, length 17 cm

791803 **JAMESON Scissors**, curved, pointed, delicate tips, length 15.5 cm

200400 **BEYER Rongeur**, slender, curved, length 17 cm

221150 **HARTMANN Forceps**, extra delicate, serrated, 1 x 4.5 mm, working length 12.5 cm

517000 **MASING Needle Holder**, smooth jaws, working length 8 cm



516015 **Needle Holder**, tungsten carbide inserts, length 15 cm

535312 **HALSTEAD "Mosquito" Artery Forceps**, micro-model, curved, length 12.5 cm

535112 **HALSTEAD "Mosquito" Artery Forceps**, micro-model, straight, length 12.5 cm

Small and Medium Joints

Instruments



- NEW** 215010 **Retractor**, 2 x 3 teeth, blunt, length 10 cm
- NEW** 505400 **Retractor**, double-ended, size 6 x 20 mm and 5 x 10 mm, length 14.5 cm
- 499003 **Hook**, one prong, large curve, length 18 cm
- NEW** 499207 **JOSEPH Double Hook**, sharp, width 7 mm, length 15 cm
- NEW** 474006 **Double Elevator**, size 18 cm
- NEW** 533116 **ADSON Tissue Forceps**, 1 x 2 teeth, length 15 cm
- 533022 **ADSON Dressing Forceps**, serrated, tungsten carbide inserts, length 12 cm
- 208000 **Surgical Handle**, Fig. 3, length 12.5 cm, for Blades 208010 – 15, 208210 – 15
- NEW** 796513 **Towel Forceps**, with serrated inserts, length 13 cm, for paper cover sheets
- 810810 **Medicine Cup**, 100 cm³, diameter 80 mm, height 30 mm

Small and Medium Joints

Instruments



28302 S



28302 S


Probe, graduated, length of hook 1 mm, diameter 1 mm, working length 7.5 cm



28145 SN

28145 SN

Probe, graduated, length of hook 2 mm, diameter 1 mm, working length 4 cm



28145 S

28145 S

Probe, graduated, length of hook 2 mm, diameter 1.5 mm, working length 8.5 cm



28124 BZ

28124 BZ

Changing Rod, diameter 2.7, length 23 cm, for use with Arthroscope Sheath 28132 CR



28302 W

28302 W

Changing Rod, diameter 2 mm, length 15 cm, for use with Arthroscope Sheaths 28303 CR and 28303 DS

Small and Medium Joints

Instruments



28302 M



28302 M

Sickle Knife, bayonet-shaped, diameter 1.5 mm, working length 7.5 cm



28728 CG



28728 CG

Microfracture Chisel, angled 30°, working length 9 cm



28728 CH

Same, angled 70°



28572 AD

Square jaws

Cross-toothed, cutting width 2 mm, sheath diameter 2.5 mm, working length 8.5 cm



28572 AD

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 ADL
NEW

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 2 mm, jaws curved to left 45°, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 ADR
NEW

Same, jaws curved to right 45°

Cross-toothed, cutting width 1 mm, sheath diameter 25 mm, working length 8.5 cm



28572 AE

SILCUT® PRO Punch, through-cutting, cross-toothed, cutting width 1 mm, straight jaws, sheath diameter 2.5 mm, straight, handle with cleaning connector, working length 8.5 cm

Oval jaws

Cross-toothed, cutting width 4,1 mm, sheath diameter 3.5 mm, working length 12 cm



28571 O

SILCUT® PRO Oval Biter, through-cutting, cross-toothed, cutting width 4.1 mm, straight jaws, sheath diameter 3.5 mm, straight, handle with cleaning connector, working length 12 cm

Components/Spare Parts see chapter 18

Small and Medium Joints

Instruments

NEW



28572 NJ

Sheath diameter 2.8 mm, working length 8.5 cm



28572 NJ

SILGRASP® PRO Suture Grasper, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 CG

SILGRASP® PRO Cartilage Grasping Forceps, spoon-shaped jaws, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 CGU

SILGRASP® PRO Cartilage Grasping Forceps, spoon-shaped jaws, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 G

SILGRASP® PRO Grasping Forceps, spoon-shaped jaws, serrated, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 GU

SILGRASP® PRO Grasping Forceps, spoon-shaped jaws, serrated, jaws curved, 30° upwards, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm



28572 AG

SILGRASP® PRO Alligator Grasping Forceps, serrated, straight jaws, sheath diameter 2.8 mm, straight, handle with cleaning connector, working length 8.5 cm

Small and Medium Joints



Endoscopic Treatment of the Carpal Tunnel Syndrome

2-Portal Technique

Compared to open operating procedures, endoscopic cutting of the carpal ligament greatly reduces discomfort resulting from skin incision.

In this method, endoscope and instruments are introduced simultaneously from proximal and distal into the

carpal tunnel and the carpal ligament is then severed under optical control. The clear and detailed picture from the HOPKINS® telescope allows precise optical control of the operation.



28731 BVA

28731 BVA

HOPKINS® Wide Angle Forward-Oblique Telescope 30°, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light connector in line of sight, fiber optic light transmission incorporated, color code: red



28147 C




28147 CO

28147 C

GILBERT Operating Sheath, continuously slotted, diameter 5.5 mm, working length 9 cm, for use with Obturator 28147 CO and HOPKINS® Telescope 28731 BVA

28147 CO

Obturator, blunt, with attached segment, for use with Operating Sheath 28147 C



28147 CL

28147 CL

GILBERT Telescope Sheath, with attached segment, for linear shifting with Operating Sheath 28147 C, working length 16 cm, for use with HOPKINS® Telescope 28731 BVA

Container for Sterilization and Storage of Telescopes see HYGIENE catalog

Components/Spare Parts see chapter 18

Small and Medium Joints

Endoscopic Treatment of the Carpal Tunnel Syndrome



28147 SA – SD

28147 S

Dilator Set

including:

Dilator, diameter 4 mm

Dilator, diameter 5 mm

Dilator, diameter 6 mm

Dilator, diameter 7 mm



28147 E




28147 E

GILBERT Rasp, for preparation of the carpal ligament



28147 R



28147 RM



28147 R

Knife, retractable, backward cutting, with exchangeable Knife Attachment 28147 RM, diameter 3.5 mm, working length 9 cm



28147 RM

Knife Attachment, backward cutting, for use with Knife 28147 R

Small and Medium Joints

Endoscopic Treatment of the Cubital Tunnel Syndrome

Apart from the carpal tunnel syndrome, the cubital tunnel syndrome (sulcus ulnaris syndrome) is the second most frequent peripheral nerve compression syndrome.

Standard surgical techniques require a skin incision of between 8 – 12 cm and, in many cases, are projected on the nerve in an unphysiological manner.

The endoscopic technique, however, only requires a skin incision of 1.5 – 2 cm and a longer neurolysis path (15 – 20 cm). This allows the transection of all fibrous arcades between the heads of the flexor carpi ulnaris muscle and thus provides better nerve decompression compared to previous methods.

With the endoscopic technique, a subcutaneous pocket is formed using a dressing and sponge holding forceps as a tunnel forceps where first an illuminating speculum is inserted and then a 4 mm endoscope with a dissector at its tip. Dissection is then performed under visual control.

The benefits of endoscopic surgery over previous methods are as follows:

- **Lower morbidity (> 90 % of patients can move their elbow freely within 24 hours)**
- **Rapid pathological improvement (> 95 % of patients within 24 hours)**
- **More rapid recovery**

Our experience shows that this technique has been successful in over 100 interventions, is safe and easy to learn and provides an excellent alternative to conventional open procedures.

The instrument set has also proved particularly valuable in endoscopic and minimally invasive surgery for radiohumeral and medial humeral epicondylitis, radial compression of the forearm (Wartenberg's syndrome) and the pronator syndrome.

*R. HOFFMANN, M.D.,
Oldenburg, Germany*




Fig. 1: Endoscopic division of the forearm fascia






Fig. 2: "Long-distance" decompression (15 cm) towards the distal end

Small and Medium Joints

Endoscopic Treatment of the Cubital Tunnel Syndrome




28731 BWA




28731 BWA

HOPKINS® Wide Angle Forward-Oblique Telescope 30°, enlarged view, diameter 4 mm, length 18 cm, **autoclavable**, fiber optic light transmission incorporated, color code: red




50200 ES



50200 ES

Optical Dissector, with distal spatula, fenestrated, sharp, working length 14.5 cm, for use with HOPKINS® telescopes 30°



50300 ES



50300 ES


NEW

Optical Dissector, with distal spatula, working length 14.5 cm, for use with HOPKINS® telescopes 30°

Container for Sterilization and Storage of Telescopes see HYGIENE catalog
Components/Spare Parts see chapter 18

Small and Medium Joints


Endoscopic Treatment of the Cubital Tunnel Syndrome



- | | |
|----------|---|
| 404055 H | COTTLE Speculum , with fiber optic light carrier, without set screw, special matt finish, blade length 55 mm, length 13 cm |
| 404090 S | Speculum , with fiber optic light carrier, with set screw, blade length 90 mm, length 13.5 cm |
| 404092 S | Same , blade length 110 mm |
| 748220 | DUPLAY Dressing and Sponge Holding Forceps , curved, with ratchet, length 21 cm |
| 748221 | Same , straight |
| 752918 | METZENBAUM Scissors , curved, length 18 cm |
| 752923 | Same , length 23 cm |
| 752928 | Same , length 28 cm |

Small and Medium Joints

Endoscopic Treatment of the Cubital Tunnel Syndrome



38851 MD

ROBI® KELLY Grasping Forceps, CLERMONT-FERRAND model, rotating, dismantling, with connector pin for bipolar coagulation, especially suitable for dissection, double action jaws, size 3.5 mm, length 20 cm, color code: light blue

including:

ROBI® Plastic Handle

ROBI® Outer Sheath with Forceps Insert





INSTRUMENTS FOR RHEUMATOLOGY

NEEDLE ARTHROSCOPES182-183

RETROFORCE® BIOPSY PUNCH184-185

Special Features:

- Small diameter of 1 mm
- Eyepiece and light connection are remote from the instrument
- Fiber optic system in proven quality
- Elimination of any obtrusive eyepiece/camera head combination in the working area
- Connected to the miniature endoscope with a flexible cable, the eyepiece with attached camera table can be fixed in a holder to the OR table.

Field of Application and Indications

In the diagnosis of inflammatory rheumatic illnesses, especially arthritis associated with an infection, examination of the synovial membrane is becoming increasingly important due to new methods of molecular biology.

When inflammation of a joint begins, the changes in the joint are often only locally pronounced. For this reason a biopsy taken under vision is more informative. The development of needle arthroscopy, and the appropriate instruments, allow small and medium-sized joints, and in particular small finger and toe joints, to be examined under local anesthesia.

Since needle arthroscopy is only negligibly more invasive than a customary arthrocentesis, it can be repeated several times. This opens up the possibility of monitoring the effects of therapeutic interventions directly at the joint itself.


*P. BRÜHLMANN, M. D.,
Rheumaklinik Universitätsspital
Zurich, Switzerland*



Instruments for Rheumatology

Needle Arthroscopes

Diameter 1 mm, length 6 cm



11508



11508


Miniature Straight Forward Telescope 0°, diameter 1 mm, length 6 cm, fiber optic light transmission incorporated, eyepiece and light connection separate from the instrument



28117 R

28117 R

Arthroscope Sheath, with lateral LUER-Lock connector, diameter 1.3 mm, working length 4 cm, for use with Miniature Straight Forward Telescope 0° 11508 and Obturators 28117 RS/RB



28117 RS



28117 RS

Obturator, sharp, for use with Arthroscope Sheath 28117 R



28117 RB

Same, blunt

28272 KLA

Holding System, autoclavable, with quick release coupling KSLOCK including:
Socket
Articulated Stand
Clamping Jaw

Components/Spare Parts see chapter 18

For native joints

There are a number of indications for synovial biopsy. Joint inflammation of unknown origin (e.g., sarcoidosis), the accumulation of crystals or proteins (amyloidosis) or synovial tumors (e.g. PVNS) cannot be detected in the blood or through radiological assessments. The

RETROFORCE® allows safe and fast synovial biopsies, particularly in large joints such as the shoulder, hip or knee. Thanks to this retrograde technique, biopsies can be performed without simultaneous imaging.



Fig. 1: The open RETROFORCE® biopsy punch after insertion via the suprapatellar recess; the correct position is confirmed by the aspiration of synovial fluid.




Fig 2: The biopsy punch is retracted until contact with the synovial tissue is obtained.





Fig. 3: The punch is closed in a retrograde manner in order to obtain the synovial biopsy.






Scan the DataMatrix code to view a video on the application of the RETROFORCE® biopsy punch.



For the safe diagnosis of implant failures

Painful or loose prosthetic joints may have various causes. Infection associated with the implant, a common cause, must first be ruled out but symptoms may also arise from an allergic reaction to the implant or metal/plastic abrasion. In the case of infection in particular, synovial biopsy is far more effective than arthrocentesis alone according to available data. Furthermore, it can detect an allergic cellular reaction or

abrasion particles in the synovial membrane. RETROFORCE® allows a synovial biopsy to be safely performed under local anesthesia in a matter of minutes, e.g., in the hip, knee or shoulder joint. The robust instrument can easily pass through the tough joint capsule and provide a thorough diagnostic evaluation of possible reasons for implant failure within a short period of time.



28902 RF

28902 RF

RETROFORCE® Biopsy Punch, for biopsy of the joints, backward cutting, pointed, diameter 4 mm, working length 13 cm, with suction channel for the aspiration of synovial fluid, suitable for use under local anesthesia or arthroscopy

including:

Outer Sheath, with LUER-Lock connector

Inner Sheath, with backward cutting punch

Handle, without ratchet

optional:

28902 HGR

Handle, with ratchet

Components/Spare Parts see chapter 18





SPINE SURGERY

see NEUROSURGERY catalog



VISUALIZATION SYSTEMS FOR OPEN SURGERY AND MICROSURGERY

VITOM® 2D

2D VISUALIZATION FOR OPEN SURGERY WITH MINIMAL ACCESS188-194

OVERVIEW195

VITOM® II NIR/ICG196-198

SPECIFICATIONS199

HOLDING SYSTEMS200-201

VITOM® 3D

3D VISUALIZATION FOR OPEN SURGERY WITH MINIMAL ACCESS202

OVERVIEW203


VITOM® 3D204

HOLDING SYSTEMS AND ACCESSORIES205-207


VITOM® 2D

Potential Applications

The VITOM® can be used for many specialties in open surgery. In addition to visualization under white light, the VITOM® system also supports the option for fluorescence imaging (ICG and PDD).



Port-based interventions
see NEUROSURGERY catalog



Dysgnathia surgery, flap preparation
see ORAL AND MAXILLOFACIAL SURGERY catalog



Open rhinoplasty, septoplasty, adenotomy
see ENDOSCOPES AND INSTRUMENTS
FOR ENT, ESOPHAGOSCOPY –
BRONCHOSCOPY catalog



**Mitral valve surgery,
pediatric heart surgery**
see ENDOSCOPES AND INSTRUMENTS
FOR CARDIOVASCULAR SURGERY catalog



Mini-thoracotomy
see THORAX catalog




Open thyroidectomy
see LAPAROSCOPY IN SURGERY,
GYNECOLOGY, UROLOGY catalog



Loop conization, colposcopy
see GYNECOLOGY catalog

① **Urethral reconstruction, hypospadias/epispadias correction, artificial sphincter implantation, open prostatectomy**
see UROLOGY catalog




① **Male sling implantation, artificial sphincter**
see PROCTOLOGY catalog




① **Dupuytren's contracture, ulnar shortening osteotomy, arthroplasty**
see ARTHROSCOPY AND SPORTS MEDICINE catalog




① **Herniated discs, spinal stenosis, spondylolysis**
see SPINE SURGERY catalog




① **Anorectal malformation, hypospadias correction, epispadias correction, ambiguous genitalia**
see PEDIATRIC SURGERY catalog



① **Display of glioblastoma in neurosurgery**
see FLUORESCENCE IMAGING WITH PDD



① **Perfusion assessment of anastomoses or free flaps, visualization of sentinel lymph nodes (in trial phase)**
see FLUORESCENCE IMAGING WITH NIR/ICG



VITOM® 2D

2D Visualization for Open Surgery with Minimal Access

The VITOM® system offers a possibility to display open surgical interventions with an incision length of up to approx. 12 cm in a high-quality manner. VITOM® is based on the renowned HOPKINS® rod lens system from KARL STORZ.

Unlike an arthroscope, the VITOM® system is not inserted into the joint but placed at a working distance of 25 – 75 cm above the surgical field with the help of a holding system. This gives the surgeon more room to work.

The VITOM® system offers:

- Excellent image quality
- Great depth of view
- Large working distance
- High flexibility thanks to VITOM® 0° and 90° versions
- Optimal illumination due to integrated lighting
- Compact design requiring minimal space in the OR
- Use of existing KARL STORZ endoscopy system possible



Using the VITOM® system in hand surgery

OR photographs courtesy of: Prof. Dr. Christophe Mathoulin, Institut le la Main, Clinique Jouvenet, Paris, France

The VITOM® system is suitable for the visualization of the following procedures in hand surgery:

- Fasciectomy (Dupuytren's contracture)
- Arthroplasty
- Ulnar-shortening osteotomy
- Ulnar and radial head prosthesis
- Four-corner fusion
- Annular ligament transection
- Neurolysis




Fig. 1: Fasciectomy, visualized with the VITOM® system



Fig. 2: Ulnar head prosthesis, visualized with the VITOM® system



Fig. 3: Annular ligament transection, visualized with the VITOM® system




Fig. 4: Four-corner fusion, visualized with the VITOM® system

VITOM® 2D

2D Visualization for Open Surgery with Minimal Access

Brilliant Visualization

The IMAGE1 S™ camera system provides optimal support for all interventions in minimally invasive and open surgery.

VITOM® provides excellent depth of field, optimal magnification as well as good contrast and excellent color reproduction, which are the ideal prerequisites for the best possible visualization of interventions in open surgery.

Documentation

The VITOM® system is perfectly suited for the documentation of interventions in open surgery with minimal access.

Ergonomic Work

Enhanced images of the open surgical procedure can be observed via a monitor from a convenient distance by the surgeon, the assistant as well as the entire OR team. The system offers everyone present in the OR an optimal view of the surgical field.

Teaching and Training

The VITOM® system is an excellent tool for teaching and training purposes as the system offers an unrestricted and magnified view of the surgical site both inside and outside the OR.




VITOM® 2D

2D Visualization for Open Surgery with Minimal Access

VITOM® Telescope 0°

The VITOM® telescope 0° is particularly suitable for brilliant documentation of open surgeries. Thanks to its

design and 0° direction of view, it can be easily positioned by an assistant.





20916025 AA

VITOM® Telescope 0° with Integrated Illuminator, VITOM® HOPKINS® straight forward telescope 0°, working distance 25 – 75 cm, length 11 cm, autoclavable, with fiber optic light transmission incorporated and condensor lenses, color code: green

VITOM® Telescope 90°

The VITOM® telescope with a 90° direction of view is recommended for the visualization of an intervention as it allows flexible and ergonomic positioning above the surgical site. This is a particular advantage for

operating surgeons who wish to benefit from a clear and enlarged view on the monitor during the procedure.



20916025 DA

VITOM® Telescope 90° with Integrated Illuminator, VITOM® HOPKINS® telescope 90°, working distance 25 – 75 cm, length 11 cm, autoclavable, with fiber optic light transmission incorporated and condensor lenses, color code: blue




5-16

Note: VITOM® is always used with a holding system.

Specifications see page 199

Recommended Set see page 195


Components/Spare Parts see chapter 18

		VITOM® Scope 0°	VITOM® Scope 90°
		with Integrated Illuminator	
		20 9160 25 AA	20 9160 25 DA
495 TIP	 <p>Fiber Optic Light Cable, with straight connector, extremely heat-resistant, enhanced light transmission, diameter 4.8 mm, length 300 cm</p>	●	●
495 NVC	 <p>Fiber Optic Light Cable, with 90° deflection to the instrument, very narrow radius of curvature, diameter 4.8 mm, length 300 cm</p>	●	-
39501 A2	 <p>Wire Tray for Cleaning, Sterilization and Storage of two rigid endoscopes and one light cable, including holder for light post adaptors, silicone telescope holders and lid, external dimensions (w x d x h): 352 x 125 x 54 mm, for rigid endoscopes up to diameter 10 mm and working length 20 cm</p>	●	●

VITOM® 2D

Overview

VITOM® Telescope 0° with Integrated Illuminator
VITOM® Telescope 90° with Integrated Illuminator



20 9160 25 AA/DA

Clamping Cylinder




28272 CN

Fiber Optic Light Cable



495 TIP

Mechanical Holding Arm



28272 UGK

28272 HC

28172 HR

IMAGE1 S™ Three-Chip FULL HD Camera Head



TH 100

Cold Light Fountain Power LED 300 SCB



TL 300

IMAGE1 S™ Camera System



TC 200EN
TC 300

26" FULL HD Monitor



9826 NB

VITOM® II NIR/ICG

for Near Infrared (NIR/ICG) Fluorescence Imaging in Open Surgery

OPAL1™ NIR/ICG – Fluorescence imaging based on the IMAGE1 S™ camera platform



With the OPAL1™ technology for NIR/ICG fluorescence imaging based on the IMAGE1 S™ camera platform, KARL STORZ is able to offer better visualization of anatomical structures that are hidden to the naked eye under white light in minimally invasive and open surgery. The fluorescent dye indocyanine green (ICG) is used for this purpose.

NIR/ICG fluorescence imaging allows the assessment of organ and tissue perfusion, e.g., when setting and controlling anastomoses or during tissue transplantations in plastic and reconstructive surgery.



The VITOM® II NIR/ICG telescope can be easily and quickly adapted to the S-Technologies for NIR/ICG and can therefore be ideally integrated into the modular structure from KARL STORZ.



***The respective national regulations with regard to the approval of fluorescence markers and their applications must be observed.**

VITOM® II NIR/ICG

for Near Infrared (NIR/ICG) Fluorescence Imaging in Open Surgery



209160 25 AGA VITOM® II NIR/ICG Telescope 0°, with integrated **illuminator** and observation filter for fluorescence diagnostics with ICG, HOPKINS®, working distance 25 – 75 cm for white light, 20 – 30 cm for fluorescence applications, length 11 cm, **autoclavable**, with fiber optic light transmission incorporated and condensor lenses, color code: green



495 NCSC Fiber Optic Light Cable, with straight connector, extremely heat-resistant, enhanced light transmission, with safety lock, diameter 4.8 mm, length 250 cm

The IMAGE1 S™ platform is recommended for NIR/ICG applications.

Components/Spare Parts see chapter 18

Suitable Light Sources for NIR/ICG Applications see TELEPRESENCE catalog

VITOM® II NIR/ICG

Overview

VITOM® II NIR/ICG Telescope
with integrated illuminator



20 9160 25 AGA

Clamping Cylinder




28272 CN

Fluid or Fiber Optic Light Cable



495 FR
495 NCSC

Mechanical Holding Arm



28272 UGK

28272 HC

28172 HR

IMAGE1 S™ H3-Z FI Three-Chip FULL HD
Camera Head



TH 102

Cold Light Fountain D-LIGHT P SCB



20 1337 01-1

IMAGE1 S™ Camera System



TC 200EN
TC 300

One-Pedal Footswitch



20 0 141 30

26" FULL HD Monitor



9826 NB

Working distance:	25 – 75 cm		
Depth of view at working distance of:	25 cm	50 cm	75 cm
Depth of view:	approx. 3.5 cm	approx. 7 cm	approx. 10 cm
Field of view at working distance of:	25 cm	50 cm	75 cm
IMAGE1 S™ H3-Z camera zoom 1x	5 cm	10 cm	15 cm
IMAGE1 S™ H3-Z camera zoom 2x	3.5 cm	7 cm	10.5 cm
Reproduction scale at working distance of:	25 cm	50 cm	75 cm
26" Monitor:			
H3-Z camera zoom 1x	approx. 8x	approx. 4x	approx. 3x
H3-Z camera zoom 2x	approx. 16x	approx. 8x	approx. 6x
42" Monitor:			
H3-Z camera zoom 1x	approx. 14x	approx. 7x	approx. 5x
H3-Z camera zoom 2x	approx. 28x	approx. 14x	approx. 10.5x
52" Monitor:			
H3-Z camera zoom 1x	approx. 17x	approx. 8x	approx. 6x
H3-Z camera zoom 2x	approx. 34x	approx. 16x	approx. 12x

Note:

To obtain a good signal for fluorescence applications with VITOM® ICG, a shorter working distance of max. 30 cm is recommended.



The mechanical holding systems from KARL STORZ offer a versatile, convenient and cost-effective possibility for the secure positioning of instruments and telescopes.


A wide range of accessories enables the systems to be configured for any desired fields of application. The robust construction ensures reliable positioning without oscillation.

Special Features:

- Simple, fast and accurate positioning
- Many fields of application possible thanks to various articulated stands and a wide range of accessories
- Flexible positioning enables a large number of different positions
- All joints can be easily released or fixed by means of the central clamp
- Socket for use with European and United States standard rails of OR table
- Variable height adjustment by using the socket
- Extension Rod 28172 HM for the adjustment of particularly large working distances, for example, the VITOM® system
- Ergonomical positioning at the operating table
- Eases the work routine of the assistant
- Instruments and telescopes are clamped securely
- Steady imaging of the operation field
- Maintenance-free solid construction
- Autoclavable
- KSLOCK rapid coupling for mounting clamping jaws, instruments and accessories with KSLOCK pins



Further Mechanical Articulated Stands and Accessories can be found in the TELEPRESENCE catalog, chapter 11 HOLDING SYSTEMS, page 185 ff.



- 28272 HC **Articulated Stand**, L-shaped, long, reinforced version, especially large swivel range, with one mechanical central clamp for all five joint functions, height 48 cm, swivel range 66 cm, with quick release coupling KSLOCK (female)
- 28172 HR **Rotation Socket**, to clamp to the operating table, with one mounted Butterfly Nut 28172 HRS, for European and US standard rails, with lateral clamp for height and angle adjustment of the articulated stand
- 28272 UGN **Clamping Jaw**, metal, clamping range 16.5 up to 23 mm, with quick release coupling KSLOCK (male), for use with all square-headed HOPKINS® telescopes

Accessories

- 28272 CN **Clamping Cylinder**, folding, for flexible mounting of 10 mm telescopes on the telescope sheath, **autoclavable**. The clamping cylinder allows vertical movement and rotation of the telescope.
- 28172 HM **Extension Rod**, 50 cm, with lateral clamp for height adjustment of the articulated stand, for use with Articulated Stands 28272 HA/HB/HC and Sockets 28172 HK/HR

Further Mechanical Articulated Stands and Accessories can be found in the TELEPRESENCE catalog, chapter 11 HOLDING SYSTEMS, page 185 ff.

VITOM® 3D

3D Visualization for Microsurgery and Open Surgery

The application possibilities of the VITOM® 3D are similar to that of the operating microscope. The surgeon can work comfortably with VITOM® 3D via a 3D monitor which allows for a relatively free choice of working positions. The most important functions are controlled via the IMAGE1 PILOT, which is mounted on the OR table in the direct vicinity of the surgeon. The VITOM® 3D system provides many surgical disciplines with a revolutionary solution for the visualization of microsurgical and open surgical interventions.

The VITOM® 3D fits seamlessly into the IMAGE1 S™ platform and can be used with this system. The visualization and documentation of surgeries can therefore be carried out with an existing endoscopy tower. This ideally supports combined work with endoscopes as in, for example, endoscopically assisted microsurgery (EAM).

Benefits at a glance:


- Ergonomic work – the user is not confined to the eyepiece
- Improved workflow – the entire OR team can view the procedure in the same image quality as the surgeon
- Flexible, diverse application possibilities – from visualization and documentation to education and training
- Beneficial for endoscopically assisted microsurgery as it is possible to combine VITOM® 3D with endoscopes
- Small, lightweight and portable system
- Economic synergetic effects from 3D visualization for microsurgery and open surgery as well as endoscopy based on the IMAGE1 S™ platform



VITOM® 3D

Overview

VITOM® 3D, with integrated illumination
Cover, for VITOM® 3D, sterile




TH 200
TH 001*

Holding Arm for VITOM® 3D



28272 HSP

Fiber Optic Light Cable



495 TIP
495 VIT

IMAGE1 PILOT
IMAGE1 PILOT Sterile Cover



TC 014
041150-20*

IMAGE1 S™ Camera System




TC 200EN
TC 302

Cold Light Fountain POWER LED 300 SCB




TL 300

Holding Arm for IMAGE1 PILOT



28272 HB
28172 HR

3D Monitors



TM 323, 9826 NB-3D

3D Polarization Glasses
3D Clip-on Glasses




9800 GF
9800 C

11-16



VITOM® 3D

3D Visualization for Microsurgery and Open Surgery



	<p>TH 200 VITOM® 3D</p>
	<p>with zoom and focus function, integrated illumination and horizontal alignment, working distance 20 – 50 cm, fiber optic light transmission incorporated, suitable for wipe disinfection</p>
For use with:	<ul style="list-style-type: none"> ● IMAGE1 S CONNECT™, basic module ● IMAGE1 S D3-LINK™, module for 3D endoscopy ● IMAGE1 PILOT, input unit

TC 014 **IMAGE1 PILOT**, control unit with 3D wheel, 4 programmable function keys and USB port, for intuitive control of camera systems and connected units, for use with IMAGE1 S™ and VITOM® 3D TH 200

Specifications:

Frame rate	50/60 Hz
Image sensor	2 chip, 4K
Image display	3D, 2D
Scanning method	progressive scan
Zoom	infinitely variable
Working distance (WD)	20 – 50 cm
Magnification (WD 30 cm with 32" 3D Monitor)	approx. 8 – 30 x
Cable length	500 cm
Cable routing	straight
Cleaning	wipe disinfection
Sterilization concept	single-use covers
Control concept	IMAGE1 PILOT for intuitive control of all relevant functions (zoom, focus, menu, navigation), 4 buttons for rapid access, 3D wheel
Camera head buttons	freely programmable
S-Technologies	CLARA, CHROMA, SPECTRA
Safety class	CF-defib

IMAGE1 PILOT is required for the use of VITOM® 3D.

VITOM® 3D and IMAGE1 PILOT are always used with a holding system.

Please note that special clamping jaws are available for mounting VITOM® 3D to the holding system.

Holding Systems and Accessories see TELEPRESENCE catalog, chapter 11 HOLDING SYSTEMS

VERSACRANE™ Holding System – for the convenient positioning of VITOM®



28272 HC

28272 HSP **VERSACRANE™ Holding Arm**, high, mobile, spring-supported, with quick release coupling KSLOCK, for use with KARL STORZ clamping jaws. The VERSACRANE™ holding arm is intended for use with VITOM® scopes.

including:

VERSACRANE™ Holding Arm

Mobile Stand, with height adjustment

WARNING: The VERSACRANE™ holding arm cannot be used with rigid endoscopes!

Clamping Jaws and Accessories for VITOM® 3D

28272 VTK **VITOM® 3D Clamping Jaw**, with ball joint and quick release coupling KSLOCK (male), for use with VITOM® 3D and KARL STORZ holding systems with quick release coupling KSLOCK

TH 001* **Cover**, for VITOM® 3D, sterile, for single use, package of 10





STERILE 

	<p>28272 VTK VITOM® 3D Clamping Jaw, with ball joint and quick release coupling KSLOCK (male), for use with VITOM® 3D and KARL STORZ holding systems with quick release coupling KSLOCK</p>
	<p>28272 VTP VITOM® 3D Clamping Jaw, for POINT SETTER, with dovetail connector, for use with VITOM® 3D and POINT SETTER holding system</p>
	<p>495 TIP Fiber Optic Light Cable, with straight connector, extremely heat-resistant, enhanced light transmission, diameter 4.8 mm, length 300 cm</p> <p>495 VIT Fiber Optic Light Cable, with straight connector, extremely heat-resistant, enhanced light transmission, diameter 4.8 mm, length 550 cm</p>
	<p>TH 001* Cover, for VITOM® 3D, sterile, for single use, package of 10</p> <p style="text-align: right;">STERILE </p>
	<p>TH 002 VITOM® 3D Illuminator, additional lighting for VITOM® 3D, with 1 adjustable lens, autoclavable, for use with VITOM® 3D and light cable</p>
	<p>TH 003 Protective Cover, high-grade protective cover, padded imitation leather, for protecting the VITOM® 3D during storage and transport, for use with VITOM® 3D and holding arm</p>
	<p>Set 2B</p> <p>39502 ZH Wire Tray, stackable, with hole plates</p> <p>39502 LH Lid</p> <p>39100 SH Silicone Insert</p> <p>39100 PS Fixation Pins, package of 12</p> <p>39360 AS Silicone Tie-Downs, package of 12</p>







Please note: The instruments displayed are not included in the wire tray.

IMAGE1 PILOT with holding system for fixation to the operating table

	<p>TC 014</p>	<p>IMAGE1 PILOT, control unit with 3D wheel, 4 programmable function keys and USB port, for intuitive control of camera systems and connected units, for use with IMAGE1 S™ and VITOM® 3D TH 200</p>
	<p>28172 HR</p>	<p>Rotation Socket, to clamp to the operating table, with one mounted Butterfly Nut 28172 HRS, for European and US standard rails, with lateral clamp for height and angle adjustment of the articulated stand</p>
	<p>28272 HB</p>	<p>Articulated Stand, reinforced version, L-shaped, with one central clamp for all five joint functions, height 48 cm, operating range 52 cm, with quick release coupling KSLOCK (female)</p>
	<p>041150-20*</p>	<p>Cover, elasticated, 42 x 164 cm, sterile, for single use, package of 20, for use with KARL STORZ holding systems and IMAGE1 PILOT</p>

Monitor

	<p>TM 323</p>	<p>32" 3D Monitor including: Mains Cord External 24 VDC Power Supply 3x 3D Polarization Glasses Cable Cover</p>
	<p>9832 SFH</p>	<p>Monitor Stand, for professional use, height-adjustable, tiltable, rotation +/-30°, disinfected, color white, with VESA 200 adaptor, for use with 32" 3D Monitor TM 323</p>
	<p>9800 GF</p>	<p>3D Polarization Glasses, fogless, passive, package of 2, for use with 3D monitors</p>
	<p>9800 C</p>	<p>3D Clip-on Glasses, circularly polarized</p>



Holding Systems and Accessories see TELEPRESENCE catalog, chapter 11 HOLDING SYSTEMS



FULL HD IMAGING FOR OPERATING MICROSCOPES

INTRODUCTION211

OVERVIEW212

IMAGE1 S™ THREE-CHIP FULL HD
C-MOUNT CAMERA HEAD213

TV ADAPTORS214-216

Accessories for Operating Microscopes

IMAGE1 S™

With the operating microscope, the surgeon always has a perfect view of the operating field. Assistants, OR nurses and students, however, often experience poor visualization of the microscope image. This is especially true if brilliant visualization is not available. KARL STORZ offers solutions from one source that are specially designed to equip operating microscopes from leading manufacturers with state-of-the-art technology. To achieve optimal results, all components in the video chain – from the camera to the monitor – must be of the highest quality.

The most straightforward and professional connection between the camera and the microscope is the so-called direct adaption.

Here the IMAGE1 S™ H3-M COVIEW® microscope camera and the corresponding QUINTUS® TV adaptor are directly connected to the microscope via the C-MOUNT connection.

The microscope camera head is part of the IMAGE1 S™ camera platform and is equipped with the S-Technologies CLARA, CHROMA and SPECTRA.



Accessories for Operating Microscopes

Overview

26" FULL HD Monitor



9826 NB

ZeroWire Transmission Set (optional)



9500 ZW

KARL STORZ AIDA® Documentation System



WD 200
WD 250

IMAGE1 S™ Camera System



TC 200EN
TC 300

IMAGE1 S™ H3-M COVIEW® Three-Chip
FULL HD C-MOUNT Camera Head



TH 106

TV Adaptors




Operating Microscope



Operating microscopes
from Carl Zeiss, LEICA Microsystems
and Möller-Wedel are supported

IMAGE1 S™ ^{NEW}

Three-Chip FULL HD C-MOUNT Camera Head for Microscopy



With C-MOUNT thread for coupling to microscopes

	TH 106 IMAGE1 S™ H3-M COVIEW® Three-Chip FULL HD C-MOUNT Camera Head
For use with:	● IMAGE1 S CONNECT™ + IMAGE1 S™ H3-LINK

Specifications:

Frame rate	50/60 Hz
Image sensor	3-chip
Resolution	1920 x 1080
Scanning method	progressive scan
Dimensions w x h x l	45 x 50 x 60 mm
Weight	240 g
Cable length	900 cm, video cable detachable at the camera head
Cable guide	straight
Camera head buttons	freely programmable
Grasping mechanism	C-MOUNT connection
Reprocessing	wipe disinfection
S-Technologies	CLARA, CHROMA, SPECTRA
Protection class	CF-Defib

QUINTUS® – High-Performance TV Adaptor for Operating Microscopes

Unleash the full performance of your operating microscope with imaging solutions from KARL STORZ

The new QUINTUS® TV adaptor is the perfect interface between the operating microscope and the IMAGE1 S™ H3-M COVIEW® microscope camera head from KARL STORZ.

The innovative features of QUINTUS® are easy to use, making it one of the most flexible TV adaptors on the market.




Product Features:


- A rotating C-MOUNT connection at the QUINTUS® TV adaptor allows immediate adaptation of the camera orientation during mounting.
- The focus control makes it possible to easily achieve parfocality (perfectly sharp camera and microscope images).
- The iris control provides convenient and optimal adjustment of the depth of field.
- Pan (X) function enables adjustment of the horizontal position of the camera image.
- Tilt (Y) function enables adjustment of the vertical position of the camera image. The pan and tilt functions help the surgeon to adjust the position of the camera image according to his individual needs.
- The QUINTUS® ZOOM model also features a variable focal length $f = 43 - 86$ mm. This allows the surgeon greater flexibility in choosing the exact zone required for documentation.

Focal length of the QUINTUS® TV adaptor:

The QUINTUS® TV adaptor is available in the fixed focal length $f = 55$ mm or as a zoom model with variable focal length $43 - 86$ mm. This provides an optimal image in 16:9 in conjunction with the H3-M COVIEW® microscope camera head.



Focal lengths: H3-M COVIEW® camera image detail using a QUINTUS® TV adaptor with a fixed focal length of 55 mm.



Variable focal length: Adjustable H3-M COVIEW® camera image detail using a QUINTUS® zoom adaptor with variable focal length of 43 – 86 mm.

Accessories for Operating Microscopes

TV Adaptors

QUINTUS® TV Adaptor for operating microscopes from CARL ZEISS MEDITEC with fixed focal length



20 9230 55 **QUINTUS® Z 55 TV Adaptor**, for CARL ZEISS MEDITEC operating microscopes, $f = 55$ mm, recommended for IMAGE1 HD H3-M/H3-M COVIEW®, H3, H3-Z as well as S1 and S3 camera heads

QUINTUS® Zoom TV Adaptor for operating microscopes from CARL ZEISS MEDITEC with variable focal length



20 9230 00 Z **QUINTUS® Zoom TV Adaptor**, for CARL ZEISS MEDITEC operating microscopes, with variable focal length $f = 43 - 86$ mm, for use with all KARL STORZ cameras (SD and HD)

Further accessories for operating microscopes from CARL ZEISS MEDITEC



20 9250 00 **Iris**, for ZEISS Pentero®, iris as a necessary extension between the QUINTUS® TV adaptor and the operating microscope ZEISS Pentero®



301513 **Optical Beamsplitter 50/50**, for use with ZEISS operating microscope or colposcope

Note: Optical beamsplitters for other operating microscopes (i.e. LEICA or Möller-Wedel) are available directly from the manufacturers.

Accessories for Operating Microscopes

TV Adaptors

QUINTUS® TV Adaptor for operating microscopes from LEICA Microsystems with fixed focal length



20 9330 55 **QUINTUS® L 55 TV Adaptor**, for LEICA Microsystems operating microscopes, $f = 55$ mm, recommended for IMAGE1 HD H3-M/H3-M COVIEW®, H3, H3-Z as well as S1 and S3 camera heads

QUINTUS® TV Adaptor for operating microscopes from LEICA Microsystems with variable focal length



20 9330 00 Z **QUINTUS® Zoom TV Adaptor**, for LEICA Microsystems operating microscopes, with variable focal length $f = 43 - 86$ mm, for use with all KARL STORZ cameras (SD and HD)

QUINTUS® TV Adaptor for operating microscopes from Möller-Wedel with fixed focal length



20 9530 55 **QUINTUS® M 55 TV Adaptor**, for Möller-Wedel operating microscopes, $f = 55$ mm, recommended for IMAGE1 HD H3-M/H3-M COVIEW®, H3, H3-Z as well as S1 and S3 camera heads

Note: Optical beamsplitters for other operating microscopes (i.e. LEICA or Möller-Wedel) are available directly from the manufacturers.



HOLDING SYSTEMS FOR ARTHROSCOPY

LEG HOLDER218

SHOULDER SUPPORT219

Holding Systems

Leg Holder



*adjustable jaws,
all-round padding*




pivots 360°



secure fastening



360° rotating



*height-adjustable,
swivels away from
OR table*

28188 D

Arthroscopy Leg Holder

including:

Release Clamp, 25 mm

Neoprene Cushion, 600 x 140 x 20 mm

Closure Stripe, perforated, Vulkollan 450 x 90 mm


Components/Spare Parts see chapter 18

Holding Systems

Shoulder Traction System

Special Features:

- Shoulder traction system for the lateral decubitus position
- Compact design
- Very light thanks to aluminium profile tubes
- For fixation to the OR table rails
- Hand fixation for positioning the hand



28188 LA **Shoulder Support**, for use with Set of Weights 28188 LB, Hand Fixation 28188 LC and Rotation Socket 28172 HR

28188 LB **Set of Weights**

28188 LC **Hand Fixation**

28172 HR **Rotation Socket**, to clamp to the operating table, with one mounted Butterfly Nut 28172 HRS, for European and US standard rails, with lateral clamp for height and angle adjustment of the articulated stand





TRAINING MODELS FOR ARTHROSCOPY

HIGH-END SIMULATORS

KNEE222-225

HIGH-END SIMULATORS

SHOULDER226-229

HIGH-END SIMULATORS

KNEE AND SHOULDER230-233



The KARL STORZ simulator for arthroscopy provides orthopedic surgeons with a training model for teaching and training the practical skills and know-how required for minimally invasive techniques.

Guided training enables trainees to enhance their surgical skills in a virtual environment and to manage complications with no risk for live patients. The simulator offers objective, comparable and reproducible performance feedback to complete the learning process. An arthroscope equipped with sensors and specially adapted to the simulation trainer makes it

possible to follow steps and movements on the monitor. The modified KARL STORZ arthroscope as well as other adapted original instruments helps trainees become familiar with instruments in a straightforward and highly realistic manner.

The anatomical knee model delivers realistic, tactile feedback in a highly realistic training environment using these instruments. Furthermore, the simulation software provides a wide range of intraoperative scenarios.

Original operating instruments provide a highly realistic simulation experience and facilitate familiarization with instruments.

Similar to the operating room, the high-end simulators feature:

- 3 virtual telescopes: 0°, 30° and 70°
- High-end PC and 23" multi touch screen, mouse and keyboard
- Mobile cart with height-adjustable monitor

Basic Module

8* guided training courses enable basic skills to be acquired that are integrated into a realistic simulation. Mastering these basic tasks enables surgeons to perform a complete arthroscopy in a more straightforward, efficient, and professional manner.

Diagnosics

Perform a guided arthroscopy tour through different portals.

“Catch the Stars”

Find and remove all the stars concealed below the meniscus and between ligaments or bones.

Meniscus resection

Visually guided meniscus resection including helpful resection map.

Learning objectives:

- Understand the concept of triangulation
- Learn the correct way to perform a diagnostic tour
- Correctly handle the instruments without causing cartilage damage
- Detect and eliminate lesions and malformations in a safe and efficient manner

Diagnostic Module

8* virtual patient cases with varying level of difficulty offer the surgeon the opportunity to perform complete diagnostic arthroscopic interventions. Virtual patient cases include various meniscus lesions, unhappy triad and arthrosis grade I-III.

Learning objectives:

- Safety in systematic examination; inspection of all important features
- Inspect the knee completely and describe visible lesions
- Safely handle the instruments to avoid collisions with the tissue

Therapeutic Module

Virtual patients with lesions in various locations provide optimal training for first steps in operative arthroscopy – with real operating instruments. Patient cases include meniscus lesions, synovial membrane inflammation and loose body removal.

Learning objectives:

- Inspect the knee completely and describe visible pathologies
- Treat the diagnosed pathologies
- Loose body removal; analysis and review of the intervention

Expert-defined metrics provide objective feedback for all modules and thus offer the best learning outcomes.

* The number of patient cases may change due to further development of the product.



573614

573611

Stationary ARTHROTRAINER, with anatomical knee model, in a reusable transport case, ideal for use at conferences, workshops and training centers including:

Integrated Learning Management System

High-end PC and 23" Multi Touch Screen

Mobile Cart, with height-adjustable monitor

Tool Set, with arthroscope, grasping forceps/punch, shaver and palpation hook

Software

Wireless Keyboard

Mains Cord

Cleaning Box

Transport Case

573614

Same, in single use packaging

Basic Instruments – included in the ARTHROTRAINER Tool Set:



5733101

5733101 **Arthroscope**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733002

5733002 **Grasping Forceps/Punch**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733004

5733004 **Palpation Hook**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733003

5733003 **Shaver**, adapted original instrument with sensors, for use with ARTHROTRAINER

Services:



- 5733103 **Refurbishment of Anatomical Knee Model**, replacement of worn components (incidentals), refurbishment, calibration and function control
- 5733104 **Skin Cover for Anatomical Knee Model**, customized cover with access points to the knee joint

Optional Accessories:



5733001

- 5733001 **Transport Case**, for all stationary trainers, reusable, recommended for frequent shipment



The KARL STORZ simulator for arthroscopy provides orthopedic surgeons with a training model for teaching and training the practical skills and know-how required for minimally invasive techniques.

Guided training enables trainees to enhance their surgical skills in a virtual environment and to manage complications with no risk for live patients. The simulator offers objective, comparable and reproducible performance feedback to complete the learning process. An arthroscope equipped with sensors and specially adapted to the simulation trainer makes it

possible to follow steps and movements on the monitor. The modified KARL STORZ arthroscope as well as other adapted original instruments helps trainees become familiar with instruments in a straightforward and highly realistic manner.

The anatomical shoulder model delivers realistic, tactile feedback in a highly realistic training environment using these instruments. Furthermore, the simulation software provides a wide range of intraoperative scenarios.

Original operating instruments provide a highly realistic simulation experience and facilitate familiarization with instruments.

Similar to the operating room, the high-end simulators feature:

- 3 virtual telescopes: 0°, 30° and 70°
- High-end PC and 23" multi touch screen, mouse and keyboard
- Mobile cart with height-adjustable monitor

Basic Module

8* guided training courses enable basic skills to be acquired that are integrated into a realistic simulation. Mastering these basic tasks enables surgeons to perform a complete arthroscopy in a more straightforward, efficient, and professional manner.

Diagnostics

Guided diagnostic arthroscopic tour of the glenohumeral joint and the subacromial space.

Triangulation

Efficient utilization of arthroscopic instruments in order to reach difficult-to-access areas in the glenohumeral joint and the subacromial space.

“Catch the Stars”

Find and remove all the stars in the glenohumeral joint and the subacromial space that are concealed between ligaments and behind bones.

Learning objectives:

- Learn the correct way to perform a diagnostic tour
- Correctly handle the instruments without causing cartilage damage
- Detect and eliminate foreign bodies in a safe and efficient manner

Diagnostic Module

4* virtual patient cases with varying level of difficulty offer the surgeon the opportunity to perform complete diagnostic arthroscopic interventions. Virtual patient cases include different lesions in the rotator cuff as well as impingement syndrome.

Learning objectives:

- Inspect the shoulder completely in both joint spaces and describe visible lesions
- Safely handle the instruments to avoid collisions with the tissue

Therapeutic Module

8* virtual patients with lesions in different locations provide optimal training for first steps in operative arthroscopy – with real operating instruments. Patient cases include loose body removal, subacromial debridement and decompression.

Learning objectives:

- Inspect the shoulder completely and describe visible pathologies
- Treat the diagnosed pathologies
- Loose body removal; analysis and review of the intervention

Expert-defined metrics provide objective feedback for all modules and thus offer the best learning outcomes.

* The number of patient cases may change due to further development of the product.



573615

573612

Stationary ARTHROTRAINER, with anatomical shoulder model (for beach chair and lateral positioning), in a reusable transport case, ideal for use at conferences, workshops and training centers

including:

Integrated Learning Management System

High-end PC and 23" Multi Touch Screen

Mobile Cart, with height-adjustable monitor

Tool Set, with arthroscope, grasping forceps/punch, shaver and palpation hook

Software

Wireless Keyboard

Mains Cord

Cleaning Box

Transport Case

573615

Same, in single use packaging

Basic Instruments – included in the ARTHROTRAINER Tool Set:



5733101

5733101 **Arthroscope**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733002

5733002 **Grasping Forceps/Punch**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733004

5733004 **Palpation Hook**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733003

5733003 **Shaver**, adapted original instrument with sensors, for use with ARTHROTRAINER

Services:



- 5733106 **Refurbishment of Anatomical Shoulder Model,** replacement of worn components (incidentals), refurbishment, calibration and function control
- 5733107 **Skin Cover for Anatomical Shoulder Model,** customized cover with access points to the shoulder joint

Optional Accessories:



5733001

- 5733001 **Transport Case,** for all stationary trainers, reusable, recommended for frequent shipment



The KARL STORZ simulator for arthroscopy provides orthopedic surgeons with a training model for teaching and training the practical skills and know-how required for minimally invasive techniques.

Guided training enables trainees to enhance their surgical skills in a virtual environment and to manage complications with no risk for live patients. The simulator offers objective, comparable and reproducible performance feedback to complete the learning process. An arthroscope equipped with sensors and specially adapted to the simulation trainer makes it

possible to follow steps and movements on the monitor. The modified KARL STORZ arthroscope as well as other adapted original instruments helps trainees become familiar with instruments in a straightforward and highly realistic manner.

The anatomical knee and shoulder models deliver realistic, tactile feedback in a highly realistic training environment using these instruments. Furthermore, the simulation software provides a wide range of intra-operative scenarios.

Basic Module for the Shoulder and Knee

Guided training courses enable basic skills to be mastered, fully integrated into a realistic simulation.

Learning objectives:

- Learn the correct way to perform a diagnostic tour
- Correctly handle the instruments without causing cartilage damage
- Detect and eliminate lesions and malformations in a safe and efficient manner
- Understand the concept of triangulation

Diagnostic Module for the Shoulder and Knee

Virtual patient cases with varying level of difficulty offer the surgeon the chance to perform complete diagnostic arthroscopic interventions.

For the **knee**, virtual patients include different meniscus lesions, unhappy triad and arthrosis grade I-III.

For the **shoulder**, virtual patients include different lesions in rotator cuff and impingement syndrome.

Learning objectives:

- Inspect the knee completely and describe visible lesions
- Safely handle the instruments to avoid collisions with the tissue
- Safety in systematic examination; inspection of all important features

Therapeutic Module for the Shoulder and Knee



Virtual patients with various lesions in different locations provide training for the first steps in operative arthroscopy – using real operating equipment.

Interventions on the **knee** include different meniscus lesions, synovial membrane inflammations and loose body removal.

Interventions on the **shoulder** include loose body removal, subacromial debridement and decompression.

Learning objectives:

- Inspect the knee and shoulder completely and describe visible pathologies
- Treating the diagnosed pathologies
- Grasp and remove the chips; analyze and review the operation



573613

573610

Stationary ARTHROTRAINER, with anatomical knee and shoulder models (for beach chair and lateral positioning), in a reusable transport case, ideal for use at conferences, workshops and training centers including:

Integrated Learning Management System

High-end PC and 23" Multi Touch Screen

Mobile Cart, with height-adjustable monitor

Tool Set, with arthroscope, grasping forceps/punch, shaver and palpation hook

Software

Wireless Keyboard

Mains Cord

Cleaning Box

Transport Case

573613

Same, in single use packaging

Basic Instruments – included in the ARTHROTRAINER Tool Set:



5733101

5733101 **Arthroscope**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733002

5733002 **Grasping Forceps/Punch**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733004

5733004 **Palpation Hook**, adapted original instrument with sensors, for use with ARTHROTRAINER



5733003

5733003 **Shaver**, adapted original instrument with sensors, for use with ARTHROTRAINER

Services Knee:



5733103 **Refurbishment of Anatomical Knee Model,** replacement of worn components (incidentals), refurbishment, calibration and function control

5733104 **Skin Cover for Anatomical Knee Model,** customized cover with access points to the knee joint

Services Shoulder:



5733106 **Refurbishment of Anatomical Shoulder Model,** replacement of worn components (incidentals), refurbishment, calibration and function control

5733107 **Skin Cover for Anatomical Shoulder Model,** customized cover with access points to the shoulder joint

Optional Accessories:



5733001

5733001 **Transport Case,** for all stationary trainers, reusable, recommended for frequent shipment





EXTRACORPOREAL SHOCK WAVE THERAPY (ESWT) IN ORTHOPEDICS

STORZ MEDICAL236

STORZ MEDICAL
DUOLITH® SD1 TOWER »ULTRA«237

STORZ MEDICAL
DUOLITH® SD1 T-TOP »F-SW ultra«238

STORZ MEDICAL
MASTERPULS® »ultra«239

Established in 1987, STORZ MEDICAL AG is a Swiss member company of the KARL STORZ Group. With its state-of-the-art technological innovations, STORZ MEDICAL is setting new standards for shock wave therapy in urology, cardiology, orthopedics, aesthetic medicine and dermatology.

Applications for Shock Wave Therapy

Orthopedics (focused and radial shock wave therapy):

- Achillodynia, calcified tendinitis, patellar tendonitis, plantar fasciitis, radial and ulnar humeral epicondylitis, tibial stress syndrome, trochanteric tendinopathy
- Myofascial pain syndrome, trigger points, fascia treatment, paravertebral treatments
- Pseudarthrosis (focused only)

Urology (focused shock wave therapy):

- ED: Erectile Dysfunction
- CPPS: Chronic Pelvic Pain Syndrome
- IPP: Peyronie's disease (Induratio Penis Plastica)

Dermatology (focused shock wave therapy):

- Wound healing
- Ulcers, diabetic foot, decubitus ulcers
- Burns
- Cellulite (combined radial and focused shock wave therapy)
- Lipedema/lymphedema

Neurology (focused shock wave therapy):

- Spastic muscle paralysis (e.g., caused by infantile cerebral palsy or a stroke)



Fig. 1: Focused shock wave therapy for epicondylitis



Fig. 2: Radial shock wave therapy for patellar tendonitis



Fig. 3: Treatment of the muscles in the lumbar spine



Fig. 4: Treatment of the fascia lata

STORZ MEDICAL DUOLITH® SD1 TOWER »ultra«

Combined Shock Wave Therapy

STORZ
KARL STORZ — ENDOSKOPE

STORZ MEDICAL

The DUOLITH® SD1 TOWER »ultra« shock wave system represents a clear modular concept that meets the growing therapeutic and diagnostic needs of a medical practice. It benefits both newcomers to extracorporeal shock wave therapy and experienced users. The DUOLITH® SD1 TOWER »ultra« can be customized according to individual needs or expanded as desired and is centrally controlled via a 15.4" touch screen. All modular elements in the entire system are

interconnected in the equipment cart. The DUOLITH® SD1 TOWER »ultra« combines radial and focused shock wave therapies*, complementary vibration and vacuum therapies as well as the integrated diagnostic ultrasound imaging in one system.

*Specifications correspond to the DUOLITH® T-TOP »F-SW ultra« and the MASTERPULS® MP200 »ultra«



Fig. 1: DUOLITH® SD1 TOWER »ultra«



Fig. 2: Handpieces can be combined as required

STORZ MEDICAL DUOLITH® SD1 T-TOP »F-SW ultra«

Focused Shock Wave Therapy

STORZ
KARL STORZ — ENDOSKOPE

STORZ MEDICAL

High-quality workmanship and optimal ergonomics mark the design of the new focused shock wave generation with the »SEPIA« handpiece. The special flexibility of the handpiece cable supports fatigue-free and, thus, easier treatment always directly at the patient – an important factor in the day-to-day routine.

All the important control elements have been integrated into the handpiece. Frequency and energy level can be adjusted directly at the handpiece. Users benefit from reduced revision costs thanks to the easy change of the coil.



DUOLITH® SD1 T-TOP »F-SW ultra«

- Focused shock wave, standard energy level:
0.01 – 0.55 mJ/mm²
- Focused shock wave, enhanced energy level:
0.03 – 1.24 mJ/mm²
- Focused »SEPIA« handpiece with integrated display for rapid treatment
- 10" touch screen (optional)

The radial shock wave systems of the MASTERPULS® »ultra« line are characterized by their compact dimensions, high reliability, low maintenance costs and silent on-board »Air Power« drive.

All important control elements are integrated into the »FALCON« handpiece display and, thus, facilitate uninterrupted and quick treatment directly at the patient.



MASTERPULS® MP50 »ultra«

- Radial shock wave:
Pressure: 0.3 – 4.0 bareff,
Frequency: 1 – 17 Hz (depending on pressure)
- »FALCON« radial handpiece with integrated display for rapid treatment
- Vibration therapy (optional), V-ACTOR®: 1 – 21 Hz
- 10" touch screen (optional)




MASTERPULS® MP100 »ultra«

- Pressure: 0.3 – 5.0 bareff,
Frequency: 1 – 21 Hz (depending on pressure)
- »FALCON« radial handpiece with integrated display and »Skin Touch« function for rapid treatment
- Vibration therapy (optional), V-ACTOR®: 1 – 31 Hz
- 10" touch screen (optional)



MASTERPULS® MP200 »ultra«

- Radial shock wave:
Pressure: 0.3 – 5.0 bareff,
Frequenz: 1 – 21 Hz
- »FALCON« radial handpiece with integrated display and »Skin Touch« function for rapid treatment
- Two R-SW connectors
- Vibration therapy (optional), V-ACTOR®: 1 – 35 Hz
- VACU-ACTOR® technology (optional)
- 10" touch screen (optional)





UNITS AND ACCESSORIES

SUCTION AND IRRIGATION SYSTEMS

MOTOR SYSTEMS

HIGH FREQUENCY SURGERY UNITS



Units and Accessories for Arthroscopy



- **SUCTION AND IRRIGATION SYSTEMS**
- **MOTOR SYSTEMS**
- **HIGH FREQUENCY SURGERY UNITS**

The units manufactured by KARL STORZ combine long-lasting precision mechanics with state-of-the-art micro-electronic programmable controls. At KARL STORZ, the greatest emphasis is placed on user and patient safety. The quality assurance system of KARL STORZ is certified in accordance with the requirements of ISO 9001/EN 46001. It guarantees constant quality testing in the selection of materials and components. At the end of each manufacturing process, tests are carried out with automatic measuring and testing systems developed specially for this purpose. The results are recorded and logged. That gives each device a distinct “fingerprint” that can be checked at any time before and after it is delivered to the customer.

The standardized, modular design of KARL STORZ units was developed based on extensive ergonomic studies and is conceived for ease of care and cleaning and user-friendly practice, as well as to meet the demands of the special hygienic standards required in surgery. Clearly laid out adjacent function keys and displays guarantee efficient operation and make it easier to constantly monitor actual and set parameters. Acoustic and visual warning signals also assist the user. The settings can be changed manually at any time. Automatic microelectronic control systems guarantee optimum operating conditions and therefore relieve the surgeon in his work who can then fully concentrate on medical procedures.

The overall KARL STORZ product line includes the following categories of units with accessories:

- **Insufflators**
- **Suction and Irrigation Systems**
- **Motor Systems**
- **Lithotripsy**
- **HF Surgery Units**

SUCTION AND IRRIGATION SYSTEMS

MOTOR SYSTEMS

HIGH FREQUENCY SURGERY UNITS



■ SUCTION AND IRRIGATION SYSTEMS

ARTHROPUMP® Power

NEW ENDOMAT® SELECT

ARTHROPUMP® Power

Special Features

Special Features:

- Can be used as both single- and double-roller pump (single or continuous flow)
- Hemostasis mode: Rapid bleeding control by activating the red footswitch (indicated by an acoustic signal)
- Lavage mode: Rapid joint irrigation for a continuously clear view by activating the blue footswitch
- Consistently good view: Optimized control software enables constant comparison and adjustment of inflow and outflow parameters to ensure constant joint distension
- No image pulsation: Special control software and pump bed design provide a homogenous and constant irrigation inflow
- Tubing sets available for single use or as day sets
- Easy connection of the tubing set – computer animation displayed on the pump screen enables smooth installation of the tubing sets during pump start-up
- Color coding of the pump bed and tubing set facilitates identification:
 - Blue: Irrigation
 - Red: Suction
- Display and adjustment of parameters via touchscreen display: Enables both pressure and flow parameters as well as hemostasis phase values and fluid bag size to be set.
- One footswitch for UNIDRIVE® S III ARTHRO SCB and ARTHROPUMP® Power: Efficient arthroscopic work due to unique synergy between shaver system and pump
- Integrated acoustic warning signal indicates impending fluid exchange



ARTHROPUMP® Power

Fluid Management System
Recommended Standard Set Configuration



- 28 3407 01-1 ARTHROPUMP® Power,**
power supply 100 – 240 VAC, 50/60 Hz
including:
- Connecting Cable,** to UNIDRIVE® S III ARTHRO SCB
 - SCB Connecting Cable,** length 100 cm
 - Four-Pedal Footswitch**
 - Tube Set Irrigation***, sterile, for single use, package of 3
 - Tube Set Suction***, sterile, for single use, package of 3



Specifications:

Pressure-regulated	- Normal: 20-200 mmHg - Hemostasis: +20% - +90% - Shaver: +0% - +80%	Power supply	100-240 VAC, 50/60 Hz
Flow-regulated	- Normal: 10-200 ml/min - Shaver: 50-500 ml/min - Lavage: 150-500 ml/min	Dimensions w x h x d	447 x 155 x 313 mm
		Weight	8.8 kg
		Certified to	IEC 601-1, CE acc. to MDD








Optional Accessories for ARTHROPUMP® Power see pages U 9-10
Components/Spare Parts see chapter 18

ARTHROPUMP® Power

System Components

SUCTION AND IRRIGATION SYSTEMS



ARTHROPUMP® Power

Optional Accessories



20 0168 34 **Four-Pedal Footswitch**



28 3407 70 **Connecting Cable**, to transmit the footswitch signal from ARTHROPUMP® Power to UNIDRIVE® S III ARTHRO SCB, length 200 cm



28 3407 71 **Extension Cable**, between ARTHROPUMP® Power and Four-Pedal Footswitch 20 0128 34

For single use

Continuous-Flow – Irrigation and Suction



031328-10* **Tubing Set Irrigation**, with two puncture needles, sterile, for single use, package of 10



031228-10* **Tubing Set Suction**, with two suction tubes, sterile, for single use, package of 10

Single-Flow – Irrigation



031328-10* **Tubing Set Irrigation**, with two puncture needles, sterile, for single use, package of 10

6-121




Day Set

Continuous-Flow – Irrigation and Suction

STERILE



031261-10* **Pump Tubing Day Set**, with two puncture needles, for day use, sterile, for single use, package of 10, for use with Patient Tubes 031162-01 or 031162-10



031162-10* **Patient Tube****, sterile, for single use, package of 10, for use with Pump Tubing Day Set 031261-01 or 031261-10




031228-10* **Tubing Set Suction**, with two suction tubes, sterile, for single use, package of 10

Single-Flow – Irrigation

STERILE



031261-10* **Pump Tubing Day Set**, with two puncture needles, for day use, sterile, for single use, package of 10, for use with Patient Tubes 031162-01 or 031162-10



031162-10* **Patient Tube****, sterile, for single use, package of 10, for use with Pump Tubing Day Set 031261-01 or 031261-10



** Also in combination with 031161-10, 031167-10, 031168-10

ENDOMAT® SELECT ^{NEW}

Roller pump for the irrigation of fluids

Special Features:

- Roller pump system for pressure-controlled irrigation
- Max. pressure setting: 150 mmHg
- Interface and communication with UNIDRIVE® S III ARTHRO SCB supports reliable joint distension
- Unit and accessories extremely easy to use
- Multidisciplinary use
- With connection option for KARL STORZ Communication Bus (KARL STORZ-SCB)
- Boost mode: For stabilization of the cavity when shaver is activated or for hemostasis by activating an additional one-pedal footswitch



ENDOMAT® SELECT ^{NEW}

Roller Pumps – Suction or Irrigation System
Recommended Standard Set Configuration

STORZ
KARL STORZ — ENDOSKOPE



Basic Unit:

UP 210 **ENDOMAT® SELECT**, suction or irrigation pump,
incl. mains cord, power supply 100 – 240 VAC,
50/60 Hz

Software Module for Arthroscopy:

UP 605 **Arthroscopy, Software, License**, allows selection of the
procedures “KNEE”, “HIP”, “SHOULDER” and “Small Joints”,
for use with ENDOMAT® SELECT UP 210

Specifications:

Software package	Arthroscopy	Operating mode	Irrigation, pressure-controlled
Pressure max.	150 mmHg	Dimensions w x h x d	305 x 110 x 260 mm
Power supply	100-240 VAC, 50/60 Hz	Certified to	IEC 601-1, CE acc. to MDD
Weight	4.7 kg		
Parameter display	- Set pressure - Actual pressure - Percentage pressure increase		



Note:


The ENDOMAT® SELECT only functions after uploading a software module (e.g. UP 605). When placing an order for this system, please consult Configuration Flyer 96311002.

Optional Accessories for ENDOMAT® SELECT see page U 14

Components/Spare Parts see chapter 18



UNIT SIDE
PATIENT SIDE








7-16



** **Optional:** Independent activation of the boost modus via One-Pedal Footswitch (200141 30).

ENDOMAT® SELECT

Optional Accessories

	031523-10*	Tubing Set , irrigation, PC, sterile, for single use, package of 10, for use with HAMOU® ENDOMAT® 26 3311 20 and ENDOMAT® SELECT UP 210	STERILE 
	UP 610	ADVANCED Package, Software, License , extends functions of installed software packages, for use with ENDOMAT® SELECT UP 210	
	20 0900 70	SCB Connecting Cable , length 30 cm	
	UP 006	Control Cable , 1x LEMO 5-pin 0° and 1x LEMO 12-pin 0° connector, length 100 cm, for transmission of the footswitch signal between UNIDRIVE® S III ARTHRO SCB 28 7230 20-1 and ENDOMAT® SELECT UP 210	
	20 0141 30	One-Pedal Footswitch , digital, one-stage, for irrigation	



Note:

Further information on additional software modules and accessories for ENDOMAT® SELECT is available in Product Highlight 96311003.



■ MOTOR SYSTEMS

UNIDRIVE® S III ARTHRO SCB

UNIDRIVE® S III ARTHRO SCB

The aim of all arthroscopic procedures is the same: To complete the procedure quickly and with minimal trauma, thereby reducing patient time under anesthesia.

With the UNIDRIVE® S III ARTHRO SCB, KARL STORZ has developed a motor system that is customized to meet these requirements.

- Easy to use
- Automatic handpiece recognition
- Control of rotation speed similar to the multifunctional handpiece
- Comprehensive portfolio of single-use and reusable blades
- Communication with ARTHROPUMP® Power



UNIDRIVE® S III ARTHRO SCB

Recommended Standard Set Configuration

Special Features:

- Arthroscopic motor system for all joints
- Stable torque throughout entire speed range
- Motors with speed of max. 8000 rpm
- Multifunctional handpiece with accessories:
 - Jacobs chucks
 - Pin drivers
 - Sagittal saws
 - Synthes-style drivers
- Various control options possible
 - Hand controls
 - Footswitch
 - Touch screen
- Fast and easy change of blade via quick coupling
- Single-use and reusable blades available
- Handle with detachable valve assembly for optimal reprocessing



28 7230 01-1 UNIDRIVE® S III ARTHRO SCB,
with color display, touch screen
operation, two motor outputs,
integrated SCB module, power supply
100 – 120/230 – 240 VAC, 50/60 Hz
including:
SCB Connecting Cable, length 100 cm
Mains Cord

Specifications:

Operating mode	- counter-clockwise - clockwise - oscillating	Power supply	100-120/230-240 VAC, 50/60 Hz
Connections	- DRILLCUT-X® ARTHRO handpiece - multifunction handpiece - footswitch - KARL STORZ-SCB	Dimensions w x h x d	305 x 165 x 280 mm
		Weight	5.2 kg
		Certified to	IEC 601-1, CE acc. to MDD

System requirements:

SCB control NEO System with installed SCB control NEO Software Release **20 0900 01-44** or higher

Components/Spare Parts see chapter 18

UNIDRIVE® S III ARTHRO SCB

Handpieces

Handpiece	KARL STORZ Quick Coupling	for use with Reusable Blades	Rotation (rpm)	Oscillation (rpm)	Connecting Cable (m)	Weight (kg)
28 721036 Multifunction Handpiece	●	-	0 to 1700	-	3.5	0.88
28200 DX DRILLCUT-X® ARTHRO Shaver Handpiece	●	●	1000 to 8000	500 to 3000	3.0	0.31



28200 DX

NEW 28200 DX **DRILLCUT-X® ARTHRO Shaver Handpiece**, up to 8000 rpm, for use with UNIDRIVE® S III ARTHRO SCB

Optional Accessories for UNIDRIVE® S III ARTHRO SCB Shaver Blades

28205 SAA **Irrigation Adaptor**, for validated cleaning of outer blades

28205 SAI **Irrigation Adaptor**, for validated cleaning of inner blades

Please note: The shaver handpieces should not be treated with universal spray.

Optional Accessories for UNIDRIVE® S III ARTHRO SCB see page U 21

Shaver Blades see pages U 22-27

UNIDRIVE® S III ARTHRO SCB

Handpieces



28 7210 36

28 7210 36 Multifunction Handpiece, for use with UNIDRIVE® S II ARTHRO SCB

Optional Accessories for Multifunction Handpiece 28 7210 36


- 28 7210 31 Jacobs Chuck**, up to diameter 4 mm
- 28 7210 37 Jacobs Chuck**, up to diameter 6.5 mm
- 28 7210 38 Jacobs Chuck**, keyless, up to diameter 7.4 mm, for use with Multifunction Handpiece **28 7210 36**
- 28 7210 39 Sagittal Saw Attachment**, keyless, with tilt lever, for use with Multifunction Handpiece **28 7210 36** and Saw Blades 28207 SLA – SLH
- 28 7210 33 Pin Driver**, for drilling wires diameter 1.5 – 3 mm
- 28 7210 34 Pin Driver**, for Synthes attachments
- 28 7210 71 Connecting Cable**, for FMS pump

Saw Blades for Sagittal Saw Attachment see page U 28

Drills see pages 84, 90, 91, 103, 149 and 152

UNIDRIVE® S III ARTHRO SCB

System Components




UNIT SIDE

PATIENT SIDE










MOTOR SYSTEMS



UNIDRIVE® S III ARTHRO SCB

Optional Accessories

For Multifunction Handpiece 28 7210 36

	28 7210 31	Jacobs Chuck , up to diameter 4 mm
	28 7210 37	Jacobs Chuck , up to diameter 6.5 mm
	28 7210 33	Pin Driver , for drilling wires diameter 1.5 – 3 mm
	28 7210 38	Jacobs Chuck , keyless, up to diameter 7.4 mm, for use with Multifunction Handpiece 28 7210 36
	28 7210 39	Sagittal Saw Attachment , keyless, with tilt lever, for use with Multifunction Handpiece 28 7210 36 and Saw Blades 28207 SLA – SLH
	28 7210 34	Pin Driver , for Synthes attachments
	28 7210 71	Connecting Cable , for FMS pump

For UNIDRIVE® S III ARTHRO SCB Shaver Blades

	28205 SAA	Irrigation Adaptor , for validated cleaning of outer blades
	28205 SAI	Irrigation Adaptor , for validated cleaning of inner blades


Shaver Blades

for use with UNIDRIVE® S III ARTHRO SCB
for cutting and grinding

Special Features:

- Shaver blades for single use and reusable blades
- Optimal cutting window for fast and efficient cutting as well as suction of tissue and bone
- Diameters ranging from 2.5 to 6.5 mm
- Working lengths ranging from 70 mm to 180 mm
- Shaver blades with up to 6 cutting edges
- Curved shaver blades
- Shaver blades with distal keyhole

Shaver Blades, for single use package of 6



28205 DKS

Shaver Blades, reusable single-packaged



28205 DD

For use with Shaver Handpiece 28200 DX DRILLCUT-X® ARTHRO in conjunction with UNIDRIVE® S III ARTHRO SCB







28200 DX


Shaver Blades

for use with UNIDRIVE® S III ARTHRO SCB
for cutting and grinding

Working length 180 mm (recommended for soft tissue)

Type	For single use package of 6 	Reusable single-packaged	Color Code
 Aggressive Cutter	28208 BKS diameter 4.5 mm	–	green
 Aggressive Full Radius Resector	28208 DCS diameter 4.5 mm	–	blue
 Curved Aggressive Full Radius Resector	28208 EHS diameter 4.5 mm	–	light green

Working length 180 mm (recommended for bone)







 Semi Hooded Barrel Burr	28208 IDS diameter 5.5 mm	–	pink
---	---------------------------------	---	------

Shaver Blades

for use with UNIDRIVE® S III ARTHRO SCB

for cutting and grinding






Working length 120 mm (recommended for soft tissue)

Type		For single use package of 6 		Reusable single-packaged		Color Code
	Aggressive Cutter	28205 ABS	Diameter 3.5 mm	28205 AB	Diameter 3.5 mm	green
		28205 ACS	Diameter 4.2 mm	28205 AC	Diameter 4.2 mm	
		28205 ADS	Diameter 5.5 mm	28205 AD	Diameter 5.5 mm	
	Aggressive Cutter	28205 AKS	Diameter 4.5 mm	28205 AK	Diameter 4.5 mm	green
	End Cutter	28205 BCS	Diameter 4.2 mm	28205 BC	Diameter 4.2 mm	red
	Full Radius Resector	28205 CBS	Diameter 3.5 mm	–	–	yellow
		28205 CCS	Diameter 4.2 mm	28205 CC	Diameter 4.2 mm	
		28205 CDS	Diameter 5.5 mm	–	–	
	Full Radius Resector	28205 CKS	Diameter 4.5 mm	28205 CK	Diameter 4.5 mm	yellow



Shaver Blades

for use with UNIDRIVE® S III ARTHRO SCB
for cutting and grinding

Working length 120 mm (recommended for soft tissue)

Type		For single use package of 6 		Reusable single-packaged		Color Code
	Aggressive Full Radius Resector	28205 DBS	Diameter 3.5 mm	28205 DB	Diameter 3.5 mm	blue
		28205 DCS	Diameter 4.2 mm	28205 DC	Diameter 4.2 mm	
		28205 DDS	Diameter 5.5 mm	28205 DD	Diameter 5.5 mm	
	Aggressive Full Radius Resector	28205 DKS	Diameter 4.5 mm	28205 DK	Diameter 4.5 mm	blue
	Curved Full Radius Resector	28205 EGS	Diameter 4.2 mm	–	–	light blue
	Curved Aggressive Full Radius Resector	28205 EHS	Diameter 4.2 mm	–	–	light green

Nutzlänge 120 mm (recommended for soft tissue and bone)

	Pro Line Shaver Blades	28205 MKS	Diameter 4.5 mm	28205 MK	Diameter 4.5 mm	pink
		28205 MDS	Diameter 5.5 mm	–	–	
	Aggressive Pro Line Shaver Blades	28205 NKS	Diameter 4.5 mm	28205 NK	Diameter 4.5 mm	light blue
		28205 NDS	Diameter 5.5 mm	–	–	

Shaver Blades

for use with UNIDRIVE® S III ARTHRO SCB
for cutting and grinding

Working length 120 mm (recommended for bone)

Type		For single use package of 6 		Reusable single-packaged		Color Code
	Round Burr	28205 FCS	Diameter 4.2 mm	28205 FC	Diameter 4.2 mm	orange
		28205 FDS	Diameter 5.5 mm	–	–	
	Finish Barrel Burr	28205 GDS	Diameter 4.2 mm	–	–	purple
		28205 GES	Diameter 5.5 mm	28205 GE	Diameter 5.5 mm	
	Aggressive Barrel Burr	28205 HCS	Diameter 4.2 mm	28205 HC	Diameter 4.2 mm	pink
		28205 HDS	Diameter 5.5 mm	28205 HD	Diameter 5.5 mm	
		28205 HES	Diameter 6.5 mm	28205 HE	Diameter 6.5 mm	

Shaver Blades

for use with UNIDRIVE® S III ARTHRO SCB
for cutting and grinding

Working length 70 mm (recommended for soft tissue)

Type		For single use package of 6 		Reusable single-packaged		Color Code
	Aggressive Cutter	28206 AAS	Diameter 2.5 mm	-	-	green
		28206 ABS	Diameter 3.5 mm	-	-	
	Full Radius Resector	28206 CAS	Diameter 2.5 mm	-	-	yellow
		28206 CBS	Diameter 3.5 mm	-	-	
	Aggressive Full Radius Resector	28206 DAS	Diameter 2.5 mm	28206 DA	Diameter 2.5 mm	blue
		28206 DBS	Diameter 3.5 mm	28206 DB	Diameter 3.5 mm	

Working length 70 mm (recommended for bone)

	Small Joint Burr	28206 FAS	Diameter 2.5 mm	-	-	orange
		28206 FBS	Diameter 3.5 mm	-	-	

Accessories

Saw Blades for use with Multifunction Handpiece 28 7210 36 in conjunction with UNIDRIVE® S III ARTHRO SCB



28207 SLA

28207 SLA

Saw Blade, blade width 10 mm, blade thickness 0.4 mm, cutting thickness 0.6 mm, working length 50 mm, unsterile, for single use



28207 SLB

28207 SLB

Same, blade width 14 mm



28207 SLC

28207 SLC

Saw Blade, blade width 10 mm, blade thickness 0.4 mm, cutting thickness 0.6 mm, with stopper at 15 mm, working length 25 mm, unsterile, for single use



28207 SLD

28207 SLD

Same, blade width 6 mm



28207 SLE

28207 SLE

Same, blade width 8 mm



28207 SLF

28207 SLF

Saw Blade, blade width 12 mm, blade thickness 0.4 mm, cutting thickness 0.6 mm, working length 22 mm, unsterile, for single use



28207 SLG

28207 SLG

Saw Blade, blade width 6 mm, blade thickness 0.4 mm, cutting thickness 0.6 mm, working length 31 mm, unsterile, for single use



28207 SLH

28207 SLH

Same, blade width 10 mm



■ HIGH FREQUENCY SURGERY UNITS

NEW AUTOCON® III 400

AUTOCON® III 400 High-End ^{NEW}

High Frequency Surgery Unit

The high-end HF unit from KARL STORZ provides the highest level of user comfort and ease of use. The 9" color touch displays procedures for all areas of application according to the needs of the user.

A footswitch allows settings to be changed during surgery directly from the sterile area. Alternatively, two sockets with separate instruments can be controlled via a footswitch.

The maximum power of 400 Watt (unipolar and bipolar) is precisely regulated by a generator. Only the amount of energy required for the desired tissue effect is emitted. Consequently, this unit delivers the best possible performance combined with the highest patient safety.

Benefits at a glance:

- Extremely easy handling thanks to 9" color touch screen
- Predefined procedures for each speciality
- For interdisciplinary use
- 400 W unipolar and bipolar performance
- Neutral electrode monitoring for highest patient safety
- Automatic smoke evacuation with the S-PILOT™ from KARL STORZ
- Best hygiene conditions thanks to smooth surface
- Can be integrated into the KARL STORZ OR1™



AUTOCON® III 400 High-End ^{NEW}

High Frequency Surgery Unit,
Recommended Standard Set Configuration

STORZ
KARL STORZ — ENDOSKOPE



UH 400

AUTOCON® III 400 High-End, power supply 220 – 240 VAC, 50/60 Hz including:

Mains Cord

HF connecting sockets unipolar:

2x 3-pin US type
5 mm connector KARL STORZ/Erbe VIO
2x 4 mm connector (via footswitch)
BOVIE (via footswitch)

bipolar:

2x 2-pin US type (28.58)
3x KARL STORZ/Erbe VIO
neutral electrode 2-pol.

System requirements:

SCB R-UI Software
Release 20090001-46 or higher
Can be integrated into OR1™ with KARL STORZ-SCB control NEO.

UH 400U

Same, power supply 100 – 127 VAC, 50/60 Hz

Specifications:

Max. power	unipolar: 400 Watt (at 200 Ohm) bipolar: 400 Watt (at 75 Ohm)
Power supply	230 VAC, 50/60 Hz (UH 400) 110 VAC, 50/60 Hz (UH 400U)
Weight	12.5 kg
Sockets	Unipolar sockets: 2 Bipolar sockets: 2 (can be expanded to 3)


Output frequency	350 kHz/1 MHz
Dimensions w x h x d	447 x 177 x 457 mm
Certified to	IEC 601-1, CE acc. to MDD.



Optional Accessories for AUTOCON® III 400 High-End see pages U 34-36
Components/Spare Parts see chapter 18

AUTOCON® III 400 High-End ^{NEW}

System Components




HIGH FREQUENCY SURGERY UNITS

7-16

AUTOCON® III 400 High-End





Optional Accessories

Footswitches

	UF 901	One-Pedal Footswitch , with button for switchover function, for use with HF generators
	UF 902	Two-Pedal Footswitch , with button for switchover function, for use with HF generators

Neutral Electrodes



	27805	Neutral Electrode , of conductive silicone with 2 rubber ties for fastening, contact surface A = 500 cm ² , for use with Connecting Cable 27806
	27806 UR	Neutral Electrode Connecting Cable , for Neutral Electrode 27805
	27806 US	Neutral Electrode Connecting Cable , for Neutral Electrode 27802
	27802	Neutral Electrode , for single use, contact surface divided into two, A = 169 cm ² , package of 50, Connecting Cable 27801 required






AUTOCON® III 400 High-End







Optional Accessories



HF Instruments unipolar – Electrodes

	26 5200 45	High Frequency Cable , for Electrode Handle 26 5200 43 , length 400 cm
	26 5200 43	Electrode Handle , with 2 buttons for activating the unipolar generator, yellow button: unipolar cutting, blue button: unipolar coagulation (Cable 26 5200 45 required)
	26 5200 46	Electrode Handle , without buttons, with integrated connecting cable, length 300 cm


For use with

	28801 EA	Arthroscopy HF Ball Electrode , diameter 2.6 mm, ball diameter 2.5 mm, working length 6 cm, sterile, for single use, package of 5	STERILE 
	28801 EB	Same , working length 11 cm	
	28801 EC	Arthroscopy HF Ball Electrode , diameter 2.6 mm, ball diameter 3.5 mm, working length 6 cm, sterile, for single use, package of 5	STERILE 
	28801 ED	Same , working length 11 cm	
	28801 EF	Arthroscopy HF Hook Electrode , diameter 2.6 mm, electrode length 2.8 mm, working length 6 cm, sterile, for single use, package of 5	
	28801 EG	Same , working length 11 cm	STERILE 
	28801 EH	Arthroscopy HF Hook Electrode , diameter 2.6 mm, electrode length 4 mm, working length 11 cm, sterile, for single use, package of 5	

AUTOCON® III 400 High-End

Optional Accessories

HF Instruments bipolar – Forceps



26176 LE

Bipolar High Frequency Cord, length 300 cm, for AUTOCON® II 400 SCB system (111, 113, 115, 122, 125), AUTOCON® II 200, AUTOCON® II 80, Coagulator 26021 B/C/D, 860021 B/C/D, 27810 B/C/D, 28810 B/C/D, AUTOCON® series (50, 200, 350), Erbe-Coagulator, T and ICC series

For use with



38851 MD

ROBI® KELLY Grasping Forceps, CLERMONT-FERRAND model, rotating, dismantling, with connector pin for bipolar coagulation, especially suitable for dissection, double action jaws, size 3.5 mm, length 20 cm, color code: light blue

**COMPONENTS /
SPARE PARTS**






The chapter “Components / Spare Parts” contains detailed information on KARL STORZ instruments.

For easy location and reference, an index is available which lists the order number of the spare parts as well as those of the entire instrument, set or unit.

Hotline

Queries concerning products, exchange, maintenance and cleaning can be addressed to Technical Support: 07461/708-980, from Monday to Thursday from 7-18 h and Friday from 7-17 h.

Example:

Components / Spare Parts		Catalog page
11508	Miniature Straight Forward Telescope 0°	183
		
Spare Parts		
	495 F Receptacle, diameter 9 mm, for Wolf fiber optic light cable	
		495 G Screw Base, for KARL STORZ fiber optic light cable and Olympus/Winter & Ibe

Components/spare parts with corresponding order number of the instrument and reference to catalog page

Table of Contents

COMPONENTS / SPARE PARTS

HOPKINS® TELESCOPES AND SHEATHS

ENDOCAMELEON® ARTHRO HOPKINS® Telescope	SP 4
Arthroscope Sheath ENDOCAMELEON®	SP 4
Miniature Straight Forward Telescope	SP 5
HOPKINS® Telescopes	SP 5
Arthroscope Sheaths, with standard coupling mechanism, fixed stopcocks	SP 6
Arthroscope Sheaths, with standard coupling mechanism, rotating stopcocks	SP 7-8
Arthroscope Sheath, with lock-in coupling mechanism, rotating stopcocks	SP 9
Arthroscope Sheaths, with snap-in coupling mechanism, fixed and rotating stopcocks	SP 10
Arthroscope Sheaths, with snap-in coupling mechanism, rotating stopcocks	SP 11
Arthroscope Sheaths, Accessories	SP 12

HOSPITAL INSTRUMENTS

Cannulas	SP 13
----------	-------

PUNCHES, FORCEPS AND SCISSORS

SILCUT® PRO and SILCUT® Punches	SP 14
SILGRASP® PRO and SILGRASP® Grasping Forceps	SP 15
RETROFORCE® Biopsy Punch	SP 15

JOINT AND BONE RECONSTRUCTION

Biopsy Set	SP 16
Obturator	SP 16
Cancellous Bone Applicators	SP 16-17

INSTRUMENTS FOR THE KNEE

Tendon Boards	SP 18
Metal Mallets	SP 18
Target Guides	SP 19-20
Dilators with Fin	SP 21
CROSSDRIVE® Screwdrivers	SP 21

INSTRUMENTS FOR THE SHOULDER

Seal Set, Handle, Transport Cassette	SP 22
SNAPPER® SHOULDER PRO® Suture Forceps	SP 22
SHOULDER PRO® Suture Forceps Attachments	SP 23
Knot Pusher and Suture Cutter	SP 23
SILCUT® Punches	SP 23
SILGRASP® Foreign Body Graspers and Suture Graspers	SP 23
SHOULDER PRO® Suture Forceps	SP 24
Mallets	SP 24

INSTRUMENTS FOR THE HIP

Evacuation Cannula	SP 25
SILCUT® Punches	SP 25
SILGRASP® Foreign Body Graspers	SP 25
SILGRASP® Suture Graspers	SP 25
Suture Forceps	SP 25

INSTRUMENTS FOR SMALL AND MEDIUM JOINTS

SILCUT® PRO Punches	SP 26
SILGRASP® PRO Grasping Forceps	SP 26
Dilator Set	SP 27
Optical Dissectors	SP 27
ROBI® KELLY Grasping Forceps	SP 27

RHEUMATOLOGY

Holding System	SP 28
----------------	-------

VISUALIZATION SYSTEMS FOR OPEN SURGERY AND MICROSURGERY

VITOM® Telescopes	SP 29
Rotation Socket, Articulated Stand	SP 29
VERSACRANE™ Holding System, 32" 3D Monitor	SP 30

HOLDING SYSTEMS

Leg Holder	SP 31
------------	-------

UNITS AND ACCESSORIES

Suction and Irrigation Systems

ARTHROPUMP® Power	SP 32
ENDOMAT® SELECT	SP 33

Motor System

UNIDRIVE® S III ARTHRO SCB	SP 34
----------------------------	-------

High Frequency Surgery Unit

AUTOCON® III 400 High-End	SP 35
---------------------------	-------

Numerical Index

COMPONENTS / SPARE PARTS

Product	Page	Product	Page	Product	Page
030647-10	SP 33	28171 CBN	SP 14	28184 RG	SP 22
031228-03	SP 32	28171 CCN	SP 14	28184 RK	SP 22
031328-03	SP 32	28171 DBN	SP 14	28184 WH	SP 22
031523-10	SP 33	28171 DCN	SP 14	28188 D	SP 31
031524-10	SP 33	28171 EBN	SP 14	28188 DP	SP 31
031529-10	SP 33	28171 ECN	SP 14	28188 FH	SP 31
031647-10	SP 33	28171 FBN	SP 14	28188 FK	SP 31
1059700	SP 34	28171 FCN	SP 14	28188 FS	SP 31
1069500	SP 32	28171 GBN	SP 14	28188 HR	SP 31
11508	SP 5	28171 GCN	SP 14	28188 PN	SP 31
1222890	SP 35	28171 HAN	SP 15	28188 SE	SP 31
1432095	SP 35	28171 HBN	SP 15	28200 DA	SP 34
174701	SP 24	28171 HCN	SP 15	28200 DB	SP 34
174800	SP 18	28171 KBN	SP 15	28200 DX	SP 34
174801	SP 18	28171 KGN	SP 15, SP 23, SP 25	28208 BA	SP 5
20016834	SP 32	28171 KGSN	SP 15, SP 23, SP 25	28229 DR	SP 7
20090170	SP 32, SP 34	28171 KPN	SP 14, SP 23, SP 25	28270 H	SP 24
2027690	SP 34	28171 KUN	SP 14, SP 23, SP 25	28272 HA	SP 28
20916025 AA	SP 29	28171 OAN	SP 14	28272 HB	SP 29
20916025 AGA	SP 29	28171 OUN	SP 14	28272 HC	SP 29
20916025 DA	SP 29	28171 PGN	SP 15	28272 HP	SP 30
28126 B	SP 6	28171 PGSN	SP 15	28272 HS	SP 30
28126 CR	SP 7	28171 SBN	SP 14	28272 HSP	SP 30
28126 R	SP 7	28171 SGD	SP 25	28272 KLA	SP 28
28129 CR	SP 9	28171 SGL	SP 15, SP 23	28272 UL	SP 28
28130 CR	SP 11	28171 SGN	SP 15, SP 23	28300 BA	SP 5
28130 R	SP 10	28171 SGR	SP 15, SP 23	28303 BS	SP 10
28131 CR	SP 11	28171 SHN	SP 23	28303 DS	SP 12
28131 R	SP 10	28171 SLN	SP 14	28305 BA	SP 5
28132 CR	SP 8	28171 SPN	SP 14	28306 BN	SP 6
28133 DS	SP 12	28171 SRN	SP 14	28340701-1	SP 32
28135 CR	SP 11	28172 HK	SP 28	28340720-1	SP 32
28136 CR	SP 11	28172 HR	SP 29, SP 31	28340770	SP 32
28136 DS	SP 11	28172 HRS	SP 29, SP 31	28571 AB	SP 14
28136 EC	SP 4	28172 HZ	SP 28, SP 29	28571 AC	SP 14
28136 S	SP 10	28180 GD	SP 22	28571 AG	SP 15
28140 D	SP 12	28180 GAN	SP 22	28571 BB	SP 14
28140 GA	SP 25	28180 GCN	SP 22	28571 BBL	SP 14
28140 S	SP 25	28180 GDS	SP 22	28571 BBR	SP 14
28146 T	SP 13	28180 GLN	SP 22	28571 BC	SP 14
28146 TT	SP 13	28180 GRN	SP 22	28571 CG	SP 15
28147 S	SP 27	28180 GRGN	SP 22	28571 CGU	SP 15
28147 SA	SP 27	28180 GFN	SP 24	28571 CL	SP 14
28147 SB	SP 27	28180 HC	SP 24	28571 CLU	SP 14
28147 SC	SP 27	28180 HL	SP 24	28571 CR	SP 14
28147 SD	SP 27	28180 HR	SP 24	28571 CRU	SP 14
28171 ABN	SP 14	28180 LA	SP 23	28571 E	SP 14
28171 ACN	SP 14	28180 LC	SP 23	28571 EU	SP 14
28171 ADN	SP 14	28180 LL	SP 23	28571 FG	SP 15
28171 AGN	SP 15	28180 LR	SP 23	28571 G	SP 15
28171 AGSN	SP 15	28180 LRG	SP 23	28571 GU	SP 15
28171 BBN	SP 14	28184 HG	SP 22	28571 LK	SP 14, SP 15, SP 22, SP 23, SP 24, SP 25, SP 26
28171 BCN	SP 14	28184 HS	SP 22	28571 O	SP 14, SP 26
28171 BDN	SP 14	28184 KF	SP 22		

Numerical Index

COMPONENTS / SPARE PARTS

Product	Page	Product	Page	Product	Page
28571 OA	SP 14	28789 CD	SP 21	6052191	SP 6, SP 27
28571 OAC	SP 14	28789 SK	SP 21	6104291	SP 6, SP 7
28571 OC	SP 14	28902 HG	SP 15	6104391	SP 8
28571 ODC	SP 14	28902 RF	SP 15	6829991	SP 19
28571 S	SP 14	28902 RFA	SP 15	6833091	SP 18
28571 SP	SP 14	28902 RFI	SP 15	6833191	SP 18
28571 SU	SP 14	28904 S	SP 16	6833291	SP 18
28572 AD	SP 14, SP 26	28904 SA	SP 16	6985691	SP 4, SP 6, SP 7, SP 8, SP 9, SP 10, SP 11, SP 12, SP 13, SP 25, SP 27
28572 ADL	SP 14, SP 26	28904 SO	SP 16	6988891	SP 7, SP 9
28572 ADR	SP 14, SP 26	28906 CB	SP 16	6995291	SP 7
28572 AE	SP 14, SP 26	28906 CBA	SP 16	7701691	SP 12
28572 AG	SP 15, SP 26	28906 CBC	SP 16	7725891	SP 10
28572 CG	SP 15, SP 26	28906 CBP	SP 16	7725991	SP 8, SP 11
28572 CGU	SP 15, SP 26	28906 CBS	SP 16	7957291	SP 4, SP 11
28572 G	SP 15, SP 26	28907 CB	SP 16	7957391	SP 12
28572 GU	SP 15, SP 26	28907 CBA	SP 16	7971891	SP 18
28572 NJ	SP 15, SP 26	28907 CBC	SP 16	8029491	SP 14, SP 15, SP 22, SP 23, SP 24, SP 25, SP 26
28572 O	SP 14	28907 CBP	SP 16	8044890	SP 18
28573 FD	SP 15, SP 23, SP 25	28907 CBS	SP 16	8064391	SP 20
2870356 HG	SP 23	28908 CB	SP 17	8069491	SP 10, SP 27
2870356 I	SP 23	28908 CBA	SP 17	8105491	SP 20
2870356 KP	SP 23	28908 CBC	SP 17	8458190	SP 4, SP 6, SP 7, SP 8, SP 9, SP 10, SP 11, SP 13, SP 27
28719 BA	SP 5	28908 CBP	SP 17	8484290	SP 4, SP 7, SP 8, SP 9, SP 10, SP 11, SP 27
28723001-1	SP 34	28908 CBS	SP 17	8515090	SP 6, SP 10, SP 12
28723020-1	SP 34	28909 CB	SP 17	8541890	SP 13, SP 25
28729 CF	SP 20	28909 CBA	SP 17	9020490	SP 12
28729 DFM	SP 21	28909 CBC	SP 17	96156013D	SP 34
28729 DFO	SP 21	28909 CBP	SP 17	9800 GF	SP 30
28729 DFP	SP 21	28909 CBS	SP 17	9826 PS	SP 30
28729 DFQ	SP 21	28910 CB	SP 17	ET52-022869	SP 30
28729 DFR	SP 21	28910 CBA	SP 17	ET52-202868	SP 30
28729 DFS	SP 21	28910 CBC	SP 17	ET52-202877	SP 30
28729 DFT	SP 21	28910 CBP	SP 17	ET52-202878	SP 30
28729 DFU	SP 21	28910 CBS	SP 17	ET52-202880	SP 30
28729 DFV	SP 21	29100	SP 23, SP 27	ET52-202881	SP 30
28729 SB	SP 18	38151	SP 27	ET52-4-6-25-00176	SP 30
28729 SBD	SP 18	38810 MD	SP 27	ET52-4-6-25-00183	SP 30
28729 SC	SP 18	38851 MD	SP 27	ET52-4-6-25-00184	SP 30
28729 WT	SP 19	39107 Z	SP 19, SP 20, SP 21	ET52-4-6-25-00206	SP 30
28729 ZA	SP 19	400 A	SP 30, SP 33, SP 34, SP 35	TM 323	SP 30
28729 ZB	SP 19	400 B	SP 35	UH 400	SP 35
28729 ZBB	SP 20	495 F	SP 4, SP 5, SP 29	UH 400U	SP 35
28729 ZF	SP 20	495 G	SP 4, SP 5, SP 29	UP 007	SP 33
28729 ZFH	SP 20	50200 ES	SP 27	UP 008	SP 33
28729 ZL	SP 19	50300 ES	SP 27	UP 009	SP 33
28729 ZR	SP 19	5900800	SP 12	UP 010	SP 33
28729 ZRF	SP 19	5916000-10	SP 16	UP 210	SP 33
28731 AE	SP 4	5916100	SP 4, SP 7, SP 8, SP 9, SP 10, SP 11, SP 27		
28731 AWA	SP 5	5917100-10	SP 16		
28731 BVA	SP 5	5919000-10	SP 16		
28731 BWA	SP 5	5941400-10	SP 17		
28731 CWA	SP 5	5941500-10	SP 17		
28760 SK	SP 21	5941600-10	SP 17		
28770 SK	SP 21				

HOPKINS® Telescopes and Sheaths

ENDOCAMELEON® ARTHRO HOPKINS® Telescope

Arthroscope Sheath ENDOCAMELEON®

Components / Spare Parts

Catalog page

28731 AE

ENDOCAMELEON® ARTHRO HOPKINS® Telescope

29



Spare Parts



495 F
Receptacle,
diameter 9 mm, for
Wolf fiber optic light cable



495 G
Screw Base, for
KARL STORZ fiber optic
light cables and Olympus
Corporation


Components / Spare Parts

Catalog page

28136 EC

Arthroscope Sheath ENDOCAMELEON®

29



Spare Parts



7957291
Outer Part,
with 2 stopcocks



8458190
Stopcock



5916100
O-Ring



8484290
Nut



6985691
Spring Cap

HOPKINS® Telescopes and Sheaths


Miniature-Straight Forward Telescope, HOPKINS® Telescopes

Components / Spare Parts

Catalog page

11508 Miniature Straight Forward Telescope 0°

183



Spare Parts



495 F
Receptacle,
diameter 9 mm, for
Wolf fiber optic light cable




495 G
Screw Base, for
KARL STORZ fiber optic
light cables and Olympus
Corporation

Components / Spare Parts

Catalog page

28305 BA	HOPKINS® Forward-Oblique Telescope 30°	41, 165
28300 BA	HOPKINS® Wide Angle Forward-Oblique Telescope 30°	40, 166
28719 BA	HOPKINS® Forward-Oblique Telescope 30°	38
28208 BA	HOPKINS® Forward-Oblique Telescope 30°	39, 167
28731 AWA	HOPKINS® Wide Angle Straight Forward Telescope 0°, enlarged view	31
28731 BWA	HOPKINS® Wide Angle Forward-Oblique Telescope 30°, enlarged view	31, 177
28731 CWA	HOPKINS® Wide Angle Lateral Telescope 70°, enlarged view	31
28731 BVA	HOPKINS® Wide Angle Forward-Oblique Telescope 30°, enlarged view	174



Spare Parts



495 F
Receptacle,
diameter 9 mm, for
Wolf fiber optic light cable



495 G
Screw Base, for
KARL STORZ fiber optic
light cables and Olympus
Corporation

HOPKINS® Telescopes and Sheaths


Arthroscope Sheaths, with standard coupling mechanism, fixed stopcocks

Components / Spare Parts

Catalog page

28306 BN High-Flow Arthroscope Sheath

41, 165



Spare Parts



6052191
Locking Lever, red



8515090
Stopcock




6985691
Spring Cap

Components / Spare Parts

Catalog page

28126 B Arthroscope Sheath

32



Spare Parts



6104291
Locking Lever, green-red-yellow



8458190
Stopcock



6985691
Spring Cap

HOPKINS® Telescopes and Sheaths


Arthroscope Sheaths, with standard coupling mechanism, rotating stopcocks

Components / Spare Parts

Catalog page

28126 R Arthroscope Sheath

33



Spare Parts



5916100
O-Ring



6995291
Outer Part, with stopcock



6104291
Locking Lever,
green-red-yellow



8458190
Stopcock



6985691
Spring Cap



8484290
Nut

Components / Spare Parts


Catalog page

28229 DR High-Flow Arthroscope Sheath

32

28126 CR Arthroscope Sheath

33



Spare Parts



5916100
O-Ring



6988891
Outer Part,
with 2 stopcocks



6104291
Locking Lever,
green-red-yellow



8458190
Stopcock



6985691
Spring Cap



8484290
Nut

HOPKINS® Telescopes and Sheaths


Arthroscope Sheaths, with standard coupling mechanism, rotating stopcocks

Components / Spare Parts

Catalog page

28132 CR Arthroscope Sheath

38



Spare Parts



5916100
O-Ring



7725991
Outer Part,
with 2 stopcocks



6104391
Locking Lever, red-yellow



8458190
Stopcock



6985691
Spring Cap



8484290
Nut

HOPKINS® Telescopes and Sheaths


Arthroscope Sheath, with lock-in coupling mechanism, rotating stopcocks

Components / Spare Parts

Catalog page

28129 CR STROBEL Arthroscope Sheath

36



Spare Parts



5916100
O-Ring



8458190
Stopcock



6985691
Spring Cap



8484290
Nut



6988891
Outer Part,
with 2 stopcocks

HOPKINS® Telescopes and Sheaths

Arthroscope Sheaths, with snap-in coupling mechanism
fixed and rotating stopcocks

Components / Spare Parts


Catalog page

28303 BS High-Flow Arthroscope Sheath

8515090

40, 166

6985691



Spare Parts



6985691
Spring Cap



8515090
Stopcock

Components / Spare Parts

Catalog page

28136 S High-Flow Arthroscope Sheath

34

28130 R High-Flow Arthroscope Sheath

34

28131 R High-Flow Arthroscope Sheath


35

8069491

7725891

8484290

8458190



Spare Parts



5916100
O-Ring

Spare part for 28130 R and 28131 R:



8458190
Stopcock



6985691
Spring Cap

Spare part for 28136 S:



8069491
Outer Part, with stopcock



8484290
Nut

Spare part for 28130 R and 28131 R:



7725891
Outer Part, with stopcock


HOPKINS® Telescopes and Sheaths

Arthroscope Sheaths, with snap-in coupling mechanism, rotating stopcocks

Components / Spare Parts

Catalog page

28136 DS	High-Flow Arthroscope Sheath	34
28130 CR	High-Flow Arthroscope Sheath	34
28131 CR	High-Flow Arthroscope Sheath	35
28136 CR	High-Flow Arthroscope Sheath	34
28135 CR	High-Flow Arthroscope Sheath	35



Spare Parts



5916100
O-Ring



6985691
Spring Cap



8484290
Nut

Spare part for 28130 CR and 28131 CR:



8458190
Stopcock

Spare part for 28136 DS/CR and 28135 CR:



7957291
Outer Part,
with 2 stopcocks

Spare part for 28130 CR and 28131 CR:



7725991
Outer Part,
with 2 stopcocks

HOPKINS® Telescopes and Sheaths


Arthroscope Sheaths, Accessories

Components / Spare Parts

Catalog page

- 28133 DS** **Arthroscope Sheath**
- 28303 DS** **High-Flow Arthroscope Sheath**

39, 167
40, 166



Spare Parts



5900800
O-Ring



8515090
Stopcock



6985691
Spring Cap



9020490
Knurled Ring



7957391
Outer Part,
with 2 stopcocks

Components / Spare Parts

Catalog page

- 28140 D** **Gasket Attachment**

161



Spare Part



7701691
Swivel Nut

Components / Spare Parts

Catalog page

28146 T Cannula, for irrigation

52

28146 TT Cannula, for irrigation

52



Spare Parts



6985691
Spring Cap

Spare part for 28146 TT:



8541890
Stopcock

Spare part for 28146 T:



8458190
Stopcock


Punches, Forceps and Scissors

SILCUT® PRO and SILCUT® Punches

Components / Spare Parts

Catalog page

28571 AB	SILCUT® PRO Punch	56
28571 BB	SILCUT® PRO Punch	56
28571 BBL	SILCUT® PRO Upbiter	56
28571 BBR	SILCUT® PRO Upbiter	56
28571 AC	SILCUT® PRO Punch	56
28571 BC	SILCUT® PRO Punch	56
28572 AD	SILCUT® PRO Punch	57
28572 ADL	SILCUT® PRO Punch	57
28572 ADR	SILCUT® PRO Punch	57
28572 AE	SILCUT® PRO Punch	57
28571 O	SILCUT® PRO Oval Biter	57
28571 OA	SILCUT® PRO Oval Upbiter	57
28572 O	SILCUT® PRO Oval Biter	57
28571 OC	SILCUT® PRO Oval Biter	57
28571 OAC	SILCUT® PRO Oval Upbiter	57
28571 ODC	SILCUT® PRO Oval Downbiter	57
28571 E	SILCUT® PRO Giga Punch	58
28571 EU	SILCUT® PRO Giga Punch	58
28571 S	SILCUT® PRO Square Punch	58
28571 SU	SILCUT® PRO Square Punch	58
28571 CL	SILCUT® PRO Side Punch	58
28571 CLU	SILCUT® PRO Side Punch	58
28571 CR	SILCUT® PRO Side Punch	58
28571 CRU	SILCUT® PRO Side Punch	58
28571 SP	SILCUT® PRO Scissors	58
28171 KPN	SILCUT® Punch	59
28171 KUN	SILCUT® Punch	59
28171 ABN	SILCUT® Punch	59
28171 BBN	SILCUT® Punch	59
28171 CBN	SILCUT® Punch	59
28171 DBN	SILCUT® Punch	59
28171 EBN	SILCUT® Punch	59
28171 FBN	SILCUT® Punch	59
28171 GBN	SILCUT® Punch	59
28171 ACN	SILCUT® Punch	60
28171 BCN	SILCUT® Punch	60
28171 CCN	SILCUT® Punch	60
28171 DCN	SILCUT® Punch	60
28171 ECN	SILCUT® Punch	60
28171 FCN	SILCUT® Punch	60
28171 GCN	SILCUT® Punch	60
28171 ADN	SILCUT® Punch	60
28171 BDN	SILCUT® Punch	60
28171 SPN	SILCUT® Punch	60
28171 SLN	SILCUT® Punch	60
28171 SRN	SILCUT® Punch	60
28171 OAN	SILCUT® Oval Upbiter	61
28171 OUN	SILCUT® Oval Upbiter	61
28171 SBN	SILCUT® Backbiter	61



Spare Parts



28571 LK
Set of LUER Caps,
silicone, reusable,
unsterile, package of 10



8029491
LUER Cap, metal,
reusable, unsterile

Punches, Forceps and Scissors

SILGRASP® PRO and SILGRASP® Grasping Forceps
RETROFORCE® Biopsy Forceps

Components / Spare Parts

Catalog page

28572 NJ	SILGRASP® PRO Suture Grasper	64
28572 CG	SILGRASP® PRO Cartilage Grasping Forceps	64
28572 CGU	SILGRASP® PRO Cartilage Grasping Forceps	64
28572 G	SILGRASP® PRO Grasping Forceps	64
28572 GU	SILGRASP® PRO Grasping Forceps	64
28572 AG	SILGRASP® PRO Alligator Grasping Forceps	64
28571 FG	SILGRASP® PRO Foreign Body Grasper	65
28571 CG	SILGRASP® PRO Cartilage Grasping Forceps	65
28571 CGU	SILGRASP® PRO Cartilage Grasping Forceps	65
28571 G	SILGRASP® PRO Grasping Forceps	65
28571 GU	SILGRASP® PRO Grasping Forceps	65
28571 AG	SILGRASP® PRO Alligator Grasping Forceps	65
28171 HAN	SILGRASP® Grasping Forceps	66
28171 HBN	SILGRASP® Grasping Forceps	66
28171 HCN	SILGRASP® Grasping Forceps	66
28171 KBN	SILGRASP® Grasping Forceps	66
28171 AGN	SILGRASP® Alligator Grasping Forceps	66
28171 AGSN	SILGRASP® Alligator Grasping Forceps	66
28171 PGN	SILGRASP® Foreign Body Grasper	67
28171 PGSN	SILGRASP® Foreign Body Grasper	67
28171 SGN	SILGRASP® Suture Grasper	67, 85
28171 SGL	SILGRASP® Suture Grasper	67
28171 SGR	SILGRASP® Suture Grasper	67
28171 KGN	SILGRASP® Foreign Body Grasper	67
28171 KGSN	SILGRASP® Foreign Body Grasper	67
28573 FD	SILGRASP® Foreign Body Grasper	67



Spare Parts



28571 LK
Set of LUER Caps,
silicone, reusable,
unsterile, package of 10




8029491
LUER Cap, metal,
reusable, unsterile

Components / Spare Parts

Catalog page

28902 RF	RETROFORCE® Biopsy Punch	71, 185
28902 RFA	Outer Sheath, with LUER-Lock connector	
28902 RFI	Inner Sheath, with retrograde cutting punch	
28902 HG	Handle, without ratchet	



Joint and Bone Reconstruction

Biopsy Set, Obturator, Cancellous Bone Applicators

Components / Spare Parts

Catalog page

28904 S Biopsy Set

75

28904 SA **Biopsy Punch**, with cutting tooth, to extract cartilage cells for ACT

28904 SO **Obturator**, to penetrate connective tissue without extracting tissue and to extrude excised biopsy sample

5919000-10 **O-Ring**, package of 10



Components / Spare Parts

Catalog page

28904 SO Obturator

75

Spare Part



5919000-10
O-Ring



Components / Spare Parts

Catalog page

28906 CB Cancellous Bone Applicator Set, diameter 6 mm


79, 109

28906 CBA **Cancellous Bone Applicator**

28906 CBP **Tappet**

28906 CBC **Sealing Cap**

28906 CBS **Plug**



Spare Part



5917100-10
O-Ring

Components / Spare Parts

Catalog page

28907 CB Cancellous Bone Applicator Set, diameter 7 mm

79, 109

28907 CBA **Cancellous Bone Applicator**

28907 CBP **Tappet**

28907 CBC **Sealing Cap**

28907 CBS **Plug**

Spare Part



5916000-10
O-Ring

Joint and Bone Reconstruction

Cancellous Bone Applicators

Components / Spare Parts

Catalog page

28908 CB Cancellous Bone Applicator Set, diameter 8 mm

79, 109

28908 CBA Cancellous Bone Applicator

28908 CBP Tappet

28908 CBC Sealing Cap

28908 CBS Plug

Spare Part



5941400-10
O-Ring

Components / Spare Parts

Catalog page

28909 CB Cancellous Bone Applicator Set, diameter 9 mm

79, 109

28909 CBA Cancellous Bone Applicator

28909 CBP Tappet

28909 CBC Sealing Cap

28909 CBS Plug

Spare Part



5941500-10
O-Ring

Components / Spare Parts

Catalog page

28910 CB Cancellous Bone Applicator Set, diameter 10 mm

79, 109

28910 CBA Cancellous Bone Applicator

28910 CBP Tappet

28910 CBC Sealing Cap

28910 CBS Plug

Spare Part



5941600-10
O-Ring

Instruments for the Knee


Tendon Boards, Metal Mallet

Components / Spare Parts

Catalog page

- 28729 SB** **Tendon Board**
- 28729 SBD** **Tendon Board Add-on**

83
95



Spare Parts



28729 SC
FLIPPTACK Retainer



6833291
Measuring Slider



6833091
Clamp



7971891
Tendon Board, without
preparation plate



6833191
Tension Slider




8044890
Preparation Plate

Components / Spare Parts

Catalog page

- 174800** **Metal Mallet**

97



Spare Part



174801
Plastic Replacement

Instruments for the Knee


Target Guides

Components / Spare Parts

Catalog page

28729 ZRF Target Guide Root Refixation

88



Spare Parts



6829991
Sliding Tube



39107 Z
Cleaning Adaptor

Components / Spare Parts

Catalog page

28729 ZA Tibial Target Guide, for ACL reconstruction

94

28729 WT Tibial Target Guide, for ACL reconstruction

95

28729 ZB Tibial Target Guide, for PCL reconstruction


102

28729 ZL Tibial Target Guide, for PCL reconstruction


102

28729 ZR Tibial Target Guide, for PCL reconstruction

102



Spare Parts



6829991
Sliding Tube



39107 Z
Cleaning Adaptor

Instruments for the Knee


Target Guides

Components / Spare Parts


Catalog page

28729 CF Tibial Target Guide

98



Spare Parts





Components / Spare Parts

Catalog page

28729 ZF CHANNEL-LOCK® Tibial Target Guide

100

Spare Part



Components / Spare Parts


Catalog page

28729 ZBB Tibial Target Guide, for PCL reconstruction

102



Spare Parts



Instruments for the Knee

Dilators with Fin, CROSSDRIVE® Screwdrivers

Components / Spare Parts		Catalog page
28729 DFM	Dilator with Fin	110
28729 DFO	Dilator with Fin	110
28729 DFP	Dilator with Fin	110
28729 DFQ	Dilator with Fin	110
28729 DFR	Dilator with Fin	110
28729 DFS	Dilator with Fin	110
28729 DFT	Dilator with Fin	110
28729 DFU	Dilator with Fin	110
28729 DFV	Dilator with Fin	110



Spare Part



39107 Z
Cleaning Adaptor

Components / Spare Parts		Catalog page
28789 SK	CROSSDRIVE® Screwdriver	122
28770 SK	CROSSDRIVE® Screwdriver	122
28760 SK	CROSSDRIVE® Screwdriver	122
28789 CD	CROSSDRIVE® Plus Screwdriver	122



Spare Part



39107 Z
Cleaning Adaptor

Instruments for the Shoulder

Seal Set, Handle, Transport Cassette,
SNAPPER® SHOULDER PRO® Suture Forceps

Components / Spare Parts

Catalog page

28180 GDS Seal Set, package of 5

129



Spare Part



28180 GD Gasket, non-sterile, for single use, with sealing cap

Components / Spare Parts

Catalog page

28184 WH WONDERHOOK® Handle

138

28184 HG WONDERHOOK® Handle

28184 KF Transport Cassette



28184 WH



28184 HG



28184 KF

Components / Spare Parts

Catalog page

28184 KF Transport Cassette

138

28184 HS Half-shell Set

28184 RG Wheel, large

28184 RK Wheel, small



28184 KF



28184 HS



28184 RG



28184 RK

Components / Spare Parts

Catalog page

28180 GAN SNAPPER® SHOULDER PRO® Suture Forceps

140

28180 GCN SNAPPER® SHOULDER PRO® Suture Forceps

140

28180 GLN SNAPPER® SHOULDER PRO® Suture Forceps

140

28180 GRN SNAPPER® SHOULDER PRO® Suture Forceps

140

28180 GRGN SNAPPER® SHOULDER PRO® Suture Forceps

140



Spare Parts



28571 LK Set of LUER Caps, silicone, reusable, unsterile, package of 10




8029491 LUER Cap, metal, reusable, unsterile

Instruments for the Shoulder

SHOULDER PRO® Suture Forceps Attachments,
Knot Pusher and Suture Cutter, SILCUT® Punches,
SILGRASP® Foreign Body Graspers and Suture Graspers

Components / Spare Parts		Catalog page
28180 LA	SHOULDER PRO® Suture Forceps Attachment	141
28180 LC	SHOULDER PRO® Suture Forceps Attachment	141
28180 LL	SHOULDER PRO® Suture Forceps Attachment	141
28180 LR	SHOULDER PRO® Suture Forceps Attachment	141
28180 LRG	SHOULDER PRO® Suture Forceps Attachment	141



Spare Part



29100
Plug, for LUER-Lock irrigation connector for cleaning, black, autoclavable, package of 10

Components / Spare Parts		Catalog page
2870356 KP	Knot Pusher and Suture Cutter	142
2870356 I	Insert and Blade	
2870356 HG	Handle	



Components / Spare Parts		Catalog page
28171 KPN	SILCUT® Punch	143
28171 KUN	SILCUT® Punch	143
28171 KGN	SILGRASP® Foreign Body Grasper	143
28171 KGSN	SILGRASP® Foreign Body Grasper	143
28573 FD	SILGRASP® Foreign Body Grasper	143
28171 SGN	SILGRASP® Suture Grasper	143
28171 SGL	SILGRASP® Suture Grasper	143
28171 SGR	SILGRASP® Suture Grasper	143
28171 SHN	SILGRASP® Suture Grasper	143



Spare Parts



28571 LK
Set of LUER Caps, silicone, reusable, unsterile, package of 10



8029491
LUER Cap, metal, reusable, unsterile

Instruments for the Shoulder

SHOULDER PRO® Suture Forceps, Mallet

Components / Spare Parts

Catalog page

28180 GFN	TARPUN SHOULDER PRO® Suture Forceps	144
28180 HC	FETCHER SHOULDER PRO® Suture Forceps	144
28180 HL	FETCHER SHOULDER PRO® Suture Forceps	144
28180 HR	FETCHER SHOULDER PRO® Suture Forceps	144



Spare Parts



28571 LK
Set of LUER Caps, silicone, reusable, unsterile, package of 10




8029491
LUER Cap, metal, reusable, unsterile

Components / Spare Parts

Catalog page

28270 H	Mallet	152
---------	--------	-----



Spare Part



174701
Plastic Mallet Head

Instruments for the Hip

Evacuation Cannula, SILCUT® Punches, SILGRASP® Foreign Body Graspers, SILGRASP® Suture Grasper, Suture Forceps

Components / Spare Parts Catalog page

28140 S Evacuation Cannula 8541890 156



Spare Parts



6985691
Spring Cap



8541890
Stopcock

Components / Spare Parts Catalog page

28171 KPN SILCUT® Punch 160

28171 KUN SILCUT® Punch 160

28171 KGN SILGRASP® Foreign Body Grasper 160

28171 KGSN SILGRASP® Foreign Body Grasper 160

28573 FD SILGRASP® Foreign Body Grasper 160

28140 GA Suture Forceps 160

28171 SGD SILGRASP® Suture Grasper 160



Spare Parts



28571 LK
Set of LUER Caps, silicone,
reusable, unsterile, package
of 10



8029491
LUER Cap, metal,
reusable, unsterile

Instruments for Small and Medium Joints

SILCUT® PRO Punches, SILGRASP® PRO Grasping Forceps

Components / Spare Parts

Catalog page

28572 AD	SILCUT® PRO Punch	172
28572 ADL	SILCUT® PRO Punch	172
28572 ADR	SILCUT® PRO Punch	172
28572 AE	SILCUT® PRO Punch	172
28571 O	SILCUT® PRO Oval Biter	172



Spare Parts



28571 LK
Set of LUER Caps,
silicone, reusable,
unsterile, package of 10



8029491
LUER Cap, metal,
reusable, unsterile

Components / Spare Parts

Catalog page

28572 NJ	SILGRASP® PRO Suture Grasper	173
28572 CG	SILGRASP® PRO Cartilage Grasping Forceps	173
28572 CGU	SILGRASP® PRO Cartilage Grasping Forceps	173
28572 G	SILGRASP® PRO Grasping Forceps	173
28572 GU	SILGRASP® PRO Grasping Forceps	173
28572 AG	SILGRASP® PRO Alligator Grasping Forceps	173



Spare Parts



28571 LK
Set of LUER Caps,
silicone, reusable,
unsterile, package of 10



8029491
LUER Cap, metal,
reusable, unsterile

Instruments for Small and Medium Joints

Dilator Set, Optical Dissectors, ROBI® KELLY Grasping Forceps


Components / Spare Parts Catalog page

28147 S	Dilator Set	175
28147 SA	Dilator , diameter 4 mm	
28147 SB	Dilator , diameter 5 mm	
28147 SC	Dilator , diameter 6 mm	
28147 SD	Dilator , diameter 7 mm	



Components / Spare Parts Catalog page

50200 ES	Optical Dissector	177
50300 ES	Optical Dissector	177



Spare Parts



5916100
O-Ring



8458190
Stopcock



6052191
Locking Lever, red



8484290
Nut




6985691
Spring Cap



8069491
Outer Part, with stopcock

Components / Spare Parts Catalog page

38851 MD	ROBI® KELLY Grasping Forceps , CLERMONT-FERRAND model	179
38151	ROBI® Plastic Handle	
38810 MD	ROBI® Outer Sheath with Forceps Insert	



Spare Part




29100
Plug, for LUER-Lock irrigation connector for cleaning, black, autoclavable, package of 10

Components / Spare Parts

Catalog page

- 28272 KLA** **Holding System**
- 28172 HK **Socket**
- 28272 HA **Articulated Stand**
- 28272 UL **Clamping Jaw**

183



Spare Part




28172 HZ
Set Screw,
for articulated stands

Visualization Systems for Open Surgery and Microsurgery

VITOM® Telescopes, Rotation Socket, Articulated Stand

Components / Spare Parts	Catalog page
20916025 AA VITOM® Telescope 0° with Integrated Illuminator	193
20916025 DA VITOM® Telescope 90° with Integrated Illuminator	193
20916025 AGA VITOM® II NIR/ICG Telescope 0°, with integrated illuminator	197



Spare Parts



495 F
Receptacle,
diameter 9 mm, for
Wolf fiber optic light cable




495 G
Screw Base, for
KARL STORZ fiber optic
light cables and Olympus
Corporation

Components / Spare Parts	Catalog page
28172 HR Rotation Socket , to clamp to the operating table	201, 207, 219

Spare Part

28172 HRS
Butterfly Nut, to clamp
Socket 28172 HR to the
operating table, one
already mounted on
Socket 28172 HR




Components / Spare Parts	Catalog page
28272 HC Articulated Stand	201
28272 HB Articulated Stand	207

Spare Part



28172 HZ
Set Screw,
for articulated stands



Components / Spare Parts


Catalog page

28272 HSP **VERSACRANE™ Holding Arm**

205

28272 HS **VERSACRANE™ Holding Arm**

28272 HP **Mobile Stand**



Spare Parts for 28272 HS

ET52-202881
Cable Support, for fixation
under Cable Covers
ET52-022869 and
ET52-202868

ET52-202877
Knurled Screw, M6x16


ET52-202878
Knurled Screw, M6x25

ET52-202868
Cable Cover,
150 mm

ET52-022869
Cable Cover,
250 mm

ET52-4-6-25-00176
Handwheel Brake,
M6x0.5

ET52-4-6-25-00206
Window Cap Lift 20



Spare Parts for 28272 HP

ET52-202880
**Footswitch Protection
Cap**

ET52-4-6-25-00183
Guide Roll, braked

ET52-4-6-25-00184
Guide Roll, unbraked

Components / Spare Parts

Catalog page

TM 323 **32" 3D Monitor**

207

400 A **Mains Cord**

9826 PS **External Power Supply**

9800 GF **3D Polarization Glasses**

Cable Cover




Holding Systems

Leg Holder

Components / Spare Parts

Catalog page

- 28188 D** **Arthroscopy Leg Holder**
- 28188 SE **Release Clamp, 25 mm**
- 28188 DP **Neoprene Cushion, 600 x 140 x 20 mm**
- 28188 PN **Closure Stripe, perforated, Vulkollan 450 x 90 mm**



218

Spare Parts



28188 FH
Fixation Device



28188 HR
Hand Wheel

Components / Spare Parts

Catalog page

- 28188 SE** **Release Clamp**



218

Spare Parts



28188 FS
Locking Wheel



28188 FK
"Small Wheel"

Components / Spare Parts


Catalog page

- 28172 HR** **Rotation Socket, to clamp to the operating table**

219

Spare Part

28172 HRS
Butterfly Nut, to clamp
Socket 28172 HR to the
operating table, one
already mounted on
Socket 28172 HR



— 28172 HRS

Suction and Irrigation Systems

ARTHROPUMP® Power

Components / Spare Parts

Catalog page

28340701-1 ARTHROPUMP® Power

U 7

28340720-1 **ARTHROPUMP® Power**,
power supply 100 – 240 VAC, 50/60 Hz

28340770 **Connecting Cable**, to UNIDRIVE® S III ARTHRO SCB

20090170 **SCB Connecting Cable**, length 100 cm

20016834 **Four-Pedal Footswitch**

031328-03* **Tubing Set Irrigation**, sterile, for single use,
package of 3

031228-03* **Tubing Set Suction**, sterile, for single use,
package of 3



28340720-1

Spare Part



1069500
Fuse, T 1.6 A, L 250 V



Suction and Irrigation Systems

ENDOMAT® SELECT

Components / Spare Parts

Catalog page

UP 210 **ENDOMAT® SELECT**

U 12

400 A **Mains Cord**, length 300 cm



UP 210

Spare Parts

for single use



031523-10*
Tubing Set, irrigation, PC,
sterile, for single use,
package of 10



031647-10*
Tubing Set, suction, BS,
sterile, for single use,
package of 10



031524-10*
Tubing Set, irrigation, FC,
sterile, for single use,
package of 10



030647-10*
Tubing Set, suction, DS,
sterile, for single use,
package of 10



031529-10*
Tubing Set, irrigation, CV,
sterile, for single use,
package of 10

reusable

UP 007
Tubing Set, irrigation, FC,
sterilizable

UP 009
Tubing Set, irrigation, DS,
sterilizable

UP 008
Tubing Set, irrigation, PC,
sterilizable

UP 010
Tubing Set, irrigation,
BS, sterilizable



Motor System

UNIDRIVE® S III ARTHRO SCB

Components / Spare Parts

Catalog page

- 28723001-1 UNIDRIVE® S III ARTHRO SCB**
- 28723020-1 UNIDRIVE® S III ARTHRO SCB**
- 20090170 SCB Connecting Cable, length 100 cm**
- 400 A Mains Cord**
- 96156018D Instruction Manual**



U 17

28723020-1

Spare Parts



2027690
Mains Fuse,
220 – 240 VAC, T 4.0 AH,
package of 10



1059700
Mains Fuse,
100 – 127 VAC, T 2.5 A,
package of 10

Components / Spare Parts

Catalog page

- 28200 DX DRILLCUT-X® ARTHRO Shaver Handpiece**

U 18



Spare Parts



28200 DA
Valve Body, without valve
lock



28200 DB
Valve Lock, for Valve Body
28200 DC

High Frequency Surgery Unit

AUTOCON® III 400 High-End

Components / Spare Parts

Catalog page

UH 400 AUTOCON® III 400 High-End,
power supply 220 – 240 VAC, 50/60 Hz

U 32

400 A **Mains Cord**, length 300 cm

UH 400U AUTOCON® III 400 High-End,
power supply 100-127 VAC, 50/60 Hz

400 B **Mains Cable**, US version, length 200 cm



UH 400

Spare Part for use at 220-240 V:



1222890
Fuse,
100 – 127 VAC, T 5.0 A,
package of 10

Spare Part for use at 100-127 V:




1432095
Line Fuse,
2x 10 AH, package of 10


KARL STORZ OR1 NEO®
ERGONOMICS, SAFETY AND EFFICIENCY IN THE OR



TELEPRESENCE
IMAGING SYSTEMS - DOCUMENTATION
ILLUMINATION - VIDEOCARTS



HYGIENE
CLEANING
STERILIZATION AND MAINTENANCE
STORAGE TECHNIQUES



ENDOPROTECT1
KARL STORZ SERVICE PROGRAM



KARL STORZ OR1 NEO® ERGONOMICS, SAFETY AND EFFICIENCY IN THE OR



The KARL STORZ OR1 NEO® objective is to provide an optimal operating room design for performing minimally invasive and conventional surgeries. Customized to meet disciplinary and interdisciplinary needs, the OR1 NEO® operating room concept offers the optimal solution to each requirement for an integrated OR workstation design. The system's modular design allows all components and functionalities to be integrated in the OR1 NEO® operating room solution and, therefore, become part of the workstation system. Once again, KARL STORZ sets new standards in ergonomics, safety and efficiency in the OR.

- **System integration**
- **Data management and documentation**
- **Telemedicine**

The OR1 NEO® components provide a customized system and compatible applications. Each component offers a reliable solution on its own; the sum of all components forms a complete multifunctional system.

TELEPRESENCE

- **Imaging systems**
- **Documentation**
- **Illumination**
- **Equipment carts**



FULL HD – New Vision in Medicine

IMAGE 1 HUB™ HD offers the user the highest image quality for the precise display of even the finest tissue and vascular structures.

IMAGE 1 HUB™ HD enables the connection of the latest HD camera heads and all standard IMAGE1 camera heads.

Existing IMAGE1 can be updated to enable HD images to be displayed and HD camera heads to be utilized.

KARL STORZ WIDEVIEW monitors deliver **optimal image display**. Using the 16:10 aspect provides a larger display window and improves the viewing ergonomics.

HYGIENE

CLEANING, STERILIZATION AND MAINTENANCE, STORAGE TECHNIQUES

- Accessories for maintenance and cleaning
- Cases for cleaning and disinfection
- Quivers for disinfection and storage of flexible endoscopes
- Wire trays for cleaning, sterilization and storage of endoscopes, instruments and motor accessories
- Instrument racks for cleaning, sterilization and storage
- Plastic containers for cleaning, sterilization and storage of endoscopes
- Plastic containers for cleaning, sterilization and storage of endoscopes, camera heads and instruments
- Stainless steel trays for sterilization and storage of instruments
- Aluminium trays for sterilization and storage of instruments
- Sterilization containers with MicroStop® system
- Racks for cleaning, sterilization and storage of ENT instruments
- Aluminium cases for HOPKINS® telescopes
- Carrying cases for instruments and accessories

ENDOPROTECT1

KARL STORZ SERVICE PROGRAM

- **Repair service**
- **Set audits**
- **Training**
- **OR1™ service**
- **Hygiene**
- **ORCHESTRION® IMM**



KARL STORZ has developed and optimized a special service program for the protection of patients, users and investments: ENDOPROTECT1

ENDOPROTECT1 from KARL STORZ provides a comprehensive range of safe and cost-effective services to meet the needs of endoscopic equipment in everyday clinical practice.

ENDOPROTECT1 Service Program:
modular – safe – cost-effective

Request per Business Reply Card or per FAX

+49 (0)7461 708 404 or one of KARL STORZ distribution companies
 – checkmark – provide address – send –




If there are not enough reply cards available, KARL STORZ also offers this service in the Internet.:

www.karlstorz.com

Please cut out reply card!

Please send us detailed information: (please check):




KARL STORZ OR1 NEO®

ERGONOMICS, SAFETY AND EFFICIENCY IN THE OR

We are particularly interested in:


- System integration
- Data management and documentation
- Telemedicine



TELEPRESENCE

We are particularly interested in:

- FULL HD – New vision in medicine
- Camera systems
- Data management and documentation
- Monitors and video printers
- Light sources
- Equipment carts



HYGIENE

CLEANING, STERILIZATION AND MAINTENANCE, STORAGE TECHNIQUES



ENDOPROTECT1

KARL STORZ SERVICE PROGRAM

We are particularly interested in:

- Repair service
- Set audits
- Training
- OR1™ service
- Hygiene
- ORCHESTRION® IMM

We would like a non-binding consultancy meeting.

Appointment requested with:

Address:

Hospital/Office

Contact

Street

Postal Code

Town/City

Tel.

E-Mail



REPLY

KARL STORZ GmbH & Co. KG
 Postfach 230

78503 Tuttlingen/Germany

Request per Business Reply Card or per FAX

+49 (0)7461 708 404 or one of KARL STORZ distribution companies
– checkmark – provide address – send –



If there are not enough reply cards available, KARL STORZ
also offers this service in the Internet:

www.karlstorz.com

Please cut out reply card!

Address:

Hospital/Office

Contact

Street

Postal Code

Town/City

Tel.

E-Mail


Postage
paid

REPLY

KARL STORZ GmbH & Co. KG
Postfach 230

78503 Tuttlingen/Germany

Please send us detailed information: (please check):




KARL STORZ OR1 NEO®

ERGONOMICS, SAFETY
AND EFFICIENCY IN THE OR

We are particularly interested in:


- System integration
- Data management and documentation
- Telemedicine



TELEPRESENCE

We are particularly interested in:

- FULL HD – New vision in medicine
- Camera systems
- Data management and documentation
- Monitors and video printers
- Light sources
- Equipment carts



HYGIENE

CLEANING,
STERILIZATION AND
MAINTENANCE,
STORAGE TECHNIQUES



ENDOPROTECT1

KARL STORZ SERVICE PROGRAM

We are particularly interested in:

- Repair service
- Set audits
- Training
- OR1™ service
- Hygiene
- ORCHESTRION® IMM

We would like a non-binding consultancy meeting.

Appointment requested with:



Request per Business Reply Card or per FAX

+49 (0)7461 708 404 or one of KARL STORZ distribution companies
– checkmark – provide address on back of card – send –



Please tear off postcard here!

Catalogs, Catalog excerpts

I prefer: Print Version Digital Version (CD, DVD) (please check)

Neurosurgery <input type="checkbox"/>	Laparoscopy in Surgery, Gynecology, Urology <input type="checkbox"/>
Oral and Maxillofacial Surgery <input type="checkbox"/>	- Pediatric Laparoscopy <input type="checkbox"/>
ENT – Esophagoscopy – Bronchoscopy <input type="checkbox"/>	- Minilaparoscopy <input type="checkbox"/>
- Standard Instruments <input type="checkbox"/>	Gynecology <input type="checkbox"/>
- Laryngology <input type="checkbox"/>	- Fetoscopy <input type="checkbox"/>
- Otology <input type="checkbox"/>	Urology <input type="checkbox"/>
- Rhinology and Rhinoplasty <input type="checkbox"/>	Proctology <input type="checkbox"/>
- Sinoscopy, Rhinoscopy, Postrhinology <input type="checkbox"/>	Arthroscopy, Sports Medicine, Spine Surgery <input type="checkbox"/>
Plastic Surgery <input type="checkbox"/>	- RECON – Bone and Joint Reconstruction <input type="checkbox"/>
Anesthesiology and Emergency Medicine <input type="checkbox"/>	Microscopy <input type="checkbox"/>
- Video Intubation Systems <input type="checkbox"/>	Pediatric Surgery <input type="checkbox"/>
Endoscopes and Instruments for Cardiovascular Surgery <input type="checkbox"/>	KARL STORZ OR1 NEO® <input type="checkbox"/>
Thorax <input type="checkbox"/>	Telepresence <input type="checkbox"/>
Gastroenterology <input type="checkbox"/>	Hygiene <input type="checkbox"/>

Please tear off postcard here!

Address:

Hospital/Office

Contact

Street

Postal Code

Town/City

Tel.

E-mail

Postage
paid

REPLY

KARL STORZ GmbH & Co. KG
Postfach 230

78503 Tuttlingen/Germany

Request per Business Reply Card or per FAX

+49 (0)7461 708 404 or one of KARL STORZ distribution companies
- checkmark - provide address on back of card - send -



Please tear off postcard here!

Address:

Hospital/Office

Contact

Street

Postal Code

Town/City

Tel.

E-mail

Postage
paid

REPLY

KARL STORZ GmbH & Co. KG
Postfach 230

78503 Tuttlingen/Germany

Please tear off postcard here!

Catalogs, Catalog excerpts

I prefer: Print Version Digital Version (CD, DVD) (please check)

- | | |
|---|--|
| Neurosurgery <input type="checkbox"/> | Laparoscopy in Surgery, <input type="checkbox"/> |
| Oral and Maxillofacial Surgery <input type="checkbox"/> | Gynecology, Urology <input type="checkbox"/> |
| ENT – Esophagoscopy – Bronchoscopy <input type="checkbox"/> | - Pediatric Laparoscopy <input type="checkbox"/> |
| - Standard Instruments <input type="checkbox"/> | - Minilaparoscopy <input type="checkbox"/> |
| - Laryngology <input type="checkbox"/> | Gynecology <input type="checkbox"/> |
| - Otology <input type="checkbox"/> | - Fetoscopy <input type="checkbox"/> |
| - Rhinology and Rhinoplasty <input type="checkbox"/> | Urology <input type="checkbox"/> |
| - Sinoscopy, Rhinoscopy, Postrhinology <input type="checkbox"/> | Proctology <input type="checkbox"/> |
| Plastic Surgery <input type="checkbox"/> | Arthroscopy, Sports Medicine, <input type="checkbox"/> |
| Anesthesiology and Emergency Medicine <input type="checkbox"/> | Spine Surgery <input type="checkbox"/> |
| - Video Intubation Systems <input type="checkbox"/> | - RECON – Bone and <input type="checkbox"/> |
| Endoscopes and Instruments <input type="checkbox"/> | Joint Reconstruction <input type="checkbox"/> |
| for Cardiovascular Surgery <input type="checkbox"/> | Microscopy <input type="checkbox"/> |
| Thorax <input type="checkbox"/> | Pediatric Surgery <input type="checkbox"/> |
| Gastroenterology <input type="checkbox"/> | KARL STORZ OR1 NEO® <input type="checkbox"/> |
| | Telepresence <input type="checkbox"/> |
| | Hygiene <input type="checkbox"/> |